

PART#	SIZE	MODEL	LOAD INDEX	SPEED RATING	WEIGHT (kg)	WEIGHT (lbs)	PR/LR	Tread Depth		Std. Rim	Section Width		Overall Dia.		Max. Load		Max. Load(DURL)		Max. Air Pressure		Static Loaded Radius		Theoretical Rolling	UTQG	M+S	EAN	UPC
								(mm)	32nds		(mm)	inch	(mm)	inch	(kg)	lbs (S)	(kg)	lbs (S)	(kPa)	psi	(mm)	(inch)	Radius				
LXST2061575020	P235/75R15	LXHT-206	105	T	13.84	30.45	/	8.5	10.7	6 1/2J	235	9.3	733	28.9	925	2039	/	/	300	44	327.21	12.9	356	500AA	✓		
LXST2061670060	P215/70R16	LXHT-206	99	T	11.72	25.78	/	8.3	10.5	6 1/2J	221	8.7	708	27.9	775	1709	/	/	300	44	320.25	12.6	344	500AA	✓		
LXST2061670070	P225/70R16	LXHT-206	101	T	12.80	28.16	/	8.5	10.7	6 1/2J	228	9.0	722	28.4	828	1819	/	/	300	44	325.71	12.8	350	500AA	✓		
LXST2061670080	P235/70R16	LXHT-206	107	T	14.04	30.89	/	8.5	10.7	7J	240	9.4	736	29.0	975	2149	/	/	340	49	331.17	13.0	357	500AA	✓		
LXST2061670090	P245/70R16	LXHT-206	106	T	14.87	32.71	/	8.5	10.7	7J	248	9.8	750	29.5	950	2094	/	/	300	44	336.63	13.3	364	500AA	✓		
LXST2061670100	P255/70R16	LXHT-206	109	T	15.63	34.39	/	8.5	10.7	7 1/2J	260	10.2	764	30.1	1030	2271	/	/	300	44	342.09	13.5	371	500AA	✓		
LXST2061670110	P265/70R16	LXHT-206	111	T	16.34	35.95	/	8.5	10.7	8J	272	10.7	778	30.6	1090	2403	/	/	300	44	347.55	13.7	378	500AA	✓		
LXST2061675020	LT225/75R16	LXHT-206	115/112	S	16.23	35.71	10PR/LRE	9.9	12.5	6J	223	8.8	744	29.3	1215	2680	1120	2470	550	80	334.29	13.2	361	/	✓		
LXST2061685020	LT235/85R16	LXHT-206	120/116	Q	18.23	40.11	10PR/LRE	9.9	12.5	6 1/2J	235	9.3	806	31.7	1380	3042	1260	2778	550	80	358.47	14.1	391	/	✓		
LXST2061675010	LT245/75R16	LXHT-206	120/116	S	18.07	39.75	10PR/LRE	10.7	13.5	7J	248	9.8	774	30.5	1380	3042	1260	2778	550	80	345.99	13.6	376	/	✓		
LXST2061675030	LT265/75R16	LXHT-206	123/120	Q	21.31	46.98	10PR/LRE	10.7	13.5	7 1/2J	267	10.5	804	31.7	1550	3415	1400	3085	550	80	358.26	14.1	390	/	✓		
LXST2061760010	P215/60R17	LXHT-206	96	H	11.58	25.48	/	8.5	10.7	6 1/2J	221	8.7	690	27.0	710	1565	/	/	300	44	316.64	12.5	335	500AA	✓		
LXST2061765010	P215/65R17	LXHT-206	98	T	12.11	26.64	/	8.5	10.7	6 1/2J	221	8.7	712	28.0	750	1653	/	/	300	44	325.22	12.8	346	500AA	✓		
LXST2061765020	P225/65R17	LXHT-206	102	T	13.05	28.71	/	8.5	10.7	6 1/2J	228	9.0	724	28.5	850	1874	/	/	300	44	329.90	13.0	351	500AA	✓		
LXST2061765030	P235/65R17	LXHT-206	103	T	13.34	29.35	/	8.5	10.7	7J	240	9.4	738	29.1	875	1929	/	/	300	44	335.36	13.2	358	500AA	✓		
LXST2061765040	P245/65R17	LXHT-206	105	T	14.86	32.69	/	8.5	10.7	7J	248	9.8	750	29.5	925	2039	/	/	300	44	340.04	13.4	364	500AA	✓		
LXST2061765050	P255/65R17	LXHT-206	110	H	15.32	33.70	/	8.5	10.7	7 1/2J	260	10.2	764	30.1	1060	2337	/	/	300	44	345.50	13.6	371	500AA	✓		
LXST2061765060	P265/65R17	LXHT-206	110	T	16.48	36.26	/	8.5	10.7	8J	272	10.7	776	30.6	1060	2337	/	/	300	44	350.18	13.8	377	500AA	✓		
LXST2061770050	P265/70R17	LXHT-206	113	T	17.26	37.97	/	8.5	10.7	8J	272	10.7	804	31.7	1150	2535	/	/	300	44	402.00	15.8	390	500AA	✓		
LXST2061780010	LT235/80R17	LXHT-206	120/117	Q	18.69	41.20	10PR/LRE	9.9	12.5	6 1/2J	235	9.3	808	31.8	1400	3085	1285	2835	550	80	362.62	14.3	392	/	✓		
LXST2061770030	LT245/70R17	LXHT-206	119/116	S	18.35	40.45	10PR/LRE	10.7	13.5	7J	248	9.8	776	30.6	1360	3000	1250	2755	550	80	350.14	13.8	377	/	✓		
LXST2061775010	LT245/75R17	LXHT-206	121/118	Q	19.63	43.28	10PR/LRE	10.7	13.5	7J	248	9.8	800	31.5	1450	3195	1320	2910	550	80	359.50	14.2	388	/	✓		
LXST2061770040	LT265/70R17	LXHT-206	121/118	Q	21.78	48.02	10PR/LRE	10.7	13.5	8J	272	10.7	804	31.7	1450	3195	1320	2910	550	80	361.06	14.2	390	/	✓		
LXST2061860030	P235/60R18	LXHT-206	102	T	13.89	30.56	/	8.5	10.7	7J	240	9.4	739	29.1	850	1874	/	/	300	44	338.55	13.3	359	500AA	✓		
LXST2061865040	P235/65R18	LXHT-206	104	T	14.4	31.68	/	8.5	10.7	7J	240	9.4	763	30.0	900	1984	/	/	300	44	347.91	13.7	370	500AA	✓		
LXST2061870010	LT265/70R18	LXHT-206	124/121	S	22.21	48.86	10PR/LRE	10.7	13.5	8J	272	10.7	829	32.6	1600	3525	1450	3195	550	80	373.65	14.7	402	/	✓		
LXST2061865030	LT275/65R18	LXHT-206	123/120	S	22.10	48.62	10PR/LRE	11.5	14.5	8J	279	11.0	815	32.1	1550	3415	1400	3085	550	80	368.19	14.5	396	/	✓		
LXST2061870020	LT275/70R18	LXHT-206	125/122	S	22.53	49.57	10PR/LRE	11.7	14.7	8J	279	11.0	843	33.2	1650	3640	1500	3305	550	80	379.11	14.9	409	/	✓		
LXST2062055010	275/55R20	LXHT-206	117	H	18.16	39.95	/	8.9	11.2	8 1/2J	284	11.2	810	31.9	1285	2833	/	/	340	49	371.82	14.6	393	500AA	✓		
LXST2062060010	275/60R20	LXHT-206	114	T	19.79	43.54	/	8.9	11.2	8J	279	11.0	838	33.0	1180	2601	/	/	300	44	382.74	15.1	407	500AA	✓		
LXST2062060020	LT265/60R20	LXHT-206	121/118	S	21.40	47.08	10PR/LRE	10.7	13.5	8J	272	10.7	826	32.5	1450	3195	1320	2910	550	80	378.06	14.9	401	/	✓		
LXST2062065010	LT275/65R20	LXHT-206	126/123	S	24.46	53.81	10PR/LRE	11.5	14.5	8J	279	11.0	866	34.1	1700	3750	1550	3415	550	80	393.66	15.5	420	/	✓		
LXST2062060030	LT285/60R20	LXHT-206	125/122	S	23.92	52.62	10PR/LRE	11.5	14.5	8 1/2J	292	11.5	850	33.5	1650	3640	1500	3305	550	80	387.42	15.3	413	/	✓		

Looking for dependable wheels and tires? Rely on Lexani for quality and long-lasting products.