

Brand	PART NO.	Ring Size	Pattern	Load Index	Speed Rating	PR/LR	Tread Depth (mm)	32nds	Std. Rim	UTQG	Section Width (mm)	inch	Overall Dia. (mm)	inch	Max Load Single (kg)	lbs (S)	Max Air Pressure (kPa)	psi	Static Loaded Radius (mm)	inch	Theoretical Rolling Radius	M+S	Weight (kg)	
LIONHART	LHSLC16010	16	LT265/75R16	LIONCLAW MT	123/120	N/A	10/E	12.3	15.5	7½J	/	267	10.5	810	31.9	1550	3415	550	80	N/A	N/A	N/A	√	N/A
LIONHART	LHSLC17020	17	35×12.50R17LT	LIONCLAW MT	121	N/A	10/E	16.3	20.5	10J	/	318	12.5	883	34.8	1450	3195	450	65	N/A	N/A	N/A	√	N/A
LIONHART	LHSLC17010	17	LT295/70R17	LIONCLAW MT	121/118	N/A	10/E	14.8	18.5	8½J	/	299	11.8	852	33.5	1450	3195	550	80	N/A	N/A	N/A	√	N/A
LIONHART	LHSLC18020	18	33×12.50R18LT	LIONCLAW MT	118	N/A	10/E	16.3	20.5	10J	/	318	12.5	832	32.8	1320	2910	450	65	N/A	N/A	N/A	√	N/A
LIONHART	LHSLC18010	18	35×12.50R18LT	LIONCLAW MT	118	N/A	8/D	16.3	20.5	10J	/	318	12.5	883	34.8	1320	2910	350	50	N/A	N/A	N/A	√	N/A
LIONHART	LHSLC20010	20	33×12.50R20LT	LIONCLAW MT	114	N/A	10/E	16.3	20.5	10J	/	318	12.5	832	32.8	1180	2600	450	65	N/A	N/A	N/A	√	N/A
LIONHART	LHSLC20020	20	35×12.50R20LT	LIONCLAW MT	121	N/A	10/E	16.3	20.5	10J	/	318	12.5	883	34.8	1450	3195	450	65	N/A	N/A	N/A	√	N/A

Looking for dependable wheels and tires? Rely on Lionhart for quality and long-lasting products.