



20040 ATF ADDITIVE 250ml

Liqui Moly GmbH

Chemwatch: **52-9730** Version No: **2.1.1.1**

Safety Data Sheet according to OSHA HazCom Standard (2012) requirements

Chemwatch Hazard Alert Code: 1

Issue Date: **17/08/2015** Print Date: **29/11/2016** S.GHS.USA.EN

SECTION 1 IDENTIFICATION

Product Identifier

Product name	20040 ATF ADDITIVE 250ml
Synonyms	Item No: 20040
Other means of identification	Not Available

Recommended use of the chemical and restrictions on use

Relevant identified uses

Use according to manufacturer's directions. Additives.

SECTION 2 HAZARD(S) IDENTIFICATION

Classification of the substance or mixture

CHEMWATCH HAZARD RATINGS

	Min Ma	X
Flammability	1	
Toxicity	0	
Body Contact	1	
Reactivity	1	
Chronic	1	





Note: The hazard category numbers found in GHS classification in section 2 of this SDSs are NOT to be used to fill in the NFPA 704 diamond. Blue = Health Red = Fire Yellow = Reactivity White = Special (Oxidizer or water reactive substances)

Classification Eye Irritation Category 2B, Acute Aquatic Hazard Category 3, Chronic Aquatic Hazard Category 3

Label elements

GHS label elements	Not Applicable
SIGNAL WORD	WARNING

Hazard statement(s)

H320	Causes eye irritation
H412	Harmful to aquatic life with long lasting effects.

Hazard(s) not otherwise specified

Not Applicable

Precautionary statement(s) Prevention

P273	Avoid release to
P2/3	Avoid release to

Avoid release to the environment.

Chemwatch: 52-9730 Page 2 of 8 Issue Date: 17/08/2015 Version No: 2.1.1.1 Print Date: 29/11/2016

20040 ATF ADDITIVE 250ml

Wash all exposed external body areas thoroughly after handling.

Precautionary statement(s) Response

P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	
P337+P313	If eye irritation persists: Get medical advice/attention.	

Precautionary statement(s) Storage

Not Applicable

Precautionary statement(s) Disposal

Dispose of contents/container in accordance with local regulations.

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
64742-56-9.	10-40	paraffinic distillate, light, solvent-dewaxed (severe)
Not Available	1-10	thiophene, tetrahydro-1,1-dioxide, 3-(C9-11 branched alkyloxy) derive.
Not Available	1-<10	methacrylate copolymer
Not Available	0.1-<1	alkyl alkoxyamine
Not Available	0.1-<1	alkyl methacrylate
125643-61-0	1-10	3,5-di-tert-butyl-4-hydroxy hydrocinnamic acid, C7-9 ester
Not Available	0.1-<2	long-chained alkylamine, alkoxylated
Not Available	0.1-<1	alkyl dithio thiadiazole

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

SECTION 4 FIRST-AID MEASURES

Description of first aid measures

Eye Contact	If this product comes in contact with the eyes: Wash out immediately with fresh running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Seek medical attention without delay; if pain persists or recurs seek medical attention. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin contact occurs: ► Immediately remove all contaminated clothing, including footwear. ► Flush skin and hair with running water (and soap if available). ► Seek medical attention in event of irritation.
Inhalation	 If fumes, aerosols or combustion products are inhaled remove from contaminated area. Other measures are usually unnecessary.
Ingestion	 Immediately give a glass of water. First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

Most important symptoms and effects, both acute and delayed

See Section 11

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

- Heavy and persistent skin contamination over many years may lead to dysplastic changes. Pre-existing skin disorders may be aggravated by exposure to this product.
- In general, emesis induction is unnecessary with high viscosity, low volatility products, i.e. most oils and greases
- High pressure accidental injection through the skin should be assessed for possible incision, irrigation and/or debridement.

NOTE: Injuries may not seem serious at first, but within a few hours tissue may become swollen, discoloured and extremely painful with extensive subcutaneous necrosis. Product may be forced through considerable distances along tissue planes.

SECTION 5 FIRE-FIGHTING MEASURES

Extinguishing media

- ▶ Foam.
- Dry chemical powder.
- ▶ BCF (where regulations permit).
- Carbon dioxide.

Special hazards arising from the substrate or mixture

Fire Incompatibility ▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result Chemwatch: 52-9730 Page 3 of 8 Issue Date: 17/08/2015 Version No: 2.1.1.1 Print Date: 29/11/2016

20040 ATF ADDITIVE 250ml

▶ Alert Fire Brigade and tell them location and nature of hazard. ▶ Wear full body protective clothing with breathing apparatus. Fire Fighting ▶ Prevent, by any means available, spillage from entering drains or water course. ▶ Use water delivered as a fine spray to control fire and cool adjacent area. Combustible. ▶ Slight fire hazard when exposed to heat or flame. ▶ Heating may cause expansion or decomposition leading to violent rupture of containers. ▶ On combustion, may emit toxic fumes of carbon monoxide (CO). Combustion products include: carbon dioxide (CO2) Fire/Explosion Hazard nitrogen oxides (NOx) phosphorus oxides (POx) sulfur oxides (SOx) other pyrolysis products typical of burning organic material. May emit corrosive fumes CARE: Water in contact with hot liquid may cause foaming and a steam explosion with wide scattering of hot oil and possible severe burns. Foaming may cause overflow of containers and may result in possible fire.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	Slippery when spilt. Remove all ignition sources. Clean up all spills immediately. Avoid breathing vapours and contact with skin and eyes. Control personal contact with the substance, by using protective equipment.
Major Spills	Slippery when spilt. Moderate hazard. Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling

Safe handling	 DO NOT allow clothing wet with material to stay in contact with skin Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. Prevent concentration in hollows and sumps.
Other information	 Store in original containers. Keep containers securely sealed. No smoking, naked lights or ignition sources. Store in a cool, dry, well-ventilated area.

Conditions for safe storage, including any incompatibilities

Suitable container	 Metal can or drum Packaging as recommended by manufacturer. Check all containers are clearly labelled and free from leaks.
Storage incompatibility	CARE: Water in contact with heated material may cause foaming or a steam explosion with possible severe burns from wide scattering of hot material. Resultant overflow of containers may result in fire. Avoid reaction with oxidising agents

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
US OSHA Permissible Exposure Levels (PELs) - Table Z1	paraffinic distillate, light, solvent-dewaxed (severe)	Oil mist, mineral	5 mg/m3	Not Available	Not Available	Not Available
US ACGIH Threshold Limit Values (TLV)	paraffinic distillate, light, solvent-dewaxed (severe)	Mineral oil, excluding metal working fluids - Pure, highly and severely refined / Mineral oil, excluding metal working fluids - Poorly and mildly refined	5 mg/m3	Not Available	Not Available	TLV® Basis: URT irr

Chemwatch: 52-9730 Page 4 of 8 Issue Date: 17/08/2015 Version No: 2.1.1.1 Print Date: 29/11/2016

20040 ATF ADDITIVE 250ml

US NIOSH Recommended Exposure Limits (RELs)	paraffinic distillate, light, solvent-dewaxed (severe)	Heavy mir	neral oil mist, Paraffin oil mist,	White mine	eral oil mist	5 mg/m3	10 mg/m3	Not Available	Not Available
EMERGENCY LIMITS									
Ingredient	Material name		TEEL-1		TEEL-2			TEEL-3	
20040 ATF ADDITIVE 250ml	Not Available		Not Available		Not Available			Not Available	
Ingredient	Original IDLH			R	evised IDLH				
paraffinic distillate, light, solvent-dewaxed (severe)	Not Available			N	ot Available				
thiophene, tetrahydro- 1,1-dioxide, 3-(C9-11 branched alkyloxy) derive.	Not Available			N	ot Available				
methacrylate copolymer	Not Available			N	ot Available				
alkyl alkoxyamine	Not Available			N	ot Available				
alkyl methacrylate	Not Available			N	ot Available				
3,5-di-tert-butyl-4-hydroxy hydrocinnamic acid, C7-9 ester	Not Available			N	ot Available				
long-chained alkylamine, alkoxylated	Not Available			N	ot Available				
alkyl dithio thiadiazole	Not Available			N	ot Available				

Exposure controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. Appropriate engineering The basic types of engineering controls are: controls

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.

Personal protection









Eye and face protection

- Safety glasses with side shields.
- Chemical goggles
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task

Skin protection

See Hand protection below

- ▶ Wear chemical protective gloves, e.g. PVC.
- ▶ Wear safety footwear or safety gumboots, e.g. Rubber

Hands/feet protection

The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final

Personal hygiene is a key element of effective hand care.

Body protection

See Other protection below

Other protection

- Overalls.
- ▶ P.V.C. apron. Barrier cream.
- Thermal hazards

Not Available

Respiratory protection

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required. Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	A-AUS P2	-	A-PAPR-AUS / Class 1 P2
up to 50 x ES	-	A-AUS / Class 1 P2	-
up to 100 x ES	-	A-2 P2	A-PAPR-2 P2 ^

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content. The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.

Chemwatch: 52-9730

20040 ATF ADDITIVE 250ml

Page 5 of 8 Issue Date: 17/08/2015 Version No: 2.1.1.1 Print Date: 29/11/2016

Information on basic physical and chemical properties

Appearance	Brown colour liquid with characteristic odour; not miscible with water.		
Physical state	Liquid	Relative density (Water = 1)	0.888
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Applicable	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	166 (40C), 26 (100C)
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water (g/L)	Immiscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	 Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

Inhaled	Inhalation hazard is increased at higher temperatures. Inhalation of oil droplets or aerosols may cause discomfort and may produce chemical inflammation of the lungs.
Ingestion	The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence.
Skin Contact	Open cuts, abraded or irritated skin should not be exposed to this material The material may accentuate any pre-existing dermatitis condition Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected. The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.
Eye	The material may be irritating to the eye, with prolonged contact causing inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.
Chronic	Long-term exposure to the product is not thought to produce chronic effects adverse to the health (as classified by EC Directives using animal models); nevertheless exposure by all routes should be minimised as a matter of course.

20040 ATF ADDITIVE 250ml	TOXICITY Not Available	IRRITATION Not Available
paraffinic distillate, light, solvent-dewaxed (severe)	TOXICITY	IRRITATION Not Available
	Inhalation (rat) LC50: 10.5 mg/l/4hr ^[1]	

Chemwatch: 52-9730 Page 6 of 8 Issue Date: 17/08/2015 Version No: 2.1.1.1 Print Date: 29/11/2016

20040 ATF ADDITIVE 250ml

	Inhalation (rat) LC50: 5.7 mg/l/4hr ^[1] Inhalation (rat) LC50: 9.6 mg/l/4hr ^[1] Oral (rat) LD50: >2000 mg/kg ^[1]	
3,5-di-tert-butyl-4-hydroxy hydrocinnamic acid, C7-9 ester	TOXICITY Oral (rat) LD50: >200 mg/kg ^[2]	IRRITATION Eye (rabbit: non-irritating * Skin (rat): non-irritating *
Legend:	Value obtained from Europe ECHA Registered Substances - Acute toxicity 2 extracted from RTECS - Register of Toxic Effect of chemical Substances	.* Value obtained from manufacturer's SDS. Unless otherwise specified data

No significant acute toxicological data identified in literature search.

The materials included in the Lubricating Base Oils category are related from both process and physical-chemical perspectives;

The potential toxicity of a specific distillate base oil is inversely related to the severity or extent of processing the oil has undergone, since:

- The adverse effects of these materials are associated with undesirable components, and
- ▶ The levels of the undesirable components are inversely related to the degree of processing;
- Distillate base oils receiving the same degree or extent of processing will have similar toxicities;
- ► The potential toxicity of *residual base oils* is independent of the degree of processing the oil receives.
- ▶ The reproductive and developmental toxicity of the distillate base oils is inversely related to the degree of processing.

Unrefined & mildly refined distillate base oils contain the highest levels of undesirable components, have the largest variation of hydrocarbon molecules and have shown the highest potential carcinogenic and mutagenic activities. Highly and severely refined distillate base oils are produced from unrefined and mildly refined oils by removing or transforming undesirable components.

For highly and severely refined distillate base oils:

In animal studies, the acute, oral, semilethal dose is >5g/kg body weight and the semilethal dose by skin contact is >2g/kg body weight. The semilethal concentration for inhalation is 2.18 to >4 mg/L. The materials have varied from "non-irritating" to "moderately irritating" when tested for skin and eye irritation. Testing for sensitisation has been negative.

The substance is classified by IARC as Group 3:

NOT classifiable as to its carcinogenicity to humans.

Evidence of carcinogenicity may be inadequate or limited in animal testing.

3,5-DI-TERT-BUTYL-4-HYDROXY HYDROCINNAMIC ACID, C7-9 ESTER

PARAFFINIC DISTILLATE.

LIGHT, SOLVENT-

DEWAXED (SEVERE)

Non-sensirising to guinea pig skin * Everspring Chemical MSDS

Acute Toxicity	0	Carcinogenicity	0
Skin Irritation/Corrosion	0	Reproductivity	0
Serious Eye Damage/Irritation	✓	STOT - Single Exposure	0
Respiratory or Skin sensitisation	0	STOT - Repeated Exposure	0
Mutagenicity	0	Aspiration Hazard	0

- 🗶 Data available but does not fill the criteria for classification
- 🗸 Data required to make classification available O - Data Not Available to make classification

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

Ingredient	Endpoint	Test Duration (hr)	Species	Value	Source
paraffinic distillate, light, solvent-dewaxed (severe)	EC50	48	Crustacea	>1000mg/L	1
paraffinic distillate, light, solvent-dewaxed (severe)	EC50	48	Crustacea	>1000mg/L	1
paraffinic distillate, light, solvent-dewaxed (severe)	NOEC	504	Crustacea	>1mg/L	1
3,5-di-tert-butyl-4-hydroxy hydrocinnamic acid, C7-9 ester	LC50	96	Fish	>0.0011mg/L	2
3,5-di-tert-butyl-4-hydroxy hydrocinnamic acid, C7-9 ester	EC50	48	Crustacea	>0.0082mg/L	2
3,5-di-tert-butyl-4-hydroxy hydrocinnamic acid, C7-9 ester	EC50	72	Algae or other aquatic plants	>0.00018mg/L	2
3,5-di-tert-butyl-4-hydroxy hydrocinnamic acid, C7-9 ester	EC50	72	Algae or other aquatic plants	>0.00018mg/L	2
3,5-di-tert-butyl-4-hydroxy hydrocinnamic acid, C7-9 ester	NOEC	72	Algae or other aquatic plants	0.00014mg/L	2

Chemwatch: 52-9730 Page 7 of 8 Issue Date: 17/08/2015 Version No: 2.1.1.1 Print Date: 29/11/2016

20040 ATF ADDITIVE 250ml

Legend:

Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 -Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) -Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

Harmful to aquatic organisms.

May cause long-term adverse effects in the aquatic environment.

Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters

Wastes resulting from use of the product must be disposed of on site or at approved waste sites.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
	No Data available for all ingredients	No Data available for all ingredients

Bioaccumulative potential

Ingredient	Bioaccumulation
	No Data available for all ingredients

Mobility in soil

Ingredient	Mobility
	No Data available for all ingredients

SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

▶ DO NOT allow wash water from cleaning or process equipment to enter drains.

- ▶ It may be necessary to collect all wash water for treatment before disposal.
- ▶ In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
- Product / Packaging Where in doubt contact the responsible authority.
 - ▶ Recycle wherever possible or consult manufacturer for recycling options.
 - Consult State Land Waste Authority for disposal.
 - Bury or incinerate residue at an approved site.
 - Recycle containers if possible, or dispose of in an authorised landfill.

SECTION 14 TRANSPORT INFORMATION

disposal

Labels Required

Marine Pollutant

Land transport (DOT): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

PARAFFINIC DISTILLATE, LIGHT, SOLVENT-DEWAXED (SEVERE)(64742-56-9.) IS FOUND ON THE FOLLOWING REGULATORY LISTS

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs	US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air Contaminants
US - Alaska Limits for Air Contaminants	US - Washington Permissible exposure limits of air contaminants
US - California Permissible Exposure Limits for Chemical Contaminants	US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants
US - California Proposition 65 - Carcinogens	US ACGIH Threshold Limit Values (TLV)
US - Hawaii Air Contaminant Limits	US ACGIH Threshold Limit Values (TLV) - Carcinogens
US - Idaho - Limits for Air Contaminants	US National Toxicology Program (NTP) 13th Report Part A Known to be Human Carcinogens
US - Michigan Exposure Limits for Air Contaminants	US NIOSH Recommended Exposure Limits (RELs)
US - Minnesota Permissible Exposure Limits (PELs)	US OSHA Permissible Exposure Levels (PELs) - Table Z1
US - Oregon Permissible Exposure Limits (Z-1)	US Priority List for the Development of Proposition 65 Safe Harbor Levels - No Significant Risk
US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants	Levels (NSRLs) for Carcinogens and Maximum Allowable Dose Levels (MADLs) for
US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants	Chemicals Causing Reproductive Toxicity
	US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

3,5-DI-TERT-BUTYL-4-HYDROXY HYDROCINNAMIC ACID, C7-9 ESTER(125643-61-0) IS FOUND ON THE FOLLOWING REGULATORY LISTS

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

Federal Regulations

Superfund Amendments and Reauthorization Act of 1986 (SARA)

20040 ATF ADDITIVE 250ml

SECTION 311/312 HAZARD CATEGORIES

Immediate (acute) health hazard	Yes
Delayed (chronic) health hazard	No
Fire hazard	No
Pressure hazard	No
Reactivity hazard	No

US. EPA CERCLA HAZARDOUS SUBSTANCES AND REPORTABLE QUANTITIES (40 CFR 302.4)

None Reported

State Regulations

US. CALIFORNIA PROPOSITION 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm

US - CALIFORNIA PREPOSITION 65 - CARCINOGENS & REPRODUCTIVE TOXICITY (CRT): LISTED SUBSTANCE

Soots, tars, and mineral oils (untreated and mildly treated oils and used engine oils) Listed

National Inventory	Status
Australia - AICS	Υ
Canada - DSL	Y
Canada - NDSL	N (paraffinic distillate, light, solvent-dewaxed (severe); 3,5-di-tert-butyl-4-hydroxy hydrocinnamic acid, C7-9 ester)
China - IECSC	Υ
Europe - EINEC / ELINCS / NLP	N (3,5-di-tert-butyl-4-hydroxy hydrocinnamic acid, C7-9 ester)
Japan - ENCS	N (paraffinic distillate, light, solvent-dewaxed (severe); 3,5-di-tert-butyl-4-hydroxy hydrocinnamic acid, C7-9 ester)
Korea - KECI	Υ
New Zealand - NZIoC	Y
Philippines - PICCS	Υ
USA - TSCA	Υ
Legend:	Y = All ingredients are on the inventory N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

SECTION 16 OTHER INFORMATION

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

PC-TWA: Permissible Concentration-Time Weighted Average

PC-STEL: Permissible Concentration-Short Term Exposure Limit

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit.

IDLH: Immediately Dangerous to Life or Health Concentrations

OSF: Odour Safety Factor

NOAEL :No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value LOD: Limit Of Detection OTV: Odour Threshold Value

BCF: BioConcentration Factors BEI: Biological Exposure Index