



GR014	Plastic Tube, 8 oz 078698217857
GR018	Plastic Tube, 14 oz 078698219950

WHITE LITHIUM GREASE

Creates long-lasting, heavy-duty lubrication, provides a thick grease coat, does not freeze, melt, or run. This is a lithium 12-hydroxystearate thickened lubricating grease formulated in high quality base oils. White Lithium Grease is fortified with extreme pressure (EP) and anti-wear additives as well as oxidation and corrosive inhibitors. White Lithium Grease is formulated to meet the needs of a multi-purpose lubricating grease.

APPLICATIONS:

- General purpose grease
- For light-to-medium duty lubrication
- For farm, home and shop
- Lubricates rolling parts, linkages, levers

TYPICAL PROPERTIES:

NLGI Grade: 2	Penetration, ASTM D 217, worked 60: 265 - 295
NLGI Certification: LB	Dropping Point, °F (°C), Minimum, ASTM D 2265: 360 (182)
Soap Type: Lithium 12 Hydroxy	Timken OK Loads, ASTM D 2509: 50
Texture: Smooth	4-Ball Weld Load, ASTM D 2596, kg: 250
Color: White	Oil Separation, ASTM D 1742, % Loss: 1
Base Oil Properties	Water Washout, ASTM D 1264, % Loss: 5
Viscosity @ 100°F, SUS: 700 - 800	Corrosion Prevention, ASTM D 1743: Pass
Viscosity @ 210°F, SUS: 60 - 70	Average Particle Size: < 50 Micron
Viscosity @ 40°C, cSt: 140 - 150	
Viscosity @ 100°C, cSt: 10 - 12	

DANGER: IMPORTANT: Do not mix greases of different types. Thoroughly remove old grease before applying. **CAUTION:** May cause eye and skin irritation. Avoid contact with eyes and prolonged or repeated contact with skin. Wash hands after using product. May be harmful if swallowed.

FIRST AID: IF SWALLOWED: DO NOT induce vomiting. Contact poison control center, physician, or hospital emergency room immediately. **IN EYES:** Rinse with water for 15 minutes. Seek medical attention if irritation develops.

KEEP AWAY FROM CHILDREN AND ANIMALS

NOTICE: While this information is presented in good faith and believed to be accurate, Radiator Specialty Company does not guarantee satisfactory results from reliance thereon. The data is offered solely for your information and Radiator Specialty Company disclaims all liability for any loss or damage from its use. Thoroughly test any application according to the product directions and independently conclude satisfactory performance. Nothing contained herein is to be construed as a recommendation to use the product in violation of any patent.