

# MATERIAL SAFETY DATA SHEET - 8 Point

## SECTION 1 – PRODUCT INFORMATION

### Mascoat

**Product Name:** LizardSkin Sound Control  
**Product ID:** LSSC  
**Common Chemical Name:** Acrylic Insulation Emulsion  
**Synonyms:** None  
**Molecular Formula:** Mixture

Sound Damping Material	
<b>HEALTH</b>	<b>1</b>
<b>FLAMMABILITY</b>	<b>0</b>
<b>PHYSICAL HAZARD</b>	<b>0</b>
<b>Personnel Protection</b>	<b>G</b>
Eye protection Gloves Dust mask/Respirator	

## SECTION 2 – HAZARDOUS INGREDIENTS DETERMINED BY OSHA

<u>Cas Number</u>	<u>Ingredients</u>	<u>% Range</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>
	NONE as determined by OSHA standards			

## SECTION 3 – PHYSICAL PROPERTIES

<b>Color:</b>	Dark Grey/Black	<b>Form/Appearance:</b>	Thick emulsion mixture
<b>Odor (wet):</b>	Slight ammonia	<b>Melting Point:</b>	N/A
<b>Boiling Point:</b>	No boiling point	<b>Evaporation Rate (Butyl Ace =1):</b>	<1
<b>Freeze Point</b>	32°F (0°C)	<b>Solubility in H2O:</b>	Dilutable
<b>Specific Gravity:</b>	1.64 g/cm <sup>3</sup>	<b>Volume Solids:</b>	50-55%
<b>Pounds/Gallon (wet):</b>	13.71	<b>VOC Content:</b>	0.27 lbs/gal. (32 g/l)
<b>Non Volatile Solids (weight):</b>	72%		

## SECTION 4 – FIRE FIGHTING MEASURES

**Flash Point:** Noncombustible  
**Auto ignition:** N/A  
**Extinguished Media:** (for dried film) carbon dioxide, dry chemical, or alcohol foam.  
**Special Fire Fighting Procedures:** Full protective equipment including self-contained breathing apparatus should be used. Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure buildup.  
**Unusual Fire and Explosion:** Product will not burn but may spatter if temperature exceeds boiling point. Extreme heat may cause closed containers to burst. Dried film of product will not burn, but decomposition products include carbon monoxide and other hydrocarbons.

## SECTION 5 – REACTIVITY DATA

**Stability Data:** Stable  
**Incompatibility:** Solvents will coagulate the product.  
**Conditions or Hazards to Avoid:** Extreme temperatures above 500°F (260°C)  
**Hazardous Decomposition:** Hazardous polymerization will not occur.  
**Corrosive Properties:** Not corrosive  
**Oxidizer Properties:** Not an oxidizer  
**Chloride Properties:** None

## SECTION 6 – HEALTH HAZARD AND FIRST AID DATA

**Routes of entry:** skin-possible                      ingestion-possible                      inhalation-possible  
**Health Hazards** Acute - In a confined area vapors in high concentration can bother some personnel.  
 Extended periods of exposure without PP may result in health concerns.

## SECTION 6 – HEALTH HAZARD AND FIRST AID DATA (cont)

**First aid procedure:** **Eye exposure** - flush eyes with water immediately. Get immediate medical attention.  
**Skin contact** - wash area with soap and water. If redness persists, seek medical attention  
**Ingestion** – If swallowed, dilute with water. **DO NOT INDUCE VOMITING.** Never give fluids or induce vomiting if the victim is unconscious or having convulsions. Get immediate medical attention.  
**Inhalation** – Move to fresh air. Aid in breathing if needed and get immediate medical attention.  
**Notes to Physicians** – none known.  
**Aggravated Medical Attention** – No data is available at this time which addresses medical conditions that are generally recognized as being aggravated by exposure to this product. Please refer to the effects of overexposure section for effects (if any) observed in animals.  
**Special Precautions** – No

**SECTION 7 – ACCIDENTAL RELEASE MEASURES**

**Steps if material is released:** Spills should be contained and placed in suitable containers for disposal by a licensed facility.  
**Waste Disposal Methods:** Waste from this material is not hazardous as defined by the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Incinerate in approved facility. Do not incinerate closed containers. Dispose of in accordance with Federal, State, and Local regulations.  
**Precaution in handling and storage:** Use only with adequate ventilation. Avoid breathing vapor and spray mist. Avoid contact with skin and eyes. Wash hands after using. Protect against dust which may be generated by sanding or abrading the dried film.  
**Other Precautions:** Keep container closed when not in use. Transfer only to approved containers with complete and appropriate labeling. Do not take internally. *Keep out of reach of children.*  
**General:** Protect from freezing.  
**Other:** Keep out of direct sunlight in storage area

**SECTION 8 – PERSONNEL PROTECTION**

**Clothing:** Coveralls or an apron recommended.  
**Respiratory Protection:** Ventilation and dust mask recommended during application. If sprayed in confined area with little ventilation, respiratory equipment is recommended due to slight ammonia odor.  
**Ventilation:** Local exhaust - *preferable* Mechanical (gen) - *acceptable*  
**Protective Gloves:** Preferred.  
**Eye Protection:** Spectacles with unperforated sideshields.  
**Other Protective Equipment:** None needed

**OTHER**

**Special Handling:** **DO NOT LET PRODUCT FREEZE.**  
**Hazardous ratings:** Mascoat Products currently uses the National Paint and Coatings Association rating system. The use of an asterisk (\*) in the HMIS rating indicates the potential for chronic health effects  
**HMIS:**

<b>Health</b>	<b>Fire</b>	<b>Reactivity</b>	<b>Special</b>
<b>1</b>	<b>0</b>	<b>0</b>	<b>0</b>

  
**Hazardous rating OSHA:** **The product is considered NON HAZARDOUS by the OSHA Hazard Communication Standard.**  
**Trademark:** LizardSkin Sound Control™ is a registered trademark of Mascoat, Houston, TX USA.  
**Important:** While descriptions, designs, data and other information contained herein are presented in good faith and believed to be accurate, they are provided for guidance only. Many factors may influence the processing or application/use, Mascoat recommends that tests be made for the suitability for the product in the intended purpose. The intended use of this document is for health and handling procedures and not intended for an ingredients list for reformulation.  
**Shipping:** This product is acceptable for shipment as non-hazardous via motor, air or ocean freight without any specialized handling. (Class 55).