

Clock

- Setting range : 12 · 24 H
- Automatically set clock according to time zone selected.

GPS message display area

AVE Speed

- Record range : 0 ~ 360 km/h (0 ~ 255 MPH)
- Record unit : 1 km/h (MPH)

Top speed record (Max.)

- Record range : 0 ~ 360 km/h (0 ~ 255 MPH)
- Record unit : 1 km/h (MPH)



Key symbol display area

Speedometer

- Display range:0~360 km/h (0~255 MPH)
- Display range:1 km/h (MPH)

Odo meter

- Display range : 0 ~ 99,999 km (mile) · reset automatically after 99,999 km (mile)
- Display unit : 1 km (mile)

Trip meter

- Display range : 0 ~ 9,999.9 km (mile) · reset automatically after 9,999.9 km (mile)
- Setting unit : 0.1 km (mile)

Riding time

- Record range:0 ~ 9,999.9 H · reset automatically after 9,999.9 H
- Record unit:0.1 H

● Speedometer Display range : 0~360 km/h (0 ~ 255 MPH)
Display range : 1 km/h (MPH)

○ Display internal <0.5 second

○ Odometer Display range : 0 ~ 99,999 km (mile) · reset automatically after 99,999 km (mile)
Display range : 1 km/h (MPH)

○ Trip meter Display range : 0 ~ 9,999.9 km (mile) · reset automatically after 9,999.9 km (mile) (delete average speed and run time records simultaneously)(delete average speed and run time records simultaneously)
Display range : 0.1 km/h (MPH)

○ AVE Speed Record range : 0~360 km/h (0~255 MPH)
Record unit : 1 km/h (MPH)

○ Riding time Record range : 0 ~ 9,999.9 H · reset automatically after 9,999.9 H
Record unit : 0.1 H

○ Top speed record Record range : 0~360 km/h (0~255 MPH)
Record unit : 1 km/h (MPH)

● Geodetic coordinate system WGS-84

○ Coordinate display method Setting range : d°m's.s" · d.d° · d°m.m'

● Time zone Setting range : UTC -12:00 ~ +14:00

● Calender Automatic Time Adjustment by GPS signal

● Clock Setting range : 12 · 24 H
Automatically set clock according to time zone selected.

● Voltage warning Battery symbol flashes when voltage is lower than the 7.0 V

● Display contrast adjustment Setting range:1~16 level

● Backlight brightness adjust Setting range : 0(Close) · 1(Darkest)~7 (Brightest). The backlight brightness will change immediately after you set the value.

● Timing mode

○ Single recording time Record range : 00'00"00~99'59"99

○ Number of loop record Record range : 1~200 Laps (Maximum)

○ Time difference compares to the best time record Display range : 00"00~99"99

○ Time difference compares to last loop Display range : -99"99~+99"99

○ Record display method Setting range : Sequentially · Best

○ Record displays retention time Setting range : 5~20 second

● Target speed timer Setting range : 30 ~ 360 km/h (20~255 MPH)
Setting unit : 5 km/h (MPH)

● Target distance timer Setting range : 1/32~30/32 mile (50~1,500 M)
Setting unit : 1/32 mile (50 M)

● Closed track single loop time recording Setting range : 0'00"00 ~ 9'59"99

● Open track single loop time recording Setting range : 0'00"00 ~ 9'59"99

● Create track Setting range : close, open

○ Track width Setting range : 5 ~ 50 M
Setting unit : 1 M

○ Track length Auto-calculation after travel a loop

○ Checkpoint Checkpoint Setting range : 0 ~ 22points (Max.)

● Effective voltage DC 12 V

● Effective temperature range -10 ~ +60 °C

● Meter standard JIS D 0203 S2

● Meter size 107.7 X 61.7 X 20.5 mm

● Meter weight 132.2 g