

High Mileage Fuel Treatment

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 10/30/2015

Revision date: 11/30/2015

Version: 2.0



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Identification

Product form : Mixture
Product name : High Mileage Fuel
Other means of identification Treatment : Part # 10977

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Additive

1.3. Details of the supplier of the safety data sheet

Lucas Oil Products, Inc

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

Flam. Liq. 4 H227 - Combustible liquid
Eye Irrit. 2A H319 - Causes serious eye irritation
Carc. 2 H350 - May cause cancer

Full text of H statements : see section 16

2.2. Label elements

GHS-US labelling

Hazard pictograms (GHS-US) :



GHS07

GHS08

Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H227 - Combustible liquid
H319 - Causes serious eye irritation
H350 - May cause cancer

Precautionary statements (GHS-US) : P201 - Obtain special instructions before use
P202 - Do not handle until all safety precautions have been read and understood
P210 - Keep away from heat, sparks, open flames. - No smoking
P264 - Wash hands thoroughly after handling
P280 - Wear eye protection, protective gloves
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P308+P313 - If exposed or concerned: Get medical advice/attention
P337+P313 - If eye irritation persists: Get medical advice/attention
P370+P378 - In case of fire: Use carbon dioxide (CO2), dry extinguishing powder, foam, Water spray to extinguish
P403+P235 - Store in a well-ventilated place. Keep cool
P405 - Store locked up
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

High Mileage Fuel Treatment

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	GHS-US classification
Kerosene	(CAS No) 8008-20-6	10 - 30	Flam. Liq. 4, H227 Asp. Tox. 1, H304
Hydrocarbons, C11-14, n-alkanes, isoalkanes, cyclic, <2% aromatics	(CAS No) 64742-47-8	5 - 15	Asp. Tox. 1, H304
Hydrocarbons, C10, aromatics, >1% naphthalene		1 - 5	Flam. Liq. 3, H226 Asp. Tox. 1, H304
Mineral Seal Oil	(CAS No) 64742-46-7	1 - 5	Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Irrit. 2, H315 Carc. 1B, H350
Poly[oxy(1,2-propanediyl)], .alpha.-(3-aminopropyl)-.omega.-hydroxy-, C12-15 alkyl ethers		0.5 - 1.5	Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
1,2,4-trimethylbenzene	(CAS No) 95-63-6	0.5 - 1.5	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Aquatic Chronic 2, H411
Naphthalene	(CAS No) 91-20-3	0.1 - 1	Acute Tox. 4 (Oral), H302 Carc. 2, H351 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : Never give anything by mouth to an unconscious person.
- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
- First-aid measures after skin contact : Gently wash with plenty of soap and water.
- First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician.
- First-aid measures after ingestion : Do NOT induce vomiting. Call a POISON CENTER or doctor/physician if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries : May cause cancer.
- Symptoms/injuries after inhalation : Inhalation of vapours may cause respiratory irritation.
- Symptoms/injuries after eye contact : Causes serious eye damage.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Carbon dioxide. Dry chemical. Foam. Water spray.
- Unsuitable extinguishing media : Do not use a solid water stream as it may scatter and spread fire.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Combustible liquid.
- Explosion hazard : May form flammable/explosive vapour-air mixture.
- Reactivity : No dangerous reactions known.

5.3. Advice for firefighters

- Precautionary measures fire : Remove ignition sources.
- Firefighting instructions : Use water spray or fog for cooling exposed containers. Do not allow run-off from fire fighting to enter drains or water courses.
- Protection during firefighting : Wear a self contained breathing apparatus. Wear fire/flame resistant/retardant clothing.

High Mileage Fuel Treatment

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking. Avoid all eye and skin contact and do not breathe vapour and mist.

6.1.1. For non-emergency personnel

Protective equipment : Chemical goggles or safety glasses. Wear suitable gloves.
Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Chemical goggles or safety glasses. Wear suitable gloves.
Emergency procedures : Stop leak if safe to do so. Ventilate area.

6.2. Environmental precautions

Do not discharge into drains or the environment.

6.3. Methods and material for containment and cleaning up

For containment : Do not allow minor leaks or spills to accumulate on walking surfaces. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
Methods for cleaning up : Absorb and/or contain spill with inert material, then place in suitable container.

6.4. Reference to other sections

Section 7: safe handling. Section 8: personal protective equipment.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Handle empty containers with care because residual vapours are flammable. Keep away from Sources of ignition. - No smoking.
Precautions for safe handling : No open flames. No smoking. Avoid all eye and skin contact and do not breathe vapour and mist. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.
Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed.
Storage conditions : Keep in fireproof place. Keep container tightly closed.
Incompatible products : Oxidizer.
Incompatible materials : Heat sources.
Heat and ignition sources : Keep away from heat, sparks and flame.
Prohibitions on mixed storage : Incompatible materials.
Storage area : Store in a well-ventilated place.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

High Mileage Fuel Treatment		
ACGIH	ACGIH TWA (mg/m ³)	5 mg/m ³ oil mist
ACGIH	ACGIH STEL (mg/m ³)	10 mg/m ³ oil mist
OSHA	Not applicable	
Kerosene (8008-20-6)		
ACGIH	ACGIH TWA (mg/m ³)	200 mg/m ³
ACGIH	Remark (ACGIH)	P
OSHA	Not applicable	
Hydrocarbons, C11-14, n-alkanes, isoalkanes, cyclic, <2% aromatics (64742-47-8)		
ACGIH	Not applicable	
OSHA	Not applicable	

High Mileage Fuel Treatment

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hydrocarbons, C10, aromatics, >1% naphthalene		
ACGIH	Not applicable	
OSHA	Not applicable	
Mineral Seal Oil (64742-46-7)		
ACGIH	ACGIH TWA (mg/m ³)	5 mg/m ³ as Mineral oil mist
OSHA	Not applicable	
Poly[oxy(1,2-propanediyl)], .alpha.-(3-aminopropyl)-.omega.-hydroxy-, C12-15 alkyl ethers		
ACGIH	Not applicable	
OSHA	Not applicable	
1,2,4-trimethylbenzene (95-63-6)		
ACGIH	ACGIH TWA (mg/m ³)	123 mg/m ³
ACGIH	ACGIH TWA (ppm)	25 ppm
OSHA	Not applicable	
Naphthalene (91-20-3)		
ACGIH	ACGIH TWA (mg/m ³)	52 mg/m ³
ACGIH	ACGIH TWA (ppm)	10 ppm
ACGIH	ACGIH STEL (mg/m ³)	79 mg/m ³
ACGIH	ACGIH STEL (ppm)	15 ppm
ACGIH	Remark (ACGIH)	Hematologic eff; URT & eye irr; Skin; A3
OSHA	OSHA PEL (TWA) (mg/m ³)	50 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	10 ppm

8.2. Exposure controls

Appropriate engineering controls	: Ensure good ventilation of the work station. Eyewash stations.
Personal protective equipment	: Avoid all unnecessary exposure.
Hand protection	: Wear suitable gloves. nitrile rubber gloves.
Eye protection	: Chemical goggles or safety glasses.
Respiratory protection	: In case of inadequate ventilation wear respiratory protection. NIOSH. Approved respirator.
Environmental exposure controls	: Prevent leakage or spillage. Prevent contaminated water run-off.
Consumer exposure controls	: Keep out of reach of children.
Other information	: Do not eat, drink or smoke when using this product.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: amber
Odour	: petroleum
Odour threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 61.1 °C
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Explosive limits	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Vapour pressure	: No data available

High Mileage Fuel Treatment

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Relative density	: 0.8642
Relative vapour density at 20 °C	: No data available
Solubility	: Water: Solubility in water of component(s) of the mixture : • 1,2,4-trimethylbenzene: 57 mg/l
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: 24.6 cSt @ 40 °C
Viscosity, dynamic	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known.

10.2. Chemical stability

Combustible liquid. May form flammable/explosive vapour-air mixture.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Open flame. Overheating. Direct sunlight. Heat. Sparks.

10.5. Incompatible materials

Oxidizer.

10.6. Hazardous decomposition products

May release flammable gases. hydrocarbons. Carbon oxides (CO, CO₂).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Likely routes of exposure : Inhalation; Skin and eye contact

Acute toxicity : Not classified

Hydrocarbons, C11-14, n-alkanes, isoalkanes, cyclic, <2% aromatics (64742-47-8)

LD50 oral rat	> 15000 mg/kg
---------------	---------------

LD50 dermal rabbit	>= 3160 mg/kg
--------------------	---------------

Mineral Seal Oil (64742-46-7)

LD50 oral rat	> 5000 mg/kg OECD 401
---------------	-----------------------

LD50 dermal rabbit	> 2000 µg/kg OECD 402
--------------------	-----------------------

LC50 inhalation rat (mg/l)	4.6 mg/l/4h OECD 403
----------------------------	----------------------

ATE US (vapours)	4.600 mg/l/4h
------------------	---------------

ATE US (dust,mist)	4.600 mg/l/4h
--------------------	---------------

1,2,4-trimethylbenzene (95-63-6)

LD50 oral rat	3415 mg/kg
---------------	------------

LD50 dermal rat	3440 mg/kg
-----------------	------------

LC50 inhalation rat (ppm)	954 ppm
---------------------------	---------

ATE US (oral)	3415.000 mg/kg bodyweight
---------------	---------------------------

ATE US (dermal)	3440.000 mg/kg bodyweight
-----------------	---------------------------

ATE US (dust,mist)	1.500 mg/l/4h
--------------------	---------------

Naphthalene (91-20-3)

LD50 oral rat	490 mg/kg
---------------	-----------

LD50 dermal rabbit	20 g/kg
--------------------	---------

LC50 inhalation rat (mg/l)	> 340 mg/m ³ 1 hour
----------------------------	--------------------------------

ATE US (oral)	490.000 mg/kg bodyweight
---------------	--------------------------

High Mileage Fuel Treatment

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Naphthalene (91-20-3)	
ATE US (dermal)	20000.000 mg/kg bodyweight
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: May cause cancer.

Hydrocarbons, C11-14, n-alkanes, isoalkanes, cyclic, <2% aromatics (64742-47-8)	
IARC group	Not listed in carcinogenicity class

Naphthalene (91-20-3)	
IARC group	2B - Possibly carcinogenic to humans
National Toxicology Program (NTP) Status	3 - Reasonably anticipated to be Human Carcinogen
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: Not classified

Mineral Seal Oil (64742-46-7)	
NOAEL (dermal, rat/rabbit, 90 days)	1000 mg/kg bodyweight/day 28 day
Aspiration hazard	: Not classified
Symptoms/injuries after inhalation	: Inhalation of vapours may cause respiratory irritation.
Symptoms/injuries after eye contact	: Causes serious eye damage.

SECTION 12: Ecological information

12.1. Toxicity

Ecology – water : Harmful to aquatic life with long lasting effects.

Hydrocarbons, C11-14, n-alkanes, isoalkanes, cyclic, <2% aromatics (64742-47-8)	
LC50 fish 1	> 1000 mg/l
EC50 Daphnia 1	> 1000 mg/l
NOEC chronic fish	0.173 mg/l Estimated. Based on growth.

Hydrocarbons, C10, aromatics, >1% naphthalene	
LC50 fish 1	2 mg/l 96 h
EC50 Daphnia 1	3 mg/l 48 h

Mineral Seal Oil (64742-46-7)	
LC50 fish 1	65 mg/l OECD 203 96h
EC50 Daphnia 1	210 mg/l OECD 202 48hr; read-across using gas oil.
ErC50 (algae)	78 mg/l OECD 201

1,2,4-trimethylbenzene (95-63-6)	
LC50 fish 1	7.72 mg/l
LC50 other aquatic organisms 1	3.6 mg/l
EC50 other aquatic organisms 1	2.356 mg/l

Naphthalene (91-20-3)	
LC50 fish 1	> 0.91 (0.91 - 2.82) mg/l Oncorhynchus mykiss (From Koppers SDS)
EC50 Daphnia 1	>= 1.96 mg/l From Koppers SDS
EC50 other aquatic organisms 1	33 mg/l From Sigma-Aldrich SDS
LC50 fish 2	> 1 (1 - 6.5) mg/l Pimpephales promelas (From Sigma-Aldrich SDS)
LOEC (acute)	3.2 mg/l From Sigma-Aldrich SDS
NOEC (acute)	1.8 mg/l From Sigma-Aldrich SDS

12.2. Persistence and degradability

High Mileage Fuel Treatment	
Persistence and degradability	May cause long-term adverse effects in the environment.

Hydrocarbons, C11-14, n-alkanes, isoalkanes, cyclic, <2% aromatics (64742-47-8)	
Biodegradation	69 % 28 days

High Mileage Fuel Treatment

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Mineral Seal Oil (64742-46-7)	
Persistence and degradability	Not readily biodegradable.
Biodegradation	35 % 28d

12.3. Bioaccumulative potential

Naphthalene (91-20-3)	
BCF fish 1	>= 427 (427 - 1158)

12.4. Mobility in soil

Mineral Seal Oil (64742-46-7)	
Mobility in soil	Distribution modeling predicts 57% distribution to soil.

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Sewage disposal recommendations	: Do not dispose of waste into sewer.
Waste disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations.
Additional information	: Handle empty containers with care because residual vapours are flammable.
Ecology - waste materials	: Avoid release to the environment.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

In accordance with DOT

Non-bulk (<= 119 gal) : Not a dangerous good per transport regulations

Bulk (> 119 gal) :

Transport document description	: NA1993 Combustible liquid, n.o.s. (Kerosene), 3, III
UN-No.(DOT)	: NA1993
Proper Shipping Name (DOT)	: Combustible liquid, n.o.s. Kerosene
Transport hazard class(es) (DOT)	: 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
Packing group (DOT)	: III - Minor Danger
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 203
DOT Packaging Bulk (49 CFR 173.xxx)	: 241
DOT Symbols	: D - Proper shipping name for domestic use only, or to and from Canada,G - Identifies PSN requiring a technical name
DOT Special Provisions (49 CFR 172.102)	: IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672) T1 - 1.5 178.274(d)(2) Normal..... 178.275(d)(2) T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3) TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / (1 + a (tr - tf))$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling
DOT Packaging Exceptions (49 CFR 173.xxx)	: 150
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 60 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 220 L
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel
Other information	: No supplementary information available.

High Mileage Fuel Treatment

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Transport by sea

No additional information available

Air transport

No additional information available

SECTION 15: Regulatory information

15.1. US Federal regulations

Hydrocarbons, C11-14, n-alkanes, isoalkanes, cyclic, <2% aromatics (64742-47-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Mineral Seal Oil (64742-46-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

1,2,4-trimethylbenzene (95-63-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Naphthalene (91-20-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory
Subject to reporting requirements of United States SARA Section 313

CERCLA RQ

100 lb

SARA Section 311/312 Hazard Classes

Delayed (chronic) health hazard
Immediate (acute) health hazard

15.2. International regulations

CANADA

Hydrocarbons, C11-14, n-alkanes, isoalkanes, cyclic, <2% aromatics (64742-47-8)

Listed on the Canadian DSL (Domestic Substances List) inventory

1,2,4-trimethylbenzene (95-63-6)

Listed on the Canadian DSL (Domestic Substances List) inventory

Naphthalene (91-20-3)

Listed on the Canadian DSL (Domestic Substances List) inventory

EU-Regulations

Hydrocarbons, C11-14, n-alkanes, isoalkanes, cyclic, <2% aromatics (64742-47-8)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

1,2,4-trimethylbenzene (95-63-6)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Naphthalene (91-20-3)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Eye Irrit. 2 H319

Carc. 2 H350

Aquatic Chronic 3 H412

Full text of hazard classes and H-statements : see section 16

National regulations

Hydrocarbons, C11-14, n-alkanes, isoalkanes, cyclic, <2% aromatics (64742-47-8)

Listed on the Inventory of Existing Chemical Substances Produced or Imported in China (IECSC)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on KECI (Korean Existing Chemicals Inventory)

Listed on Taiwan National Chemical Inventory

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on NZIoC (New Zealand Inventory of Chemicals)

High Mileage Fuel Treatment

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

1,2,4-trimethylbenzene (95-63-6)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on KECI (Korean Existing Chemicals Inventory)
Listed on Taiwan National Chemical Inventory
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on the Chinese Catalog of Hazardous Chemicals

Naphthalene (91-20-3)

Listed on IARC (International Agency for Research on Cancer)
Listed as carcinogen on NTP (National Toxicology Program)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Chinese Catalog of Hazardous Chemicals
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on KECI (Korean Existing Chemicals Inventory)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on Taiwan National Chemical Inventory

15.3. US State regulations

Naphthalene (91-20-3)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
Yes	No	No	No	

Naphthalene (91-20-3)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

Indication of changes	: Original Document.
Revision date	: 11/30/2015
Data sources	: ACGIH (American Conference of Government Industrial Hygienists). European Chemicals Agency (ECHA) C&L Inventory database. Kriester Forsberg and S.Z. Mansdorf, "Quick Selection Guide to Chemical Protective Clothing", Fifth Edition. National Fire Protection Association. Fire Protection Guide to Hazardous Materials; 10th edition. NIOSH Occupational Health Guide for chemical Substances - Vol. II, September, 1978. OSHA 29CFR 1910.1200 Hazard Communication Standard. TSCA Chemical Substance Inventory.
Abbreviations and acronyms	: ATE: Acute Toxicity Estimate. CAS (Chemical Abstracts Service) number. CFR: Code of Federal Regulations. EC50: Environmental Concentration associated with a response by 50% of the test population. GHS: Globally Harmonized System (of Classification and Labeling of Chemicals). LD50: Lethal Dose for 50% of the test population. OSHA: Occupational Safety & Health Administration. STEL: Short Term Exposure Limits. TSCA: Toxic Substances Control Act. TWA: Time Weighted Average.
Other information	: None.

High Mileage Fuel Treatment

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-statements:

H226	Flammable liquid and vapour
H227	Combustible liquid
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H318	Causes serious eye damage
H319	Causes serious eye irritation
H332	Harmful if inhaled
H350	May cause cancer
H351	Suspected of causing cancer
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H411	Toxic to aquatic life with long lasting effects

NFPA health hazard

: 1 - Exposure could cause irritation but only minor residual injury even if no treatment is given.

NFPA fire hazard

: 2 - Must be moderately heated or exposed to relatively high temperature before ignition can occur.

NFPA reactivity

: 0 - Normally stable, even under fire exposure conditions, and not reactive with water.



Redstone SDS US GHS for Lucas Oil

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product