

## TECHNICAL DATA SHEET



# SLICK MIST® SPEED WAX

PRODUCT # 10160, 10161, 10980



### TEST

### ASTM

### TYPICAL

<b>Specific Gravity @ 60°F</b>	<b>D-1298</b>	<b>1.0</b>
<b>Density @ 60°F LBS/US Gal</b>	<b>D-1298</b>	<b>8.328</b>
<b>Flash Point, COC °F</b>	<b>D-92</b>	<b>Non-Flammable</b>
<b>Color</b>	<b>Visual</b>	<b>Aqua</b>
<b>pH</b>		<b>6 - 7</b>
<b>Odor</b>		<b>Bubble Gum</b>
<b>Pour Point, °F</b>	<b>D-97</b>	<b>32 (Avoid Freezing)</b>

**Lucas Slick Mist® is a unique speed wax developed to quickly detail your car, truck, boat and airplane, and leave your paint with a showroom shine. Slick Mist® is used by professional auto show vehicle detailers and racing professionals who demand the ultimate performance.**

**Lucas Slick Mist® is designed to be used on wet or dry surfaces, even in direct sunlight, and provides excellent UV protection. Excellent for all vinyl wraps and decals, and helps keep mud, bugs and tar from sticking to your vehicle. Safe for use with leather, plastic or aluminum surfaces.**

**For best results, shake bottle well prior to use, apply a fine spray and wipe dry with a soft terry cloth towel, chamois or micro fiber towel.**

**ATTENTION: Do not use any Slick Mist® products on floors, vehicle controls (pedals, grips, steering wheels), motorcycle seats or tire treads, bicycle seats or tire treads, brake drums and any other surfaces where slipperiness may be hazardous.**