

## TECHNICAL DATA SHEET



# RED 'N' TACKY SPRAY GREASE

PRODUCT # 11025

## TEST

## ASTM

## TYPICAL

### Thickener Type

Texture

Color

Worked Penetration

(with Propellant Removed)

Timken OK Load, Lbs

Corrosion Prevention Test

Base Oil Properties:

Pour Point, °F

Flash Point, °F

Base Oil Viscosity

@100°F, SUS

@210°F, SUS

Silica

Smooth & Tacky

Red

275 (after 60 strokes)

290 (after 10,000 strokes)

60

Pass

D217

D2509

D665

D97

D92

D445

0

450

4,100

280

**Lucas Red "N" Tacky Spray Grease is a high-quality silica grease in a convenient aerosol package. The application is ideal for putting grease in those hard-to-reach areas. Our customers tell us there are many times that they'd prefer to lubricate a part or piece of equipment with grease, rather than a penetrating or general-purpose oil, common in aerosol cans, but need the convenience of a spray. Lucas Red "N" Tacky Spray Grease is the answer. Excellent for cars, trucks, RVs, industrial or farm equipment and around the house. Use wherever grease is the preferred lubricant.**

### Features:

- **A Narrow, Confined Spray Pattern**
- **Fast Carrier Solvent Evaporation**
- **Good Cling to the Applied Surface**
- **Resists Separation**
- **Resists Water Washout**
- **Good Heat Resistance**
- **Broad Temperature Use Range, 0°-450°F**