

TECHNICAL DATA SHEET



SYNTHETIC SAE 10W-30

PRODUCT #10050

API SERVICE SM/SL/SJ/CF

TEST

ASTM

TYPICAL

API Gravity	D-1298	33.2
Specific Gravity @ 60°F	D-1298	.8591
Density @ 60°F LBS/US Gal	D-1298	7.153
Viscosity @ 40°C cSt	D-445	57.0
Viscosity @ 100°C cSt	D-445	10.5
Viscosity Index	D-2270	178
Flash Point, COC °F	D-92	455
Pour Point	D-97	-36
Color		Light Brown
CCS @ -25°C, CPS	D-5293	7,000 Max
MRV TP-1 @ -30°C, CPS	D-4684	60,000 Max
Z, Wt %	ICP	0.08 Typ
P, Wt %	ICP	0.08 Max
TBN, Mg KoH/g	D-2896	8.0

This excellent product provides the consistent viscosity needed for precision ET racing. Lucas Synthetic SAE 10W-30 is a formulation of only the finest light synthetic base oils plus an exclusive additive package that includes lubricity agents and anti-seize agents that control drag like a zero weight oil and protect like a heavy multi-viscosity oil.

It is the perfect non-foaming lubricant for high RPM karting and motorcycle engines. It is also excellent for normal highway use.

Lucas Synthetic SAE 10W-30 is the perfect lubricant for extreme low temperatures or extreme high temperatures and blends with other synthetic or regular motor oil. Blend a quart or two into your conventional motor oil for easier starting and longer oil life.

Exceeds American and European OEM specifications. Exceeds performance levels of API SM/SL/SJ/CF, ILSAC GF-4, ACEA A3-98, B3-98, B4-98, VW 500/502/505, Daimler Chrysler 229.1, BMW Longlife Oil.

