

Model M073K - 7"



Mounting Feet

- Lowest profile high performance reversibles on the market
- Sealed motor tested in accordance with DIN EN 60529, dust and water proof to IP68
- Quiet, reversible S-blade design
- All glass-filled nylon construction
- Includes (4) 90° mounting feet and nylon tie kit
- Includes locking mating pigtail connector and rubber spacers for proper spacing off of heat exchanger
- Recommended wire harnesses* (sold separately)
 - Part No. MFA100 (adjustable thermostat)
 - Part No. MFA102 (185° temperature switch)
 - Part No. MFA103 (195° temperature switch)
- Optional brackets* (sold separately)
 - Part No. MFA104 (metal bracket strips)
 - Part No. MFA105 (aluminum brackets)



Fan Harness

Pigtail

TYPICAL PERFORMANCE DATA		
M073K 7" LP REVERSIBLE CHAMPION 12V 130W		
Static In H ₂ O	Total Flow CFM	13.5 VDC AMPS
0.00	349	5.4
0.10	333	5.4
0.20	303	5.4
0.30	269	5.4
0.40	226	5.2
0.50	184	5.3
0.60	160	5.3
0.70	142	5.3
0.80	125	5.3
1.20	STALL @ 1.2"	6.3

