

Model M093K - 9"



- Lowest profile high performance reversibles on the market
- Sealed motor tested in accordance with DIN EN 60529, dust and water proof to IP68
- Quiet, reversible S-blade design
- All glass-filled nylon construction
- Includes (4) 90° mounting feet and nylon tie kit
- Includes locking mating pigtail connector and rubber spacers for proper spacing off of heat exchanger
- Recommended wire harnesses* (sold separately)
 - Part No. MFA100 (adjustable thermostat)
 - Part No. MFA102 (185° temperature switch)
 - Part No. MFA103 (195° temperature switch)
- Optional brackets* (sold separately)
 - Part No. MFA104 (metal bracket strips)
 - Part No. MFA105 (aluminum brackets)



Mounting Feet

Fan Harness

Pigtail

| TYPICAL PERFORMANCE DATA | | |
|--|----------------|---------------|
| M093K 9" LP REVERSIBLE CHAMPION 12V 130W | | |
| Static In H ₂ O | Total Flow CFM | 13.5 VDC AMPS |
| 0.00 | 790 | 7.7 |
| 0.10 | 747 | 8.0 |
| 0.20 | 679 | 8.2 |
| 0.30 | 598 | 8.3 |
| 0.40 | 514 | 8.3 |
| 0.50 | 431 | 8.3 |
| 0.60 | 352 | 8.3 |
| 0.70 | 280 | 8.3 |
| 0.80 | 213 | 8.5 |
| 0.90 | 152 | 8.7 |
| 1.00 | 92 | 9.1 |
| 1.10 | STALL @ 1.1" | 9.9 |

