

Model M113K - 11"



Mounting Feet

- Lowest profile high performance reversibles on the market
- Sealed motor tested in accordance with DIN EN 60529, dust and water proof to IP68
- Quiet, reversible S-blade design
- All glass-filled nylon construction
- Includes (4) 90° mounting feet and nylon tie kit
- Includes locking mating pigtail connector and rubber spacers for proper spacing off of heat exchanger
- Recommended wire harnesses* (sold separately)
 - Part No. MFA100 (adjustable thermostat)
 - Part No. MFA102 (185° temperature switch)
 - Part No. MFA103 (195° temperature switch)
- Optional brackets* (sold separately)
 - Part No. MFA104 (metal bracket strips)
 - Part No. MFA105 (aluminum brackets)



Fan Harness

Pigtail

TYPICAL PERFORMANCE DATA		
M162K 16" LP REVERSIBLE CHAMPION 12V 225W		
Static In H ₂ O	Total Flow CFM	13.5 VDC AMPS
0.00	2170	17.7
0.10	2034	18.2
0.20	1984	18.8
0.30	1716	19.0
0.40	1462	19.0
0.50	1208	18.8
0.60	890	17.9
0.70	540	17.3
0.80	222	17.3
0.90	STALL @ 0.9"	17.4

