

Model M142K - 14"



- Lowest profile high performance reversibles on the market
- Sealed motor tested in accordance with DIN EN 60529, dust and water proof to IP68
- Quiet, reversible S-blade design
- All glass-filled nylon construction
- Includes (4) 90° mounting feet
- Includes locking mating pigtail connector and rubber spacers for proper spacing off of heat exchanger
- Recommended wire harnesses* (sold separately)
 - Part No. MFA100 (adjustable thermostat)
 - Part No. MFA102 (185° temperature switch)
 - Part No. MFA103 (195° temperature switch)
- Optional brackets* (sold separately)
 - Part No. MFA104 (metal bracket strips)
 - Part No. MFA105 (aluminum brackets)



Mounting Feet



Fan Harness



Pigtail

| TYPICAL PERFORMANCE DATA | | |
|---|----------------|---------------|
| M142K 14" LP REVERSIBLE CHAMPION 12V 225W | | |
| Static In H ₂ O | Total Flow CFM | 13.5 VDC AMPS |
| 0.00 | 2135 | 16.8 |
| 0.10 | 2015 | 17.3 |
| 0.20 | 1878 | 17.5 |
| 0.30 | 1743 | 17.6 |
| 0.40 | 1615 | 18.0 |
| 0.50 | 1409 | 18.1 |
| 0.60 | 1126 | 17.8 |
| 0.70 | 899 | 17.8 |
| 0.80 | 620 | 16.4 |
| 1.10 | STALL @ 1.1" | 17.2 |

