

## Model MP109K - 10"



- Lowest profile high performance reversibles on the market
- Sealed motor tested in accordance with DIN EN 60529, dust and water proof to IP68
- Quiet, reversible S-blade design
- All glass-filled nylon construction
- Includes (4) 90° mounting feet
- Includes locking mating pigtail connector and rubber spacers for proper spacing off of heat exchanger
- Recommended wire harnesses\* (sold separately)
  - Part No. MFA100 (adjustable thermostat)
  - Part No. MFA102 (185° temperature switch)
  - Part No. MFA103 (195° temperature switch)
- Optional brackets\* (sold separately)
  - Part No. MFA104 (metal bracket strips)
  - Part No. MFA105 (aluminum brackets)

| TYPICAL PERFORMANCE DATA                   |                |               |
|--|----------------|---------------|
| MP109K 9" LP REVERSIBLE PACESETTER 12V 90W |                |               |
| Static In H <sub>2</sub> O                 | Total Flow CFM | 13.5 VDC AMPS |
| 0.00                                       | 666            | 4.5           |
| 0.10                                       | 584            | 4.5           |
| 0.20                                       | 467            | 4.5           |
| 0.30                                       | 378            | 4.7           |
| 0.40                                       | 296            | 5.2           |
| 0.50                                       | 222            | 5.4           |
| 0.60                                       | 131            | 5.3           |
| 0.70                                       | STALL @ 0.7"   | 5.4           |

