

# PREMIUM BREAK-IN

## HIGH PERFORMANCE 4-STROKE BREAK-IN OIL

#### **DESCRIPTION:**

Mineral based 4-stroke engine oil specifically formulated for breaking in engines with flat tappet camshafts, roller elements and where maximum anti-wear performance is needed. High ZDDP formulation combines the highest quality mineral base stocks with a shear-stable polymer system to provide fast and effective ring seal. Advanced, proprietary additive system utilizes a complex, low-temperature activating 2X Zinc system that ensures immediate and lasting protection. Dyno proven to increase break-in efficiency.

#### **FEATURES & BENEFITS:**

- Formulated for break-in of all 4-stroke engines
- Ideal for use in race engines, OEM rebuilds, and crate motors
- Ensures fast and effective ring seal
- Maximum protection for both flat tappet and roller cam shafts
- 2X Zinc system provides optimum and immediate protection at all temperatures
- Dyno tested and approved

#### **APPLICATIONS:**

For all 4-stroke engines. Safe for wet clutches and motorcycle transmissions. Designed for high performance applications.

### **TECHNICAL DATA**

| SPECIFICATION           | TEST METHOD | 10W-30 |
|-------------------------|-------------|--------|
| APPEARANCE              | VISUAL      | Amber  |
| VISCOSITY @ 40°C (cSt)  | D445        | 69.8   |
| VISCOSITY @ 100°C (cSt) | D445        | 10.8   |
| VISCOSITY INDEX         | D2270       | 144    |
| FLASH POINT (°C)        | D92         | 228    |
| POUR POINT (°C)         | D97         | -39    |
| DENSITY @ 15 °C (g/ml)  | D4052       | 0.868  |