



# SXS GEAR

## HIGH PERFORMANCE GEAR OIL

### DESCRIPTION:

Mineral-based gear oil specifically formulated for hypoid-type differentials found in modern side-by-side (SXS) vehicles. Robust, shear-stable formulation can also be used in side-by-side transmissions and gear cases requiring SAE 90wt gear oil. Proprietary shape combines the finest mineral base stocks with industry leading extreme pressure and anti-wear additives to ensure hardware protection and smooth shifting. Exceeds the requirements of API GL-5.

### FEATURES & BENEFITS:

- Formulated specifically for use in modern side-by-side vehicles
- Superior protection from wear, pitting and spalling
- Shear stable formula maintains viscosity and ensures smooth shifting
- Surface-active chemistry keeps surfaces free of corrosion, deposits and wear
- Exceeds API GL-5 specifications

### APPLICATIONS:

For hypoid-type differentials found in modern SXS, ATV and UTV. Can be used in SXS, ATV and UTV transmissions and gear cases recommending SAE 90wt gear oil.

### TECHNICAL DATA

SPECIFICATION	TEST METHOD	80W-90
APPEARANCE	VISUAL	Amber
VISCOSITY @ 40°C (cSt)	D445	171.7
VISCOSITY @ 100°C (cSt)	D445	16.3
VISCOSITY INDEX	D2270	99
FLASH POINT (°C)	D92	397
POUR POINT (°C)	D97	-27
DENSITY @ 15 °C (g/ml)	D4052	-