

that you have read and understand these instructions.

If you have any questions or are uncertain about any aspect of the installation of this system to your vehicle please contact your dealer before commencing installation.





Figure 1



Figure 2



Figure 3



Figure 4

2009-13 TOYOTA TUNDRA

Removal of Stock System:

1. Apply a penetrating lubricant liberally to all exhaust fasteners, hangers and rubber insulators.

2. Remove hardware from stock extension pipes. Retain for reinstallation. **Refer to Figure 1**.

3. Remove exhaust from rubber insulators. Refer to Figure 2.

4. Remove the exhaust from the rearmost hanger. Leave the rubber insulators on the truck for installation. **Refer to Figure 3**.

Installation of MBRP Inc. Performance Exhaust:

1. <u>Install the Driver Side Front Pipe</u>, reusing the existing hardware and attaching the hanger to the existing rubber insulator. Leave the hardware loose enough for some adjustment. **Refer to Figure 4**.





Figure 5



Figure 6



Figure 7



Figure 8



Figure 9

2. Install the **Passenger Side Front Pipe** reusing the existing hardware. Leave the hardware loose enough for some adjustment. **Refer to Figure 5**.

3. Slide 2 1/2"Clamps over the Passenger Side Front Pipe and the Driver Side Front Pipe. Install the Mufflers onto the Driver Side Front Pipe and then the Passenger Side Front Pipe. Refer to Figure 6.

4. Slide a 2 1/2"Clamp over the outlet side of the driver's side Muffler.
Position the Driver Side Over Axle Pipe and loosely attach it to the Muffler.
Install the Driver Side Over Axle Pipe hanger into the factory rubber insulator. Refer to Figure 7.

5. Slide a 2 1/2"Clamp over the Driver Side Tailpipe and install onto the Driver Side Over Axle Pipe. Install the Hanger Assembly onto the Driver Side Tailpipe and install to the frame using the fastener provided. Refer to Figures 8, 9 and Detail A on Page 1.





Figure 10



Figure 11

7. Slide a 2 1/2" Clamp over the outlet of the passenger side Muffler. Position the Passenger Side Over Axle Pipe over the axle and loosely attach it to the Muffler. Loosely attach to the Driver Side Over Axle Pipe using the hardware provided. Refer to Figure 10. Note: Additional 5/16" Flat Washers are provided in case spacing is required for adjustments.

8. Slide the **Passenger Side Tail Pipe** onto the **Passenger Side Over Axle Pipe** installing the hanger to the existing rubber insulator. **Refer to Figure 11**.

9. Install and adjust the **Exhaust Tips** to suit. Using a 17mm wrench tighten the lock bolt located on each **Exhaust Tip**.

10. Align the exhaust as required. Starting at the front of the vehicle exhaust, tighten all clamps and connections.

11. Check along the whole length of the exhaust system to ensure that there is adequate clearance around the spare tire, fuel and brake lines.



Congratulations! You are ready to begin experiencing the improved power, sound and driving experience of your MBRP Inc. performance exhaust system. We know you will enjoy your purchase.