



Installation Instructions for 70-1720T

Honda Civic 1996-1998 Keyless Entry Retention

HARNESS FEATURES

- Incorporates the factory keyless-entry security system into the aftermarket installation

HARNESS COMPONENTS

- A) Wiring harness


TOOLS REQUIRED

- Phillips screwdriver • 8mm socket wrench

CAUTION! All accessories, switches, climate controls panels, and especially air bag indicator lights must be connected before cycling the ignition. Also, do not remove the factory radio with the key in the on position, or while the vehicle is running.


Disassembly

1. Remove (2) Phillips screws from the bottom edge of the glove box door, and then remove the door.
2. Remove (3) Phillips screws from the lower steering column panel.
3. Remove (2) Phillips screws under the climate control panel.
4. Remove (4) Phillips screws from the lower dash location.
5. Remove (2) 8mm screws securing the rear of the radio, and then remove and unplug the radio.




Kit Assembly

1. Remove the (2) Phillips screws securing the rear support bracket to the back of the factory radio, and then remove. (Figure A)
2. Re-route the factory wiring harness behind the lower console and plug the female end of the Metra harness into the factory harness. Plug the green security plug into position "A", and then plug the male end of the Metra harness into position "B" in the back of the factory radio. (Figure A)
3. Carefully slide the factory radio between the metal support brackets and place the radio behind the lower dash. (Figure B)



(Figure A)



(Figure B)

Note: The face of the radio should point up.

4. Test the radio and keyless entry for proper operation. Using the instructions found in the 99-7891 or 89-30-7891, secure the assembly to the sub-dash.