

Mobil Multi-Vehicle ATF

Mobil Passenger Vehicle Lube, United States



Automatic Transmission Fluid

Product Description

Mobil Multi-Vehicle ATF is a premium synthetic blend lubricant formulated for use in a wide variety of North American, European, and Asian vehicles.

Features and Benefits

Advantages offered by Mobil Multi-Vehicle ATF over transmission fluids of lower quality are:

- Long fluid life and long transmission life
- Exceptional oxidation stability and resistance to chemical deterioration
- Excellent flow properties at low start-up temperatures and high operating temperatures
- Excellent lubricating characteristics for quiet operation, smooth shifting, and excellent wear protection
- Excellent viscosity stability (high viscosity index) to help assure adequate lubrication without excessive thinning in severe high-temperature service or thickening at low starting temperatures
- Dependable protection against rust and corrosion

Applications

Mobil Multi-Vehicle ATF is a premium lubricant for car and truck automatic transmissions and other applications & recommended by ExxonMobil for use in applications that require an automatic transmission fluid satisfying Ford Mercon and Mercon V performance levels.

Recommended by ExxonMobil for use in applications requiring Dexron III.

Good maintenance practice dictates that automatic transmissions be checked for proper fluid levels at regular intervals, and that the fluid be drained and replaced at intervals recommended by the manufacturer. Some manufacturers recommend more frequent changes of transmission fluid under severe driving conditions such as those that occur in heavy traffic, in hot weather, or when pulling a trailer.

Specifications and Approvals

Mobil Multi-Vehicle ATF meets or exceeds the requirements of:	
Ford Mercon V	X
MAN 339 V1	X

According to ExxonMobil, Mobil Multi-Vehicle ATF is of the following quality level:	
Allison C4	X
Ford MERCON	X
GM DEXRON IIIH	X
GM DEXRON IIIG	X
GM DEXRON IIE	X
GM DEXRON IID	X
GM DEXRON II	X
GM DEXRON	X
JASO 1-A	X
Volvo 97340	X
Volvo 97341	X

Typical Properties

Mobil Multi-Vehicle ATF	
Viscosity	
cSt @ 40°C	34.1
cSt @ 100°C	7.42
cP @ -40°C	9260
Viscosity Index	193
Flash Point, °C (°F)	180 (356)
Gravity, API	34.7
Color	Red

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design are trademarks of Exxon Mobil Corporation, or one of its subsidiaries. DEXRON® and MERCON® are registered trademarks of General Motors and Ford Motor Company, respectively. Chrysler, ATF+3® and ATF+4® are registered trademarks of DaimlerChrysler Motors Company LLC.

12-2016

Mobil Multi-Vehicle ATF	
Specifications and approvals	Technical details
Mobil Multi-Vehicle ATF meets or exceeds the requirements of:	Viscosity
<ul style="list-style-type: none">• Ford MERCON® V• MAN 339 V1	cSt @ 40°C 34.1
According to ExxonMobil, Mobil Multi-Vehicle ATF is of the following quality level:	cSt @ 100°C 7.42
<ul style="list-style-type: none">• Allison C4• Ford MERCON®• GM DEXRON® IIIH• GM DEXRON® IIIG• GM DEXRON® IIE• GM DEXRON® IID• GM DEXRON® II• GM DEXRON®• JASO 1-A• Volvo 97340• Volvo 97341	cP @ -40°C 9260
	Viscosity Index 193
	Flash Point, °C (°F) 180 (356)
	Gravity, API 34.7
	Color Red