



P/N 74055-Battery Installation Kit

This kit has been designed to wire your battery when it has been relocated to the trunk area. All necessary parts are included to make the installation hassle free.

PARTS LIST

20 Ft. 2 GA. Cable	6 Cushion Clamps
1 Double Ended Top Post Terminal	2 Plastic Grommets
4 Terminal Eyes	4 Shrink Sleeves
4 Terminal Fittings	

INSTALLATION

- 1). Determine the location of the battery and battery box. Optimum weight transfer for drag racing will occur when the battery is mounted in the right rear corner of the trunk.
- 2). Measure and determine the positive battery cable length; routing from the battery disconnect switch to the starter solenoid.
- 3). Cut and terminate the 20 ft. cable to length and slide a shrink sleeve over the cable before terminating the ends.
- 4). After installing the terminal eyes on the cable, heat the shrink sleeve so that it seals half on the cable and half on the terminal end.
- 5). Measure, cut and terminate the double ended cable into two pieces. Use one piece for the ground cable and the other for the positive lead to the disconnect switch. A grommet has been provided to protect the positive cable to the disconnect switch if it passes through the floor.
- 6). Secure the cable from the switch to the starter solenoid using the included cushion clamps.

OTHER MOROSO RELATED PRODUCTS:

74100- Master Battery Disconnect Switch
74101- Heavy Duty Master Battery Disconnect Switch
74105- Push/Pull Handle
74145- Thru-Panel Battery Connector
74050- Battery Box