

M206

Metal Aerosol, 6 oz. 078698130200

## **BELT CONDITIONER**

GUNK® Belt Conditioner is for use on all conventional "V" and Micro-V "Flat" Serpentine Belts in Cars, Trucks, Boats, Appliances, Heating & Cooling Systems, Tractors, Machinery, & Heavy Equipment.

## **APPLICATIONS:**

- Conditions serpentine and V-belts for prolonged belt life
- Provides better belt grip and traction while eliminating squeals and chattering
- Latest technology formula

DIRECTIONS: 1. Keep hands away from moving belts and shut motor off before use. Determine if belt tension meets manufacturer's recommended specifications. Examine belt for deterioration, cracks or worn surfaces. If the belt needs adjustment or replacement, take the proper steps to correct. 2. Hold can upright about 12 inches from belt and spray small amount on underside of belt just before the pulley. Use extension tube for hard to reach places. Wipe excess. Allow belt to run for several minutes to distribute product evenly. 3. Repeat every 3 months or 3000 miles to help keep rubber soft and flexible. If belt still squeaks, further adjustment or replacement is necessary. IMPORTANT: Pretest painted, varnished, lacquered or plastic surfaces. Flush surface with water after testing.

**STORAGE, HANDLING & DISPOSAL:** Store in a dry, well-ventilated area below 120°F/49°C. Do not expose to heat, spark, or open flame. Do not puncture or incinerate can. Dispose of product, container and residue in accordance with all local, state and federal laws and regulations.

**DANGER:** FIRE AND EXPLOSION HAZARD: Use only in a well-ventilated area away from heat, sparks, or flame. Do not place container near hot surfaces, batteries or electrical current, due to risk of explosions or flash fire. Use added caution in any confined areas, including basements. BREATHING AND INGESTION HAZARDS: Do not breathe vapors, gas or mist. Use only in well-ventilated area. Harmful or fatal if swallowed. CONTACT HAZARD: Avoid contact with eyes, skin or clothing. Remove contaminated clothing and wash before reuse.

**FIRST AID:** EYES: Flush with water for 15 minutes while lifting eyelids and get prompt medical attention. SKIN: Wash with soap and water. If irritation develops, get prompt medical attention. INHALATION: Move to fresh air. If breathing becomes difficult, get prompt medical attention. INGESTION: If swallowed, do not induce vomiting. Call poison control center, physician, or hospital emergency room immediately.

## **KEEP AWAY FROM CHILDREN AND ANIMALS**

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

NOTICE: While this information is presented in good faith and believed to be accurate, Radiator Specialty Company does not guarantee satisfactory results from reliance thereon. The data is offered solely for your information and Radiator Specialty Company disclaims all liability for any loss or damage from its use. Thoroughly test any application according to the product directions and independently conclude satisfactory performance. Nothing contained herein is to be construed as a recommendation to use the product in violation of any patent.

