



Aftertreatment Service Kit

Compatible with All Makes and Models of Diesel Engine Aftertreatment Systems

PN 307000



The **Aftertreatment Service Kit** is used as part of a cleaning routine to remove particulates and soot that impede or obstruct the honeycomb filter within the front face of the Diesel Oxidation Catalyst (DOC).

This kit will change the way service technicians manage the removal of soot and other particulate matter that builds up on the face of the DOC.

While diesel particulate matter buildup can prevent regeneration of the Aftertreatment System, air cleaning the DOC reduces Aftertreatment exhaust back pressure and enables the technician to safely run a Parked Regen.

A source of compressed air and a shop vacuum equipped with a 2.5-inch diameter hose (and a dust bag to capture soot removed from the DOC) are also required (not included with kit).

KIT INCLUDES:

- 13" Aftertreatment Adapter
- 6" Aftertreatment Adapter
- Retaining Collar
- Retaining Straps
- Blow Gun Assembly

NOTE: PERFORMING AN AFTERTREATMENT DIAGNOSTIC ROUTINE TO IDENTIFY AND CORRECT THE CAUSE BEFORE PERFORMING THIS FACE PLUGGING CLEANING PROCEDURE IS RECOMMENDED. TYPICAL DOC PLUGGING CAUSES ARE VEHICLE SHORT DUTY CYCLES, EXCESSIVE IDLE TIME, STATIONARY PTO OPERATION, OR A HARDWARE ISSUE WITH THE ENGINE.

