

Mud Grappler®



NITTO

EXTREME MUD TERRAIN LIGHT TRUCK TIRE

Wheel Dia.	Tire Size		Stock Number	Tread Depth (1/32")	Inflated Dimensions		Approved Rim (Measuring Rim) Width (in.)	Maximum		
					Overall Dia. (in.)	Overall Width (in.)		Load (lbs.)	@	Press (PSI)
15	33x13.50R15LT C	109Q	200650	21.0	33.07	13.94	8.5-(11.0)	2270	@	35
	35x14.50R15LT C	116P	200580	21.0	34.80	14.57	10.0-(12.0)	2755	@	35
	38x15.50R15LT C	123P	200630	21.0	37.64	15.55	11.0-(12.0)-13.0	3415	@	35
16	LT305/70R16 E	124/121P	201040	19.7	33.07	12.01	8.0-(9.0)-9.5	3525	@	65
	LT315/75R16 E	127/124P	201050	20.7	34.96	12.87	8.0-(8.5)-11.0	3860	@	65
	LT385/70R16 D	130Q	201060	21.0	37.72	15.35	9.5-(11.0)-12.0	4190	@	50
17	33x12.50R17LT E	120Q	200760	21.0	32.95	12.68	8.5-(10.0)-11.0	3085	@	65
	35x12.50R17LT E	125P	200670	21.0	34.84	13.19	8.5-(10.0)-11.0	3640	@	65
	37x13.50R17LT E	131P	200600	21.0	37.05	14.57	8.5-(11.0)	4300	@	65
	40x13.50R17LT D	131Q	200770	21.0	39.72	14.57	8.5-(11.0)	4300	@	50
18	33x12.50R18LT E	118Q	200690	21.0	32.95	12.68	8.5-(10.0)-11.0	2910	@	65
	35x12.50R18LT E	123Q	200550	21.0	35.04	13.39	8.5-(10.0)-11.0	3415	@	65
	37x13.50R18LT D	124P	200660	21.0	37.05	14.17	8.5-(11.0)	3525	@	50
	38x15.50R18LT D	128Q	200500	21.0	37.72	16.30	11.0-(12.0)-13.0	3970	@	50

LT tires with a "C" load range have a 6-ply rating. LT tires with a "D" load range have an 8-ply rating. LT tires with an "E" load range have a 10-ply rating.

Mud Grappler®

(continued)

**NITTO**

EXTREME MUD TERRAIN LIGHT TRUCK TIRE

Wheel Dia.	Tire Size		Stock Number	Tread Depth (1/32")	Inflated Dimensions		Approved Rim (Measuring Rim) Width (in.)	Maximum		
					Overall Dia. (in.)	Overall Width (in.)		Load (lbs.)	@	Press (PSI)
20	33x12.50R20LT E	114Q	200680	21.0	32.95	12.80	8.5-(10.0)-11.0	2600	@	65
	35x12.50R20LT E	121Q	200570	21.0	35.04	13.00	8.5-(10.0)-11.0	3195	@	65
	37x13.50R20LT E	127Q	200540	21.0	37.05	14.13	8.5-(11.0)	3860	@	65
	38x15.50R20LT D	125Q	200510	21.0	37.72	16.30	11.0-(12.0)-13.0	3640	@	50
	40x15.50R20LT D	130Q	200720	21.0	39.72	15.91	11.0-(12.0)-13.0	4190	@	50
22	37x13.50R22LT E	123Q	200530	21.0	37.05	14.13	8.5-(11.0)	3415	@	65
	40x15.50R22LT D	127Q	200520	21.0	39.72	16.30	11.0-(12.0)-13.0	3860	@	50

LT tires with a "C" load range have a 6-ply rating. LT tires with a "D" load range have an 8-ply rating. LT tires with an "E" load range have a 10-ply rating.

Your tires may be the most important components on your vehicle.