



## PART NUMBER

Norton Urethane Seam Sealer

076607**82751**

## PACKAGE SIZE

10.1 fl oz (300 mL)

6/Case



## DESCRIPTION

A one-component, polyurethane seam sealer that cures quickly to a permanent, flexible sealant designed for sealing interior and exterior body joints and seams and duplicates OEM appearance. Paintable in 1 hour. Flexible foil package eliminates product waste. Use with Application Gun (076607**82786**)

## APPLICATION

1. Clean surface with Norton Panel and Adhesive Cleaner (076607**82780**)
2. Using a razor blade, puncture or cut around the end of sausage pack to remove metal clip
3. Load into application gun (076607**82786**)
4. Apply material as needed. After use, store product in gun

## SUBSTRATES

Bare Steel, Bare Galvanized, Bare Aluminum, Primer- Self-Etch, 1K, 2K

## TECHNICAL DATA

PAINT TIME: 1 hour minimum (check for compatibility)  
 CURE TIME: 4 mm after 24 hours (> 1/8 inch per 24 hours)  
 APPEARANCE: White  
 SHELF LIFE: 1 Year

## REGULATORY

CATEGORY: SEALANT			
VOC Actual	<0.83 lb/gal (100 g/l)	Weight % of Exempt Compounds	0
VOC Regulatory	<0.83 lb/gal (100 g/l)	Volume % of Exempt Compounds	0
Weight % Volatiles	7.0 to 8.0%	Density of Material #/gal	9.2 to 10.0 lb/gal
Weight % of Water	0		

## PRECAUTIONS

For professional use only. Before use, read and follow all TDS, label and SDS precautions.



FORM # 8743-82751 REV. 08/19  
 © Saint-Gobain August 2019.  
 Norton is a registered trademark of Saint-Gobain Abrasives.