

STL78/88 SERIES

6" Oval Sealed LED Lights for Surface Mount

- Sonically sealed, waterproof
- Mount in any 360 degree position
- Flange surface mount no panel cut-out required
- · Hard wired with separate ground wire
- Lifetime LED warranty

STL78RB 10-LED red light, hard wired

STL78RPG 10-LED red light, .180 male bullets

STL78REZB 10-LED red light, 3-way female PL-3 plug **STL78RLPB** 10-LED red light, low profile 9/16" thick,

female PL-3 plug, gasket included

STL88RCB 10-LED clear lens red light, hard wired

STL88RCPG 10-LED clear lens red light, 3-way

female PL-3 plug

STL78AB 10-LED yellow light, hard wired

FMVSS: Red I6 P3 S2 T2; Yellow I6 P

MATERIALS: Polycarbonate lens and housing

VOLT/AMP: Red: 12.8VDC - .243A Stop/Turn, .046A Tail

Yellow: 12.8VDC - .275A Turn, .042A Parking

WT/DIMS STL78/88: .265 lbs. / 7.563" x 3.313" x .750"

STL78RLPB: .260 lbs. / 7.563" x 3.313" x .563"

WARRANTY Lifetime LED Warranty







STL78RB



STL88RCB



STL78AB



STL78AB with A78CB1

