



2,200 lb. Capacity Low-Lift Transmission Jack

- The 8-1/4" low height is perfect for aerodynamic trucks with low ground clearance.
- Special mounting adapter fits popular Eaton® Fuller® RoadRanger® transmissions used on nearly all Class 7 and 8 heavy-duty trucks. Mounting plate angle is adjusted with the turn of a wrench.
- Degree of tilt: 20° back, 15° forward, 12° side-to-side.
- Swiveling pump handle permits ease of operation in restricted working spaces. Fast-acting pump quickly raises lifting arm.



No. 5019A – Low-lift transmission jack. Includes No. 540231 adapter for Eaton® Fuller® RoadRanger® transmissions (also available separately).
Wt., 330 lbs.



Model	Capacity (tons)	Overall Length	Overall Width	Max. Height	Min. Height	Weight
5019A	1.1	52"	32-1/2"	36-1/2"	8-1/4"	330 lbs.

Accessories for No. 5019A

No. 540232 – Mack transmission mounting brackets. Provides a stable platform for Mack T200 series transmissions. Wt., 20 lbs., 14 oz.

No. 49611 – Eaton® Fuller® RoadRanger® auxiliary housing adapter. Bolts directly to the countershaft bearing caps to provide a stable platform for removing and installing the auxiliary housing. Wt., 11 lbs., 13 oz.

No. 540231 – Eaton® Fuller® RoadRanger® transmission adapter. Wt., 22 lbs.

No. 528150 – Eaton® "Lightning" adapter. Used with the No. 5019A transmission jack. Wt., 12 lbs.


No. 543284 – RoadRanger® transmission adapter for model series FRO-11210C to FRO-18210C that are equipped with an integrated cooler. Used with the No. 5019A transmission jack. Wt., 19 lbs.



540231




540232



528150



49611



543284



Differential Mounting Adapter for Category 7 & 8 Heavy-Duty Trucks

No. 553516 – Differential Mounting Adapter. Mounts easily using existing bolt patterns. Fits the most common differentials currently in use on Category 7 and 8 Heavy Duty Trucks. Including: Eaton, Fuller, Rockwell, Meritor, Spicer, International, and Mack. For use on OTC 5019A / 5078 and Stinger 1522A Transmission Jacks. Wt., 33 lbs., 4 oz.



553516



553516 shown mounted on OTC 5019A Low-Lift Transmission Jack.