EQUIPMENT: 1595, 5285



1,650 lb. capacity and 2,500 lb. capacity lifts

NEED A LIFT?



7 TRAIN LI

Get set up with OTC shop equipment

FEATURES

OIC

- These lifts will handle engine and transmission assemblies, gas tanks, drive axle assemblies, engine/transaxle assemblies, electric vehicle batteries, and more.
- Scissors-type design allows access to all four sides of a component.
- Two independent adjusting screws tilt the table ± 15° side-to-side, or fore and aft. Can be operated manually or with non-impact air wrench.
- ✓ 20" x 32" table.
- Larger casters provide enhanced mobility under heavy loads.

5285 POWER TRAIN LIFT (1,650 LB. CAPACITY)

- Air / hydraulic operation Foot control pump with hose allows movement around lift.
- Minimum height is 31-1/2" with an 74-1/2" maximum height.

5285 Specifications								
Rated Load	Power	Min. Height	Max. Height	Footprint	Table Dimension	Foot Control	Casters	Table Tilt
1,650 lbs.	Air/ hydraulic	31-1/2"	74-1/2"	33" Wide 48" long	20" Wide 32" long	Pump	8" Swivel	±15°



- Powered by a quiet, 110V electric/hydraulic pump.
- Smooth, steady lifting and lowering motion controlled by hand-held remote.
- Minimum height is 29" with an 80" maximum height.
- A 30 ft. long retractable extension cord is mounted to the frame.

1595 Spec	cifications							
Rated Load	Power	Min. Height	Max. Height	Footprint	Table Dimension	Handheld Control	Casters	Table Tilt
2,500 lbs.	110 VAC	29"	80"	31" Wide 50" long	20" Wide 32" long	2 Button 10" Cord	8" Swivel	±15°

ANSI/PALD compliant.



5285 collapsed



EQUIPMENT: 1585A & 1758



POWER TRAIN LIF



1,250 lb. capacity lift

1585A - POWER TRAIN LIFT (1,250 LB. CAPACITY)

- Ideal for engine and transaxle service.
- Supports up to 1,250 lbs.
- Compact design and swivel casters for easy maneuverability.
- Comes with tilting plate. Height range is 29-1/2" to 68-1/2".

1585A Sp	585A Specifications						
Rated Load	Power	Min. Height	Max. Height	Footprint	Table Dimension	Table Tilt	
1,250 lbs.	Shop Air	29-1/2"	68-1/2"	42-3/4" Wide 58-3/4" long	20-1/2" Wide 30-1/2" long	15° Front/back 17° side/side	



1758 – FUEL TANK HANDLER

- Provides safe and efficient handling of fuel tanks; adjusts horizontally from 24" to 38" and vertically from 7" to 11" to service tanks up to 40 gallons.
- Universal adapter plate fits virtually all competitive transmission jacks in the market.
- Use with OTC Power train lifts Nos.1585A, 5285, 1595 and High-Lift Transmission Jacks No. 1728, 1791, 5237 and OTC Stinger Nos. 1793, 1793A, 1794, 1794A.
- Gearing mechanism ensures equal extension of lift arms to correctly balance load over jack.
- Four support risers individually adjust to ensure perfect fit to any fuel tank design.
- Cross-link polyethylene foam pads protect tanks from damage.





12-93 ©2012 OTC. All rights reserved. Because of ongoing product improvements, we reserve the right to change design, materials, and specifications without notice. Certain kits may require additional cables or adapters. Product shipped may differ from photo(s) shown.

Learn more about automotive tools we have.