

J BEST

ALL-NEW TRANSMISSION JACKS

UNIVERSAL SADDLES, ADJUSTABLE CORNER BRACKETS AND SAFETY CHAINS

ASME PASE-2019 tested with limited lifetime warranty



TJH10 1,000-lb capacity high-lift transmission jacks

- Head tilts front to back and side to side to make removal and installation of transmission and driveline components easier
- Hydraulic system features flash-chromed rams to prevent rust from entering the system, prolonging jack life
- A foot-operated pump and lowering pedal allow for ease of control when positioning or removing a transmission



TJHP10

Air/hydraulic 1,000-lb capacity high-lift transmission jack

- Foot pedals control the air operation, which lifts the head quickly
- A hand pump secondary hydraulic stage allows for precise operator control
- Specially designed with a wide leg base and oversize 5" polyurethane swivel wheels for smooth maneuvering over rough surfaces and small debris, while providing stability and easy placement during jobs

TJHP15

Air-assisted 1,500-lb capacity high-lift transmission jack

- Rugged wall tubing and oversized base add strength and stability for any transmission job
- Foot-operated air pump controls the air-powered hydraulic operation, which lifts the head quickly and effortlessly to the work location
- Big, easy-to-grip knobs make mounting head adjustments simple, and the included safety chains securely hold components during removal, transport and installation

Transmission jack specs

Lift	Min height	Max height	Tilt, forward	Tilt, backward	Tilt, side/side	Wheel size	Air pressure
тјн10	35″	71-5/8""	24°	19°	20°	4″	N/A
TJHP10	37-5/8″	76-1/2″	50°	38°	14°	5″	100 PSI
TJHP15	41-1/2"	65″	50°	38°	14°	4″	80 – 140 PSI

TRANSMISSION JACKS ADAPTERS SHOP EQUIPMENT



TJH10, TJHP10 and TJHP15 are fully compatible with OTC transmission jack adapters



1870 Universal transmission adapter

- Universal fit features four independently adjustable and movable indexing, locking arms
- Adapts to most high or low-lift transmission jacks.
- 400-lb maximum capacity



1758

Fuel tank handler

- Universal adapter plate and adjustability holds tanks up to 40 gallons
- Unique gearing holds load evenly to balance load over jack
- Heavy-duty foam-covered risers protect tanks and are individually adjustable
- Fits most transmission jacks



1797

Heavy-duty clutch adapter

- Adapter allows high or low-lift transmission jacks to handle heavy-duty clutch assemblies
- Expands use of your transmission jack; accepts optional splined shaft adapters – 545765, 48596, 48625, 440533 and 600011.
- Includes safety strap to securely hold clutch when moving or working

1797 adapter shown on TJHP15; jack not included

OIC



Optional splined shaft adapters

545765 – Splined Shaft Adapter, 10 spline, 2" OD, 1.18" Pilot
48596 – Splined Shaft Adapter, 10 spline, 2" OD, 1.08" Pilot
48625 – Splined Shaft Adapter, 10 spline, 1-3/4" OD, 1.18" Pilot
440533 – Splined Shaft Adapter, 10 spline, 1-3/4" OD, 1" Pilot
600011 – Splined Shaft Adapter , 14 Spline, 2" OD, 1.18" Pilot



HEAVY DUTY EQUIPMENT

POWERTRAIN LIFTS



5285 **1,650-LB POWERTRAIN LIFT**

- Air/hydraulic operation with foot control pump
- Scissor design to access all 4 sides of powertrain



5130 **1,000 LB DRIVELINE LIFT**

shafts and more

- Includes 553516 differential adapter Pivoting pump handle to raise/lower
- from multiple positions • For removal of differentials, light-duty transmissions, auxiliary boxes, drive



1595A 2,500-LB POWERTRAIN LIFT

- Air/hydraulic operation with foot control pump
- Scissor design to access all 4 sides of powertrain



1585A **1,250 LB POWERTRAIN LIFT**

- Ideal for engine and transaxle service
- Moves easily around the shop with
- compact design and swivel casters
- Air/hydraulic operation



5295 1,760-LB SPLIT TOP **POWERTRAIN LIFT**

- Sliding split-top helps separate
 powertrains, differentials, axles and more
- High ground clearance for floor crane access when collapsed
- Air/hydraulic lifting mechanism smoothly lifts and lowers components
- Large, tilting tabletop to access all sides of components
- Air/hydraulic operation with foot control pump

Lift Spec.	Capacity (lbs)	Table size	Tilt side/side	Tilt front/back	Min height	Max height	Caster size
5285	1,650	20″ x 32″	15°	15°	31.5″	74.5″	8″
1595A	2,500	20" x 32"	15°	15°	29″	80″	8″
5295	1,760	36" x 42"	N/A	N/A	21.5″	70″	8″
5130	1,000	N/A	15°	15°	7″	30″	4″
1585A	1,250	20.5" x 30.5"	17°	22°	29.5″	68.5″	4″



092019_65



TRANSMISSION JACKS



5019A 2,200 LB TRANSMISSION JACK

- Includes 540231 adapter for Eaton Fuller RoadRanger transmissions
- Pivoting pump handle to raise/lower from multiple positions



5078 2,000 LB HIGH-LIFT TRANSMISSION JACK

- Air/hydraulic operation with foot control pump
- Includes adapter for Allison 500
 and 600-series transmissions





1522A 2,000 LB LOW-LIFT TRANSMISSION JACK

- Includes 220492 adapter for Eaton Fuller RoadRanger transmissions
- Pump handle rotates 360° to raise/lower from multiple positions



1521A 1,000 LB LOW LIFT TRANSMISSION JACK

- Universal mounting head and adjustable brackets for easy transmission alignment
- Pump handle rotates 360° to raise/lower from multiple positions

Lift Spec.	Capacity (lbs)	Min height	Max height	Tilt, forward	Tilt, backward	Tilt, side/side
5019A	2,200	8.25″	36.5″	15°	20°	12°
5078	2,000	41.5″	65″	50°	38°	14°
1522A	2,000	6.875″	35.25″	24°	18°	11°
1521A	1,000	7.5″	29.75″	67°	17°	30°
TJH10	1,000	35"	71-5/8"	24°	19°	20°
TJHP10	1,000	37-5/8"	76-1/2"	50°	38°	14°
TJHP15	1,500	41-1/2"	65"	50°	38°	14°

TRANSMISSION JACKS



TJH10 1,000-LB CAPACITY HIGH-LIFT TRANSMISSION JACKS

- Head tilts front to back and side to side to make removal and installation of transmission and driveline components easier
- Hydraulic system features flash-chromed rams to prevent rust from entering the system, prolonging jack life
- A foot-operated pump and lowering pedal allow for ease of control when positioning or removing a transmission



TJHP10 AIR/HYDRAULIC 1,000-LB CAPACITY HIGH-LIFT TRANSMISSION JACK

- Foot pedals control the air operation, which lifts the head quickly
- A hand pump secondary hydraulic stage allows for precise operator control
- Specially designed with a wide leg base and oversize 5" polyurethane swivel wheels for smooth maneuvering over rough surfaces and small debris, while providing stability and easy placement during jobs



TJHP15 AIR-ASSISTED 1,500-LB CAPACITY HIGH-LIFT TRANSMISSION JACK

- Rugged wall tubing and oversized base add strength and stability for any transmission job
- Foot-operated air pump controls the air-powered hydraulic operation, which lifts the head quickly and effortlessly to the work location
- Big, easy-to-grip knobs make mounting head adjustments simple, and the included safety chains securely hold components during removal, transport and installation

COMPATIBILITY ADAPTER		POWERTRAIN LIFTS				DRIVELINE	LOW-L	LOW-LIFT TRANS JACKS			HIGH-LIFT TRANS JACKS			
	Adapters	5285	1595A	5295	1585A	5130	5019A	1522A	1521A	5078	TJH10	TJHP10	TJHP15	
	558382 Auxiliary box adapter					Yes	Yes	Yes		Yes				
	561949 Light duty transmission adapters					Yes	Yes	Yes		Yes				
	528150 Eaton lightning adapter						Yes							
	543284 Roadranger transmission						Yes							
	49611 Eaton Fuller Roadranger auxiliary housing						yes							
	553516 Differential mounting adapter					Yes, included with lift purchase	Yes	Yes		Yes				



COMPATIBILITY ADAPTER		POWERTRAIN LIFTS			DRIVELINE	LOW-L	LOW-LIFT TRANS JACKS			HIGH-LIFT TRANS JACKS			
	Adapters	5285	1595A	5295	1585A	5130	5019A	1522A	1521A	5078	TJH10	TJHP10	TJHP15
	314729 Allison 5//0600 series adapter									Yes, included with lift purchase			
Hi i i	540231 Eaton Fuller Roadranger transmission adapter						Yes, included with lift purchase						
	540232 Mack transmission mounting brackets						yes						
	5091 HD spindle adapter					Yes	Yes	Yes					
	1870 Universal transmission adapter										Yes	Yes	Yes
	5295-DA Powertrain Lift Differential adapter set			Yes									
	1797 splined shaft adapter										Yes	Yes	Yes
The start	1758 Fuel tank handler	Yes	Yes	Yes	Yes						Yes	Yes	Yes

Learn more about automotive tools on our website.