

MOTOR OIL



PENTO SUPER PERFORMANCE III 5W-30

Fully Synthetic Extended Life Engine Oil

DESCRIPTION

5W-30 Pento Super Performance III is a newly formulated high performance engine oil designed to be used in vehicles that call for extended oil drain intervals. This oil is blended by using some of the most modern additives available and carefully selected synthetic based oils. By doing this the oil is considered a “Low SAPS” formulation that preserves catalysts, the environment, and maintains outstanding engine performance.

PRODUCT ATTRIBUTES

Appearance	Amber & Clear
Density at 15°C	849 kg/m ³
Density at 20°C	850 kg/m ³
Kinematic Viscosity at 100°C	11.7 mm ² /s
Kinematic Viscosity at 40°C	71.4 mm ² /s
Viscosity Index	160
Dynamic Viscosity at -30°C	6530 mPa*s
Pour Point	-48°C/-54.4°F
Flash Point	240°C/464°F

SIZE	PART NUMBER	GTIN-13
1 Liter	8078106	4008849115431
5 Liter	8078206	4008849115448
20 Liter	1078208	4008849115301
60 Liter	1078303	4008849111563
210 Liter	1078305	4008849111761

OE REFERENCE NUMBERS

Make	Reference Number
Audi/Volkswagen	GAU 052 195 M2
Audi/Volkswagen	GVW 052 195 M2
Audi/Volkswagen	G 052 195 M4
Audi/Volkswagen	G 052 195 M6
BMW	83 21 0 398 507
BMW/Mini	83 21 0 398 508
Mercedes Benz	000 989 89 01 10

APPROVALS/SPECIFICATIONS

Organization Name	Specification Met
Audi/Volkswagen	504.00, 507.00
BMW	LL-04
Mercedes Benz	229.51
ACEA	A3/B4
API	Exceeds SM Class

Always consult the vehicle owner's manual to identify fluid specification requirements. MSDS available to professional installer upon request.