

BRAKE FLUID



PENTOSIN SUPER DOT 4

Corrosion Resistant Universal Brake Fluid

DESCRIPTION

Pentosin Super DOT 4 is a brake fluid of superior quality for universal use in modern brake systems and ideal for vehicles with ABS systems. Pentosin Super DOT 4 offers safety against vapor lock; it has excellent resistance to absorbing and retaining water and provides superior corrosion resistance.

PRODUCT ATTRIBUTES

Appearance	Yellow & Clear
Density at 20°C	1065 kg/m ³
Kinematic Viscosity at 40°C	7.9 mm ² /s
Kinematic Viscosity at 20°C	14.5 mm ² /s
Kinematic Viscosity at -40°C	≤ 1500 mm ² /s
Melting Point	>-50°C/>-58°F
Flash Point	130°C/266°F
Ignition Temperature	>200°C/>392°F
Boiling Point	≥265°C/≥509°F
Wet Boiling Point	≥165°C/≥329°F
pH Value	8

SIZE	PART NUMBER	GTIN-13
0.25 Liter	1204112	4008849204036
0.5 Liter	1204114	4008849204067
1 Liter	1204116	4008849204074
5 Liter	1204204	4008849204159

OE REFERENCE NUMBERS/RECOMMENDATIONS

Make	Reference Number
Audi/Volkswagen	B 000 700 A1
Audi/Volkswagen	B 000 700 A3
Audi/Volkswagen	B 000 700 A6
BMW/Mini	81 22 9 407 510
BMW/Mini	81 22 9 407 511
BMW/Mini	81 22 9 407 512
BMW/Mini	81 22 9 407 513
Land Rover	LRNDOT4
Mercedes Benz	000 989 08 07 10
Mercedes Benz	000 989 08 07 11

OE REFERENCE NUMBERS/RECOMMENDATIONS

Make	Reference Number
Mercedes Benz	000 989 08 07 19
Porsche	000 043 203 66
Porsche	000 043 203 67

APPROVALS/SPECIFICATIONS

Organization Name	Specification Met
MAN	TUC 6518/07
FMVSS	No. 116 DOT 4
ISO	4925 Class 4
SAE	J1704

Always consult the vehicle owner's manual to identify fluid specification requirements. MSDS available to professional installer upon request.