



Technical Data Sheet

Permatex® Contact Cement

PRODUCT DESCRIPTION

S.I.N.: 834-300

Permatex® Contact Cement is a neoprene based adhesive designed for fast grab and high strength.

PRODUCT BENEFITS



- Moisture resistant
- Fast grab
- Dries quickly

TYPICAL APPLICATIONS

- Weatherstripping
- Rubber, glass, metal

DIRECTIONS FOR USE

1. Surfaces to be bonded must be free from moisture, dirt, grease, wax, rust or scale.
2. Apply a uniform coat to both surfaces to be bonded. Allow to air dry for a minimum of 10 minutes.



3. Reassemble and apply even pressure over the entire area.
4. The adhesive will develop about 90% of its strength within 24 hours.
5. May be brushed on with fast drying.
6. May be applied with a paint roller.

For Cleanup

1. For clean-up, use lacquer thinner.
2. Clean brushes and rollers quickly after use.
3. Clean hands with a dry cloth or Permatex® Fast Orange® hand cleaner.

PROPERTIES OF UNCURED MATERIAL

	Typical Value
Chemical Type	Neoprene rubber
Appearance	Amber medium syrup
Odor	Petroleum
Specific Gravity	0.79
Flash Point, Setaflash, °F	<0

TYPICAL ENVIRONMENTAL RESISTANCE

Temperature Resistance	Typical Values
Continuous, °C (°F)	49(120)

Chemical / Solvent Resistance

The product retains effective properties in contact with motor oil, moisture.

GENERAL INFORMATION

This product is not recommended for use in pure oxygen and/or oxygen rich systems and should not be selected as an adhesive for chlorine or other strong oxidizing materials.

For safe handling information on this product, consult the Material Safety Data Sheet, (MSDS).

ORDERING INFORMATION

Part Number	Container Size
25905	1.5 fl. oz. tube, carded

STORAGE

Products shall be ideally stored in a cool, dry location in unopened containers at a temperature between 8° to 28°C (46° to 82°F) unless otherwise labeled. Optimal storage is at the lower half of this temperature range. To prevent contamination of unused product, do not return any material to its original container.

NOTE

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. **Permatex, Inc. specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Permatex, Inc. products and disclaims any liability for consequential or incidental damages of any kind, including lost profits.**

This product may be covered by one or more United States or foreign patents or patent applications.