



Technical Data Sheet

Permatex® Aerosol Anti-Seize Lubricant

PRODUCT DESCRIPTION

S.I.N.: 834-300

Permatex® Anti-Seize Lubricant is a heavy duty, high temperature aerosol lubricant that prevents galling, seizing and corrosion during assembly and assures easier disassembly. Also reduces wear in heavy pressure applications. The product contains tenacious metals, oils and graphite materials that can be used on slow moving parts.

PRODUCT BENEFITS

- Effectively lubricates assemblies exposed to high temperatures and heavy contact pressures
- Suitable for service up to 870°C (1,600°F)
- Reduce corrosion and seizing due to weathering or chemicals
- Permits easy disassembly of parts exposed to heat or corrosive environments

TYPICAL APPLICATIONS

- Spark plug threads installed into aluminum heads
- Exhaust manifold and engine bolts
- Anchor pins on brake assemblies
- U-bolts and spring bolts
- Lubricates and permits easy disassembly of assemblies exposed to high temperatures and heavy contact pressures, such as boiler and oven parts, jet engines, and industrial turbines.
- Hinges, gears, chain, sprockets and rollers

DIRECTIONS FOR USE

1. Provide adequate ventilation.
2. For best results, apply to clean, dry surfaces.
3. Tap bottom of can to loosen the ball agitator. Shake can for 2 minutes. For best results, aerosol can should be at room temperature before spraying.
4. Holding can 8 to 10 inches from the surface to be coated, press the nozzle and uniformly discharge the product to the surface.
5. Spray or apply a light coat of the product directly to parts where lubrication/protection is desired.



6. Wipe off excess material.

For Cleanup

1. Turn can upside-down and spray to clear nozzle.
2. Clean hands with Permatex® brand hand cleaners.

PROPERTIES OF MATERIAL

	Typical Value
Chemical Type	Grease
Appearance	Silver metallic liquid
Odor	Light petroleum
Specific Gravity	1.17 (base)
Temperature Range, _C (_F)	870 (1,600)
Viscosity, cPs	200,000 (base)
Flash Point	Aerosol, contents under pressure, consult MSDS
NFPA 704 Flammability Rating	4 (Highly Flammable)
Particle size, µm	22.5

GENERAL INFORMATION

This product is not recommended for use in pure oxygen and/or oxygen rich systems and should not be selected for use with chlorine or other strong oxidizing materials.

For safe handling information on this product, consult the Material Safety Data Sheet, (MSDS).

ORDERING INFORMATION

Part Number	Container Size
81464 (133MA)	12 oz. aerosol can

STORAGE

Products shall be ideally stored in a cool, dry location in unopened containers at a temperature between 8_ to 28_C (46_ to 82_F) unless otherwise labeled. Optimal storage is at the lower half of this temperature range.