AUXILIARY GABLE FAMILY The Extra Power You Need!

ISOCOIL[™]

- For ISO/auxiliary applications
- Flexible from -82°F to 195°F (-63°C to 91°C)
- Excellent recoil memory, chemical & abrasion resistance
- Twisted pair brown & green wires reduces signal noise

- Spring-wrapped compression contact pins
- Male ground pin to prevent mis-connections
- Heavy-duty, reinforced zinc die-cast plugs

Part No.	Description
31-9323	12', with zinc die-cast plugs
31-9623	15', with zinc die-cast plugs
31-9923	15', 48" lead, with zinc die-cast plugs

ISOFLEXTM

reduces signal noise

- For ISO/auxiliary applications
- Good chemical and abrasion resistance
 Twisted pair brown & green wires
- Spring-wrapped compression
- contact pins
- Male ground pin to prevent mis-connections
- Heavy-duty, reinforced zinc die-cast plugs

Part No.	Description
31-2033	10', with zinc die-cast plugs
31-2053	12', with zinc die-cast plugs
31-2073	15', with zinc die-cast plugs
31-2093	20', with zinc die-cast plugs

ACCESSORY CABLE

- For ISO/auxiliary applications
- Brown & green wires are not twisted
- Flexible from -82°F to 195°F (-63°C to 91°C)
- Good recoil memory, chemical & abrasion resistance

Part No.	Description		
31-4323	12', with zinc die-cast plugs		
31-4623	15', with zinc die-cast plugs		

- Spring-wrapped compression contact pins
- Male ground pin to prevent mis-connections
 Heavy-duty, reinforced zince
- Heavy-duty, reinforced zinc die-cast plugs

P	L	P	5



