

JK BRAWLER MID FRONT BUMPER INSTALLATION



The Poison Spyder Customs Brawler MID Front Bumper is easy to install with the right tools and good mechanical abilities. If you are not confident in your mechanical skills, please seek the help of a professional to perform the installation. Please read through these entire instructions before proceeding with installation.

PARTS LIST

Please check your packages immediately upon arrival to ensure that everything listed is included, and to check for damage during shipping. The locknuts and washers are shipped attached to the mounting studs inside the bumper.

- (1) JK Brawler MID Front Bumper
- (8) 1/2-13 nylon insert lock nut
- (8) 1/2 flat washer

TOOLS NEEDED

- Ratchet with 6" socket extension, 19mm deep socket and 3/4" deep socket
- Torque wrench (ft./lbs.)
- 7/32" hex key
- Dead blow hammer or rubber mallet
- Phillips & flat head screwdrivers
- Removal tool for push-in retainer clips or small pry bar

BEFORE YOU BEGIN

The JK Brawler MID Front Bumper and associated components are shipped un-painted.

Before you paint or powder coat, perform the entire installation of the product to ensure that it fits without risking damage to your paint or powder coat finish. Poison Spyder Customs is not responsible for paint or powder coat costs in the event you damage the finish during installation, or that the parts are incorrect or defective.

You will want to paint or powder-coat these components prior to FINAL installation. If painting them yourself, we recommend starting with a quality etching primer and allowing sufficient cure/dry time between coats and before you apply color. Quality spray-can paints are fine, however be sure to thoroughly paint all of the inside corners and hard-to-reach areas of the bumper. A little extra time and attention to detail on your preparation and paint process will pay off in longer-lasting good looks and rust prevention.

INSTALLATION PROCEDURE

1. **Park vehicle on a level** surface and set the emergency brake. You will want to wear eye protection beyond this point.
2. **Remove the plastic lower air dam.** Use a push-in retainer removal tool to pop out the plastic push-in retainers along the front edge and also underneath/behind the air dam where it attaches to the crash bar. If you do not have a push-in retainer tool, a flat-edge screwdriver or small pry-bar may be used.



FIGURE 2

Poison Spyder Customs • JK BRAWLER MID FRONT BUMPER

3. If your Jeep is equipped with factory fog lamps, reach behind the bumper and disconnect the wiring harness plugs from the sockets at the back of each lamp. A small flat head screwdriver may be useful to release the tangs on the plug
4. Use a ratchet and 19mm deep socket to remove the eight (8) nuts that fasten the bumper to the frame. There are two of these nuts on the inner side, and two on the outer side, of each frame rail where it joins the bumper.



FIGURE 3

With these nuts removed, remove the bumper from the Jeep.



FIGURE 4

5. If your Jeep is equipped with factory fog lamps, these may be removed from the stock bumper and re-installed into the Brawler MID bumper. Use a Phillips screwdriver to remove the four (4) retaining screws from each lamp, on the back side of the bumper.



FIGURE 5

Install the factory fog lamps into the fog lamp mounts in the back side of the Brawler MID bumper. Re-use the OE retaining screws. These sheetmetal screws will form their own threads as you drive them into the retaining rings on the RockBrawler bumper, so press firmly as you twist the screwdriver.



FIGURE 6

6. Remove the plastic top bumper cover. You may be able to remove the two plastic screws with a Phillips screwdriver. But it is likely they're "frozen" in place and will have to be pried up with the push-in retainer removal tool.



FIGURE 7

Poison Spyder Customs • JK BRAWLER MID FRONT BUMPER

IMPORTANT: If installing the optional Skid Plate, refer at this point to the instructions that came with the Brawler MID Skid Plate, and proceed with those steps. Return to these instructions and proceed with the next step, below, once the Skid Plate installation instructions have been completed.

- 7. Install the Bumper onto the frame.** There are eight (8) threaded studs located on the inside/backside of the bumper, which will correspond with the bumper mounting holes on the frame. It may be a tight fit due to slight manufacturing variances from Jeep to Jeep, but the bumper will fit with some gentle persuasion. You may need to use a rubber mallet or soft dead-blow hammer to tap the bumper into place. Be careful not to mar your paint or powdercoat finish.
- 8. Locate the 1/2-13 nylon insert lock nuts and 1/2" flat washers** that came with your bumper (usually these are shipped threaded onto the studs). Install a flat washer and lock nut onto each of the eight bumper mounting studs at the outside and inside of the frame rail on either side of the Jeep. Snug these with the 3/4" deep socket, extension and ratchet. Torque these nuts to 70 ft.-lbs.
- 9. If you installed the OE fog lamps** into the Brawler MID bumper, plug the harness connectors back into the sockets in the back of each lamp. The OE wire harness may be secured with stick-on harness anchors and zip-ties (not provided).

Congratulations, you have completed the installation of your Poison Spyder JK Brawler MID Front Bumper!

INSTALLATION INSTRUCTIONS

Poison Spyder Customs • JK BRAWLER MID FRONT BUMPER

WARRANTY

Poison Spyder Customs™ warranties all of the products we sell and distribute for one (1) year from the date of sale. These products will be free from defects in material and workmanship under normal installation, and use. Due to the intended use the powder coat finish is warranted for ninety (90) days. The finish warranty will not cover a product if it has been damaged in any way. Warranty is limited to repair or replacement. Poison Spyder Customs™ does not offer any type of labor or shipping allowance and all warranty claims are subject to inspection by Poison Spyder Customs™.

At the discretion of Poison Spyder Customs™, the products in question can be repaired or replaced when found defective. Prior to any replacement or repair, written authorization must be obtained from Poison Spyder Customs™. Failure to contact us prior to having warranty work performed will immediately void all applicable warranties; and it is then the sole responsibility of the customer to remit any payment incurred.

The warranty expressed above is the sole warranty of Poison Spyder Customs™, and any other expressed or implied warranties are hereby specifically excluded and disclaimed.

HOLD HARMLESS AGREEMENT

In purchasing a Poison Spyder Customs Product™ I release, waive, discharge and covenant not to sue Poison Spyder Customs officers, servants, agents, or employees (hereinafter referred to as Releasees) from any and all liability, claims, demands, actions and causes of action whatsoever arising out of or related to any loss, damage, or injury, including death, that may be sustained by me (or anyone else), any property belonging to me (or anyone else), whether caused by the negligence of the releasees or otherwise, while working on, using or any activity related to this product.

I am fully aware of risks and hazards connected with the use of a this product and I elect to voluntarily engage in such use of this product knowing that the use may be hazardous to me and my property. I voluntarily assume full responsibility for any risks of loss, property damage or personal injury, including death, that may be sustained by me (or anyone else), or

any loss or damage to property owned by me (or anyone else), as a result of using this product, whether caused by the negligence of releasees or otherwise.

I further agree to indemnify and hold harmless the releasees from any loss, liability, damage or costs, including court cost and attorney fees, that they may incur due to my use of a this product, whether caused by negligence of releasees or otherwise.

It is my express intent that this Release and Hold Harmless Agreement shall bind the members of my family and spouse, if I am alive, and my heirs assigns and personal representative, if I am deceased, and shall be deemed as a release, waiver, discharge, and covenant not to sue the above named releasees. I further agree that this Waiver of Liability and Hold Harmless Agreement shall be construed in accordance with the laws of the State of California.

By accepting this product, I acknowledge and represent that I have read the above Waiver and Liability and Hold Harmless Agreement, understand it and accept it voluntarily as my own free act and deed; no oral presentations, statements, or inducements, apart from the foregoing written agreement, have been made; I am at least eighteen (18) years of age and fully competent; and I execute this Release for full, adequate and complete consideration fully intending to be bound by same.

If you do not agree with the preceding Hold Harmless Agreement, you may return the product and receive a full refund. Please, contact a Poison Spyder Customs™ sales representative and they will issue a call tag for the product in question. Once the product has been received by Poison Spyder Customs™ a full refund will be issued.

INSTALLATION INSTRUCTIONS