

2015+ GMC Sierra HD Boss Grille Installation Instructions

Please read all instructions before installation and to check to see that all parts are included.

KIT CONTENTS:	
Description	Qty.
Boss Grille	1
1/4" - 20 x 3/4" SS bolt	6
1/4" - 20 SS Lock Nut	6
1/4" SS Washer	6
Only for Lighted Grille (below)	
10" Luminix Light	2
Wiring Harness	1
Switch	1
Light Bar Installation Instructions	1

Tools Needed:

- 7mm, 10mm Wrench
- Flat Head Screw Driver
- Saw- Recommended:
Oscillating Hand Tool
- Pliers

Grille Installation

1. Remove Grille from packaging. Check to see if all parts from above table of kit contents are included.



2. Remove plastic cover by removing 12 retaining clips with flat head screw driver (locations shown above).



3. Once cover is removed, remove the top 4 grille screws with 10mm wrench (location shown above).



4. Remove grille by pulling grille forward away from the truck.
5. Use saw to cut inner section of grille out (white lines below).



Before



After

6. Insert Putco grille into the grille shell. Position grille in grille shell and mark holes through brackets for drilling. Removed Putco grille and drill 1/4" holes in locations marked.
7. Reinsert grille into grille shell and bolt in using supplied hardware. Bolt head goes against bracket on the back of the Putco grille. Tighten bolts using a 7/16" wrench.
8. Reinstall grille shell by following steps 4 through 1.

For Lighted grilles, refer to Wiring Installation on Light Bar Installation Instructions for wiring instruction