



Installation Instructions

Upper Door Skin 897XX 97-06 Jeep Wrangler

IMPORTANT NOTICE:

Carefully read instructions before attempting to install this product. Rampage Products is not responsible for any damage to the vehicle or personal injury that may occur during the installation or use of this product.

WARNING

This product is designed to enhance the appearance of the vehicle and only for protection against the elements. Do not rely on this product to contain occupants within the vehicle or to protect against injury during an accident.

WEAR SEAT BELTS AT ALL TIMES

UPPER SKIN INSTALLATION TIPS

To help ease the installation, be sure to install the Upper Skins when temperatures are above 70° F. The material shrinks substantially at lower temperatures and may become difficult to install. The Skins may seem wrinkled when first installed; this is caused by the fabric becoming wrinkled in shipping. It will relax after a few days on the vehicle. NOTE: Over the years, many different companies have produced upper door frames, and while they are similar, the exact dimensions will vary, which may require adjustments in installation. The Velcro attachment system allows for frame variables, but should not be secured until all 4 corners are attached. The skin may appear tight at first, but will stretch and adjust into position as you follow steps 1 thru 4 in the attached illustration. Please insure the window is unzipped until skin installation is complete.

Upper Window Skin Installation

1. After removing Upper window Skins from packaging, leave the skins out in sunlight for at least one hour (above 70° F).
2. Remove old window skin from frame (cutting may be required).
3. Un-zip (open) window on skin to help ease installation.
4. Install upper skin on frame in the order shown below **Figure 1**.
5. Adjust skin and tighten Velcro.

(WINDOW FRAME SHOWN FOR INSTALLATION, NOT INCLUDED)

