WIRELESS BACKUP CAMERA SYSTEM WITH MIRROR MONITOR

SAFETY

A Safe Fleet Brand

RVS - 091407



The new Digital Wireless Backup Camera System will revolutionize the backup camera industry. The new digital wireless camera guarantees no interference up to 70ft so you get a great and beautiful picture at all times. The system is complete with a color 4.3" TFT-LCD Mirror Monitor with distance grid lines which can either attach to the existing rear view mirror or replace it. The camera boasts a 130° MTV136 High Definition camera with 9 infra-red night vision lights which enables you to see in total darkness. The backup system comes with all the wires, connectors and mounts you will need. The camera is completely weatherproof with an IP68 rating, strong and reliable, shock resistant, with a 10G vibration rating (highest in the industry). It comes with a full year warranty.

WIRELESS BACKUP CAMERA SYSTEM WITH MIRROR MONITOR RVS - 091407



- SUPER SHARP 4.3"TFT LCD DISPLAY MIRROR MONITOR
- COMPLETELY WEATHERPROOF WITH AN IP68 RATING
- 130° MTV136 HIGH DEFINITION CAMERA WITH 9 INFRA RED NIGHT VISION
- SHOCK RESISTANT WITH A 10G VIBRATION RATING



MONITOR

TYPE SCREEN SIZE DOT RESOLUTION DISPLAY FORMAT DISPLAY BRIGHTNESS VIEWING ANGLE VIDEO INPUT VIDEO SOURCE POWER SUPPLY POWER CONSUMPTION OPERATING TEMPERATURE VIDEO SYSTEM OVERALL DIMENSIONS WEIGHT VIBRATION RATING SYNC AREA SYNC SYSTEM

TFT LCD 4.3" 1440 (H) X 234 (V) 16:9 350CD/m 90° 1 CHANNEL 1VP - P. 75 Ω DC 12V - 24V (+/- 10%) 5W -10 °C ~ +65 °C AUTO NTSC / PAL 10"(L) X 3.5"(H) X 1"(D) 400G 5G 154.08 (H) X 86.58 (V)

INTERNAL

CAMERA

SENSOR PICTURE ELEMENTS GAMMA CORRECTION IMAGE SENSOR

LENS

VIEW ANGLE

SYNC SYSTEM

INTERNAL S

INFRA - RED DISTANCE

USABLE ILLUMINATION

POWER SOURCE

S/N RATIO

ELECTRONIC IRIS

VIDEO OUTPUT

IR SWITCH CONTROL

VIBRATION AND IMPACT RATING

OPERATING TEMPERATURE

STORAGE TEMPERATURE

2.1MM

130°

100 FEET (9 II)

0 LUX (IR OF

0 LUX (IR OF

0 LUX (IR OF

1/50, 160-1)

1/50, 160-1)

1/50, 160-1)

1/50, 160-1)


1/50, 160-1)


2.5°C ~ +50

-25°C ~ +60

250,000 PIXELS R=0.45 TO 1.0 480 TV LINES, PAL: 500 (H) X 582 (V) NTSC: 510 (H) X 492 (V) 2.1MM 130° INTERNAL SYNCHRONIZATION 30 FEET (9 INFRARED) 0 LUX (IR ON) DC 12V-24V (+/- 10%) MORE THAN 48DB 1/50, 160-1/100,000SEC 1VP - P, 75 Ω ACDS AUTOMATIC CONTROL -25°C ~ +50°C / RH 95% MAX -25°C ~ +60°C / RH 95% MAX

MT9V136










WIRELESS BACKUP CAMERA

Our Wireless Backup Camera is designed to mount flush on the back of the vehicle but comes with a mounting bracket as a second option. Its MT9V136 lens gives you a viewing angle of 130° and 480 TV lines for the best quality image. The 9 infra-red lights on this camera provide perfect vision up to 30 feet even in the darkest night. With extremely strong weatherproof casing and an IP68 rating, this camera is fit to ride out any storm.



WIRELESS MIRROR MONITOR

This Mirror Monitor attaches to the windshield, either connecting to or replacing the existing rear view mirror and connects wirelessly to the backup camera. Its reflective surface allows it to act both as a rear view mirror and as a monitor for the backup camera. The Wireless Mirror Monitor comes with a 4.3" TFT LCD Digital Display and its menu can be navigated with the on dash buttons.

Learn more about other cameras & driver safety products by Rear View Safety on our website.