


Wireless Backup Camera System with 5" Single Screen Monitor

RVS-155W

REAR VIEW
SAFETY
A Safe Fleet Brand



Perfection takes time, especially with something as complicated as wireless transmission. Our newest system was born from years of testing and multiple prototypes. Introducing a wireless camera system that really works in all conditions. This one camera setup boasts a 100' digital wireless range which is guaranteed to work even at highway speeds. Installation takes less than an hour and with a cigarette lighter plug or hardwire kit, the monitor installs instantly.



INSTANT PAIR

The Instant Pair feature allows you to pair the monitor to camera without leaving your cab. Simply hit **PAIR** on your monitor and turn on power for your trailer, and the backup camera and monitor will pair automatically.



RVS-155W

Wireless Backup Camera System with 5" Single Screen Monitor

Mounting Brackets

Attach your monitor to the dashboard (1) or windshield (2)



SYSTEM SPECIFICATION

MONITOR

PANEL SIZE	5" LED DIGITAL PANEL
VIDEO SYSTEM	NTSC / PAL AUTO DETECTION
RESOLUTION	480 X 3 (RGB) X272
BRIGHTNESS	450 CD/m ²
CONTRAST RATIO	500:1
SCREEN MODE	16:9
FIELD OF VIEW	TOP 50°, BOTTOM 70°, L/R 70°
AUDIO OUTPUT	OPTIONAL; 0.5W SPEAKER
DOT PITCH	0.077(W) × 0.231(H) MM
ACTIVE AREA	110.000(W) × 62.832(H) MM
POWER INPUT	DC10-32V
OPERATING TEMP.	-20°C ~ +70°C RH 90% MAX
STORING TEMP.	-30°C ~ +80°C RH 90% MAX
FREQUENCY	2400-2500MHZ
TRANSMISSION TYPE	DIGITAL WIRELESS
VIDEO INPUT	1 CHANNEL
VIDEO SOURCE	1VP-P 75Ω
AUTO PAIR	YES
POWER CONSUMPTION	ABOUT 4W
POWER SUPPLY	DC9-32V


CAMERA

SENSOR	1099 COLOR CAMERA
EFFECTIVE PIXEL ARRAY	976 (H) X 496 (V)
PICTURE ELEMENTS	480,000 PIXELS
NTSC OUTPUT	720 (H) X 480 (V)
PAL OUTPUT	720 (H) X 576 (V)
OPTICAL FORMAT	1/4 INCH
CAMERA CORRECTION	R=0.45-1.0
LENS	F=2.5MM
WATERPROOF RATING	IP69K
POWER CONSUMPTION	ABOUT 3.5W(IR ON)
POWER INPUT	DC10-32V
OPERATING TEMP.	-40°C ~ +70°C RH 90% MAX
STORING TEMP.	-40°C ~ +80°C RH 90% MAX
FREQUENCY	2400-2500MHZ
TRANSMISSION TYPE	DIGITAL WIRELESS
TRANSMISSION RANGE	100FT
VIDEO SOURCE	1VP-P 75Ω
S/N RATIO	MORE THAN 48 DB
WHITE BALANCE	AUTO
IR CONTROL	AUTO




WIRELESS THAT WORKS

Perfection takes time, especially with something as complicated as wireless transmission. This new system went through years of testing and multiple prototypes until we got it just right.



100' TRANSMISSION

We guarantee this system to work up to 100ft. It's digital wireless transmission was perfected to work even at long distances with no interference.




HIGHWAY SPEEDS

Our transmission guarantee applies even at highway speeds! This means that even while travelling at 60-70mph, the system will hold the signal.



WATERPROOF + NIGHT VISION

With an IP69K rating (highest IP rating there is), the camera works in all weather conditions. 18 infra-red lights ensure a perfect view even on the darkest night.




DUAL POWER OPTION

System comes with two powering options - a cigarette lighter plug and a hard wire option. Either wire it to the vehicle's fuse box or plug it right into the 12V outlet!



EASY INSTALL + INSTANT PAIR

System installs in under an hour and comes with instant pair which allows you pair the camera and monitor together without leaving the cab.



Learn more about other cameras & driver safety products by Rear View Safety on our website.