

BACKUP CAMERA SYSTEM WITH 5.6" MONITOR RVS - 7706033

REAR VIEW
SAFETY
A Safe Fleet Brand



This backup camera system is complete with a crystal clear 5.6" TFT DIGITAL LCD Color Monitor with mirror image capability and optional distance grid lines. It can connect up to 3 cameras with automatic system switch. The system includes one 130° CCD camera with 50 foot infra-red night vision and all the wires, connectors and mounts you will need. The rear view system is completely weatherproof with an IP69K rating, strong and reliable, shock resistant, with a 20G vibration (highest in the industry). It comes with a full year warranty.

BACKUP CAMERA SYSTEM WITH 5.6" MONITOR

RVS - 7706033

**REAR VIEW
SAFETY**
A Safe Fleet Brand

- CAMERA IS COMPLETELY WEATHERPROOF WITH AN IP69K RATING
- 5.6" DIGITAL TFT LCD COLOR MONITOR WITH MIRROR IMAGE CAPABILITY
- 1/3" SHARP® COLOR CCD, 410K PIXELS, 2.5 MM WIDE LENS WITH 130° ANGLE
- 3 CHANNELS ALLOWING YOU TO CONNECT ADDITIONAL CAMERAS
- SHOCK RESISTANT WITH A 20G VIBRATION AND 100G IMPACT RATING



MONITOR

TYPE	TFT LCD
SCREEN SIZE	5.6"
DOT RESOLUTION	800 X 3 (RGB) X 480
DISPLAY FORMAT/CONTRAST	16:9 / 500:1
DISPLAY BRIGHTNESS	400CD/m ²
VIEWING ANGLE	U:50° D:60° L/R:70°
VIDEO INPUT	3 CHANNEL
VIDEO SOURCE	1VP-P, 75Ω
POWER SUPPLY	DC 9V-32V
POWER CONSUMPTION	5W
OPERATING TEMPERATURE	-30° C ~ +80° C
VIDEO SYSTEM	AUTO NTSC/PAL
OVERALL DIMENSIONS	5" (L) X 5" (H) X 1" (D)
WEIGHT	400G
VIBRATION RATING	5G
DOT PITCH	154.08 (H) X 86.58 (V)
SYNC SYSTEM	INTERNAL

CAMERA

CAMERA	1/3" SHARP® COLOR CCD
PICTURE ELEMENTS	410,000 PIXELS
GAMMA CORRECTION	R=0.45 TO 1.0
IMAGE SENSOR	620 TV LINES
PIXELS	PAL: 752 (H) X 582
	NTSC: 811 (H) X 507 (V)
LENS	F=2.5MM
VIEW ANGLE	130°
WATERPROOF RATING	IP69K
SYNC SYSTEM	INTERNAL SYNCHRONIZATION
INFRA-RED DISTANCE	50 FEET (18 INFRARED)
USABLE ILLUMINATION	0 LUX (IR ON)
POWER SOURCE	DC 9V-32V
S/N RATIO	MORE THAN 48DB
ELECTRONIC IRIS	1/50, 160-1/100,000SEC
VIDEO OUTPUT	1VP - P, 75 Ω
IR SWITCH CONTROL	ACDS AUTOMATIC CONTROL
VIBRATION AND IMPACT RATING	20G / 100G
OPERATING TEMPERATURE	-40°C ~ +70°C / RH 95% MAX
STORAGE TEMPERATURE	-40°C ~ +85°C / RH 95% MAX
NET WEIGHT	220Z



Same camera is used in hundreds of OEM applications



System usually outlives the vehicles they are mounted on



Installation Time: 2 hours

Adjustable Sunshade



Built In Mic



18 Infra-Red Lights

For ultimate vision at night



Weighs 22 Ounces

Commercial grade build



Heavy Duty Metal



Auto Iris Sensor

Infra-reds adjust strength based on outside light



IP69K Rating

Protected against close range, high pressure spray downs

BACKUP CAMERA

This 1/3" Sharp® CCD Color Camera is built with heavy duty zinc metal which encases the 2.5 mm Sharp® lens. It has a viewing angle of 130° and 620 TV lines, which means you get the best quality image with no blind spots. The 18 infra-red lights allow you to see up to 50 feet even in the darkest of night, and the foam around the lens guarantees no glare from these infra-reds. With an IP69K rating, this camera is fit to ride out any storm and boasts a 20G vibration. This device comes equipped with Aircraft Grade cable connections.

Auto Dimming
Screen dims in low light



Super Sharp Digital Image



TFT LCD Display
Just one inch thin



5.6 Inch Display



Distance Grid Lines

Optional: can be switched on or off



Built In Speaker



Back-lit Buttons

Buttons illuminate in the dark

5" REAR VIEW MONITOR

Our 5" TFT LCD Color Monitor comes with a Super Sharp Digital Display and a pixel resolution of 800 x 480. It comes with distance grid lines and a built-in speaker to hear audio from the backup camera. On dash back lit buttons allow for easy menu navigation and an included remote provides an even easier navigation option.

Learn more about other cameras & driver safety products by Rear View Safety on our website.