

120° SIDE CAMERA

RVS-775

*SHOWN WITH RCA CONNECTOR
(5 PIN CONNECTION ALSO AVAILABLE)



SPECIFICATIONS

CAMERA	1/4" SHARP® COLOR CCD
PICTURE ELEMENTS	250,000 PIXELS
GAMMA CORRECTION	R=0.45 TO 1.0
IMAGE SENSOR	420TV LINES
LENS	2.1MM
VIEW ANGLE	120°
SYNC SYSTEM	INTERNAL SYNCHRONIZATION
INFRA-RED DISTANCE	30 FEET (9 INFRARED IR)
USABLE ILLUMINATION	0 LUX (IR ON)
POWER SOURCE	DC 12V
S/N RATIO	MORE THAN 48DB
ELECTRONIC IRIS	1/50, 1/60-1/100,000SEC
VIDEO OUTPUT	1VP.P 75 Ω
IR SWITCH CONTROL	CDS AUTOMATIC CONTROL
VIBRATION RATING	20G
OPERATING TEMPERATURE	-40°C ~ +80°C / RH 95% MAX
STORAGE TEMPERATURE	-40°C ~ +60°C / RH 95% MAX
NET WEIGHT	14 OZ

REAR VIEW
SAFETY
REVERSE WITH CONFIDENCE™

**Heavy Duty
Zinc Metal**



**120 Degree
Viewing Angle**



Auto Iris Sensor
Infra-reds adjust strength
based on outside light



9 Infrareds
35ft visible at night



IP68 Rating

Protected against complete,
continuous submersion in water



Weighs 400 Grams

Just under a pound



**Removable Mounting
Bracket**

Can be mounted with bracket or
flush against vehicle



SIDE CAMERA

The Side Cameras that come with our systems are made from heavy duty zinc metal and come with a 2.1 mm Sharp® CCD lens. Their viewing angle is 120° and with 9 Infrared Lights will allow you to see more than 30ft in total darkness. Its mounting bracket is removable allowing the camera to be mounted flush on the vehicle if so desired. Our side cameras are completely weatherproof with an IP68 rating, shock resistant with a 20G Vibration Rating and come with aircraft grade cable connections.

Learn more about other cameras & driver safety products by Rear View Safety on our website.