

120° HEATED CAMERA WITH 30 INFRA-RED ILLUMINATORS

RVS-812N



SPECIFICATIONS

IMAGE DEVICE	1/3" SONY® SUPER HAD CCD
TV SYSTEM	PAL / NTSC
TOTAL NUMBER OF PIXELS	PAL: 537 (H) × 597 (V) / NTSC: 537 (H) × 505 (V)
EFFECTIVE PIXELS	PAL: 500 (H) × 582 (V) / NTSC: 510 (H) × 492 (V)
SENSING AREA	4.9 MM (H) × 3.7 MM (V)
SYNC. SYSTEM	INTERNAL
RESOLUTION	700 TV LINES
MINIMUM ILLUMINATION	0 LUX (WITH IR)
MICROPHONE	YES
VIDEO OUTPUT	COMPOSITE SIGNAL (1.0 VP-P, 75 Ω)
GAMMA CORRECTION	0.45
AGC	ON
S/N RATIO	BETTER THAN 48 DB
WHITE BALANCE	AUTO
ELECTRONIC SHUTTER	1/50-1/100,000 SEC. / 1/60-1/100,000 SEC.
BLC	AUTO
CURRENT CONSUMPTION	MAX. 300 MA
POWER SUPPLY	DC 12 V
ANTI-VIBRATION	10 G
OPERATING TEMPERATURE	-45°C~70°C, RH 95% MAX.
STORAGE TEMPERATURE	-45°C~80°C, RH 95% MAX.
LENS	3.6 MM OPTIONAL
LENS ANGLE	120°

REAR VIEW
SAFETY
 REVERSE WITH CONFIDENCE™



HEATED CAMERA

Our Heated CCD Camera is made for those real intense moments. With an IP69K rating and heated lens, this camera is made to withstand almost anything mother nature throws against us. It has a viewing angle of 120° and boasts 30 Infra-red Illuminators giving you an ideal image at all times. Adding to its durability is its 100G Impact Rating and Aircraft Grade Cable Connections.

Learn more about other cameras & driver safety products by Rear View Safety on our website.