Rearward	In stallation I		s Part Numbers:
	Installation I		5
	Lexus		24923
	ascia Lexus	IS 350	60358
F			77310
	(Sold separately)		Do Not Exceed Lower of Towing Vehicle
	Drawbar Kit: 3594		Manufacturer's Rating or
	\mathbf{X}	Drawbar must be used in the	2000 LB (908 Kg) Max Gross Trailer Weight
	<u>RISE</u> position only.		200 LB (90.8 Kg) Max Tongue Weight
Hitch Shown In Proper Position			Wiring Access Location: PC 3, 4
Equipment Required: Metal snips			
Fastener Kit: 24923F			Figure 2
Wrenches: 17mm, 19mm			
Drill Bits: None			
	Existing weldnuts on		3"
\sim	top side of vehicle		
	frame		
The			
Frame rail			
	<		Optional Heat Shield
NAK	Trent	L HI	Trimming
8. 100	ACT		
An	Sel -	J China	Exhaust hanger
Figure 1			bracket
		2^{10}	
Note: Fasteners typical both side	es.	Ŭ2	
D Qty. (6) Bolt M12 X 1.25 X 40 CL1	.9 ②	Qty. (6) Conic	cal washer 1/2"

- 1. Lower exhaust by removing four rubber isolators (two per side).
- 2. Remove six M12 bolts (three per side). Lay two exhaust brackets to the side. Return fasteners to owner.
- 3. Raise hitch into place over heat shield, or trim heat shield as shown in figure 2 on both sides of vehicle. Sandwich hitch between vehicle frame and exhaust hanger brackets. Install provided fasteners as shown.
- 4. Torque all hardware to specification below.
- 5. Raise exhaust back into position and reattach to rubber isolator.

Tighten all M12 CL10.9 fasteners with torque wrench to 75 Lb.-Ft. (102 N*M)

Note: check hitch frequently, making sure all fasteners and ball are properly tightened. If hitch is removed, plug all holes in trunk pan or other body panels to prevent entry of water and exhaust fumes. A hitch or ball which has been damaged should be removed and replaced. Observe safety precautions when working beneath a vehicle and wear eye protection. Do not cut access or attachment holes with a torch.

This product complies with safety specifications and requirements for connecting devices and towing systems of the state of New York, V.E.S.C. Regulation V-5 and SAE J684.

Reese Towpower products are your right choice if you need quality and reliability.