



## **10 GAUGE "H" SERIES SINGLE DOOR UNDERBODY BOX SPECIFICATIONS** **BLACK POWDER FINISH**

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 10 gauge cold rolled steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a super durable black polyester powder coat.
- Door is horizontally hinged and constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Door is attached to the hull of the box with stainless steel pillow block type hinges with self-lubricating bushings and 5/16" stainless steel hinge pins.
- Hinges are welded to the box.
- Door is held in the open position with heavy-duty machine chains.
- Chains are easily detachable to drop door down to 180°.
- A three point, stainless steel "T" handle is recessed into the door of the box.
- Top panel of the box forms a drip rail over the door.
- Two keys are furnished per box.
- Ribbed D-Bulb seal is installed in a recessed channel that runs the full perimeter of the door opening.
- Door has a formed knife edge on all 4 sides that contacts the seal when the door is closed.



## **12 GAUGE "H" SERIES SINGLE DOOR UNDERBODY BOX SPECIFICATIONS** **BLACK POWDER FINISH**

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 12 gauge cold rolled steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a super durable black polyester powder coat.
- Door is horizontally hinged and constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Door is attached to the hull of the box with stainless steel pillow block type hinges with self-lubricating bushings and 5/16" stainless steel hinge pins.
- Hinges are welded to the box.
- Door is held in the open position with heavy-duty machine chains.
- Chains are easily detachable to drop door down to 180°.
- Top panel of the box forms a drip rail over the door.
- A full size, stainless steel paddle latch is recessed into the door of the box.
- Door can be closed with the latch in the locked position.
- Two keys are furnished per box.
- Ribbed D-Bulb seal is installed in a recessed channel that runs the full perimeter of the door opening.
- Door has a formed knife edge on all 4 sides that contacts the seal when the door is closed.



## **14 GAUGE "V" SERIES SINGLE DOOR BOX SPECIFICATIONS** **BLACK POWDER FINISH**

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a black super durable polyester powder coat.
- Door is vertically hinged and constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Door is left hand hinged as standard.
- Welds are full arc welds, no spot welds.
- Door is attached to the hull of the box with stainless steel pillow block type hinges with self-lubricating bushings and 5/16" stainless steel hinge pins.
- Hinges are welded to the box.
- Door has a heavy-duty machine chain stops
- Chain is easily detachable to allow door to swing around to 180°.
- Top panel of the box forms a drip rail over the door.
- A full size, stainless steel paddle latch is recessed into the door of the box.
- Two keys are furnished per box.
- Door can be closed with the latch in the locked position.
- Ribbed D-Bulb seal is installed in a recessed channel that runs the full perimeter of the door opening.
- Door has a formed knife edge on all 4 sides that contacts the seal when the door is closed.



## **14 GAUGE "H" SERIES SINGLE DOOR UNDERBODY BOX SPECIFICATIONS** **BLACK POWDER FINISH**

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a black super durable polyester powder coat.
- Doors are horizontally hinged and constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Door is attached to the hull of the box with stainless steel pillow block type hinges with self-lubricating bushings and 5/16" stainless steel hinge pins.
- Hinges are welded to the box.
- Door is held in the open position with heavy-duty machine chains.
- Chains are easily detachable to drop door down to 180°.
- Top panel of the box forms a drip rail over the door.
- A full size, stainless steel paddle latch is recessed into the door.
- Two keys are furnished per box.
- Doors can be closed with the latch in the locked position.
- Ribbed D-Bulb seal is installed in a recessed channel that runs the full perimeter of the door opening.
- Door has a formed knife edge on all 4 sides that contacts the seal when the door is closed.



## **14 GAUGE "H-2" SERIES TWO DOOR UNDERBODY BOX SPECIFICATIONS** **BLACK POWDER FINISH**

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a black super durable polyester powder coat.
- Doors are horizontally hinged and constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Doors are attached to the hull of the box with stainless steel pillow block type hinges with self-lubricating bushings and 5/16" stainless steel hinge pins.
- Hinges are welded to the box.
- Doors are held in the open position with heavy-duty machine chain.
- Chains are easily detachable to drop door down to 180°.
- Top panel of the box forms a drip rail over the door.
- A full size, stainless steel paddle latch is recessed into each door.
- Two keys are furnished per box.
- Doors can be closed with the latch in the locked position.
- Ribbed D-Bulb seal is installed in a recessed channel that runs the full perimeter of the door opening.
- Door has a formed knife edge on all 4 sides that contacts the seal when the door is closed.



## **14 GAUGE "V-2" SERIES TWO DOOR BOX SPECIFICATIONS** **BLACK POWDER FINISH**

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a black super durable polyester powder coat.
- Doors are vertically hinged and constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Both doors to be left hand hinged as standard.
- Welds are full arc welds, no spot welds.
- Doors are attached to the hull of the box with stainless steel pillow block type hinges with self-lubricating bushings and 5/16" stainless steel hinge pins.
- Hinges are welded to the box.
- Doors have heavy-duty machine chain stops.
- Chains are easily detachable to allow doors to swing around to 180°.
- Top panel of the box forms a drip rail over the door.
- A full size, stainless steel paddle latch is recessed into each door.
- Two keys are furnished per box.
- Doors can be closed with the latch in the locked position.
- Ribbed D-Bulb seal is installed in a recessed channel that runs the full perimeter of the door opening.
- Doors have a formed knife edge on all 4 sides that contacts the seal when the doors are closed.



## **14 GAUGE "V-20" SERIES DOUBLE OVERLAPPING DOOR BOX SPECIFICATIONS** **BLACK POWDER FINISH**

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a black super durable polyester powder coat.
- Doors are vertically hinged and constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Leading door to be left hand hinged as standard.
- Welds are full arc welds, no spot welds.
- Doors are attached to the hull of the box with stainless steel pillow block type hinges with self-lubricating bushings and 5/16" stainless steel hinge pins.
- Hinges are welded to the box.
- Doors have heavy-duty machine chain stops.
- Chains are easily detachable to allow doors to swing around to 180°.
- Top panel of the box forms a drip rail over the door.
- A full size, stainless steel paddle latch is recessed into the leading door.
- Trailing door has a two point latch with inside release.
- Two keys are furnished per box.
- Leading door can be closed with the latch in the locked position.
- Ribbed D-Bulb seal is installed in a recessed channel that runs the full perimeter of the door opening.
- Doors have a formed knife edge on all 4 sides that contacts the seal when the door are closed.



## **43S SINGLE LID SIDE BOX SPECIFICATIONS** **WHITE POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

43-3/4" overall length, 13-3/16" wide at the top, 8" wide at the bottom and an overall depth of 13-3/16".

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a white super durable polyester powder coat.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Full length small parts storage in the front of the box.
- A full size, stainless steel paddle latch is recessed into the hull of the box.
- Two keys are furnished per box.
- A spring type lid prop assists in the opening and closing of the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail, mounting instructions included.
- Weight: 75 lbs.





## **43SA SINGLE LID ALUMINUM SIDE BOX SPECIFICATIONS** **BRIGHT DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

44" overall length, 13-3/16" wide at the top, 8" wide at the bottom and an overall depth of 13-11/16".

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 bright diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and welded in with full arc welds.
- Lid is constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with three 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Full length small parts storage tray is in the front of the box.
- A full size, stainless steel paddle latch is recessed into the hull of the box.
- Two keys are furnished per box.
- Lid is equipped with a gas shock for one-hand opening of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail, mounting instructions included.
- Weight: 42 lbs.



## **43SAB SINGLE LID ALUMINUM SIDE BOX SPECIFICATIONS** **BLACK DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

44" overall length, 13-3/16" wide at top, 8" wide at the bottom and an overall depth of 13-11/16".

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and welded in with full arc welds.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with three 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Full length small parts storage tray is in the front of the box.
- A full size, stainless steel paddle latch is recessed into the hull of the box.
- Two keys are furnished per box.
- Lid is equipped with a gas pressure shock for one-hand opening of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Black boxes go through a five-stage zinc phosphate wash and are finished with a black super durable polyester powder coat.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 44 lbs.



## **43SAW SINGLE LID ALUMINUM SIDE BOX SPECIFICATIONS** **WHITE DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

44" overall length, 13-3/16" wide at the top, 8" wide at the bottom and an overall depth of 13-11/16".

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and welded in with full arc welds.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with three 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Full length small parts storage tray is in the front of the box.
- A full size, stainless steel paddle latch is recessed into the hull of the box.
- Two keys are furnished per box.
- Lid is equipped with a gas pressure shock for one-hand opening of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- White boxes go through a five-stage zinc phosphate wash and are finished with a white super durable polyester powder coat.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 44 lbs.



## **43SB SINGLE LID SIDE BOX SPECIFICATIONS** **BLACK POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

43-3/4" overall length, 13-3/16" wide at the top, 8" wide at the bottom and an overall depth of 13-3/16".

### **To include the following features:**

- 14 gauge cold rolled steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a black super durable polyester powder coat.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Full length small parts storage in the front of the box.
- Full size, stainless steel paddle latch is recessed into the hull of the box.
- Two keys are furnished per box.
- A spring type lid prop assist in the opening and closing of the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 75 lbs.



## **43SLP SINGLE LID LOW PROFILE SIDE BOX SPECIFICATIONS** **WHITE POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

43-3/4" overall length, 13-3/16" wide at the top, 8" wide at the bottom and an overall depth of 13-3/16".  
8-3/4" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a white super durable polyester powder coat.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- A spring type lid prop assists in the opening and closing of the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail, mounting instructions included.
- Weight: 75 lbs.



## **43SLPA SINGLE LID ALUMINUM LOW PROFILE SIDE BOX SPECIFICATIONS** **BRIGHT DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

44" overall length, 13-11/16" wide at the top, 8" wide at the bottom and an overall depth of 13-3/16".  
8-3/4" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 bright diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and welded in with full arc welds.
- Lid is constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with three 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with a gas shock for one-hand opening of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail, mounting instructions included.
- Weight: 44 lbs.



## **43SLPAB SINGLE LID ALUMINUM LOW PROFILE SIDE BOX SPECIFICATIONS** **BLACK DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

44" overall length, 13-3/16" wide at the top, 8" wide at the bottom and an overall depth of 13-11/16".  
8-3/4" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and welded in with full arc welds.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with three 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with a gas pressure shock for one-hand opening of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Black boxes go through a five-stage zinc phosphate wash and are finished with a black super durable polyester powder coat.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 46 lbs.



## **43SLPAW SINGLE LID ALUMINUM LOW PROFILE SIDE BOX SPECIFICATIONS** **WHITE DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

44" overall length, 13-3/16" wide at top, 8" wide at the bottom and an overall depth of 13-11/16".  
8-3/4" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and welded in with full arc welds.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with three 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with a gas pressure shock for one-hand opening of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- White boxes go through a five-stage zinc phosphate wash and are finished with a white super durable polyester powder coat.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 46 lbs.





## **43SLPB SINGLE LID LOW PROFILE SIDE BOX SPECIFICATIONS** **BLACK POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

43-3/4" overall length, 13-3/16" wide at the top, 8" wide at the bottom and an overall depth of 13-3/16".  
8-3/4" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a black super durable polyester powder coat.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- A spring type lid prop assists in the opening and closing of the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 75 lbs.



## **43SLPW SINGLE LID LOW PROFILE WIDE SIDE BOX SPECIFICATIONS** **WHITE POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

43-3/4" overall length, 18-3/16" wide at the top, 13" wide at the bottom and an overall depth of 13-3/16".  
8-3/4" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a white super durable polyester powder coat.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Full length small parts storage in the front of the box.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail, mounting instructions included.
- Weight: 99 lbs.



## **43SLPWA SINGLE LID ALUMINUM LOW PROFILE WIDE SIDE BOX SPECIFICATIONS** **BRIGHT DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

44" overall length, 18-11/16" wide at the top, 13" wide at the bottom and an overall depth of 13-3/16".  
8-3/4" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 bright diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and welded in with full arc welds.
- Lid is constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with three 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Small parts storage in the front of the box.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with two gas shocks for one-hand opening of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail, mounting instructions included.
- Weight: 48 lbs.



## **43SLPWAB SINGLE LID ALUMINUM WIDE LOW PROFILE SIDE BOX SPECIFICATIONS** **BLACK DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

44" overall length, 18-11/16" wide at the top, 13" wide at the bottom and an overall depth of 13-3/16".  
8-3/4" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and welded in with full arc welds.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with three 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Small parts storage in the front of the box.
- Two keys are furnished per box.
- Lid is equipped with a gas pressure shock for one-hand opening of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Black boxes go through a five-stage zinc phosphate wash and are finished with a black super durable polyester powder coat.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 50 lbs.



## **43SLPWA SINGLE LID ALUMINUM WIDE LOW PROFILE SIDE BOX SPECIFICATIONS** **WHITE DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

44" overall length, 18-3/16" wide at the top, 13" wide at the bottom and an overall depth of 13-3/16".  
8-3/4" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and welded in with full arc welds.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with three 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Small parts storage in the front of the box.
- Two keys are furnished per box.
- Lid is equipped with a gas pressure shock for one-hand opening of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- White boxes go through a five-stage zinc phosphate wash and are finished with a white super durable polyester powder coat.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 50 lbs.



## **43SLPWB SINGLE LID LOW PROFILE WIDE SIDE BOX SPECIFICATIONS** **BLACK POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

43-3/4" overall length, 18-11/16" wide at the top, 13" wide at the bottom and an overall depth of 13-3/16".  
8-3/4" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a black super durable polyester powder coat.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Full length small parts storage in the front of the box.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- A spring type lid prop assists in the opening and closing of the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 99 lbs.



## **43SW SINGLE LID WIDE SIDE BOX SPECIFICATIONS** **WHITE POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

43-3/4" overall length, 18-3/16" wide at the top, 13" wide at the bottom and an overall depth of 13-3/16".

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a white super durable polyester powder coat.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Full length small parts storage in the front of the box.
- A full size, stainless steel paddle latch is recessed into the hull of the box.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail, mounting instructions included.
- Weight: 93 lbs.



## **43SWB SINGLE LID WIDE SIDE BOX SPECIFICATIONS** **BLACK POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

43-3/4" overall length, 18-3/16" wide at the top, 13" wide at the bottom and an overall depth of 13-3/16".

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a black super durable polyester powder coat.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Full length small parts storage in the front of the box.
- A full size, stainless steel paddle latch is recessed into the hull of the box.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 93 lbs.





## **48SLP SINGLE LID LOW PROFILE SIDE BOX SPECIFICATIONS** **WHITE POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

49" overall length, 13-3/16" wide at the top, 8" wide at the bottom and an overall depth of 13-3/16".  
8-3/4" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a white super durable polyester powder coat.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- A spring type lid prop assists in the opening and closing of the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 83 lbs.



## **48SLPA SINGLE LID ALUMINUM LOW PROFILE SIDE BOX SPECIFICATIONS** **BRIGHT DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

49" overall length, 13-3/16" wide at the top, 8" wide at the bottom and an overall depth of 13-11/16".  
8-3/4" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 bright diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and welded in with full arc welds.
- Lid is constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with three 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with a gas pressure shock for one-hand opening of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 49 lbs.



## **48SLPAB SINGLE LID ALUMINUM LOW PROFILE SIDE BOX SPECIFICATIONS** **BLACK DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

49" overall length, 13-11/16" wide at the top, 8" wide at the bottom and an overall depth of 13-3/16".  
8-3/4" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and welded in with full arc welds.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with three 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with a gas pressure shock for one-hand opening of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Black boxes go through a five-stage zinc phosphate wash and are finished with a black super durable polyester powder coat.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 51 lbs.



## **48SLPAW SINGLE LID ALUMINUM LOW PROFILE SIDE BOX SPECIFICATIONS** **WHITE DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

49" overall length, 13-11/16" wide at the top, 8" wide at the bottom and an overall depth of 13-3/16".  
8-3/4" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and welded in with full arc welds.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with three 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with a gas pressure shock for one-hand opening of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- White boxes go through a five-stage zinc phosphate wash and are finished with a white super durable polyester powder coat.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 51 lbs.



## **48SLPB SINGLE LID LOW PROFILE SIDE BOX SPECIFICATIONS** **BLACK POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

48-3/4" overall length, 13-3/16" wide at the top, 8" wide at the bottom and an overall depth of 13-3/16".  
8-3/4" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a black super durable polyester powder coat.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- A spring type lid prop assists in the opening and closing of the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 83 lbs.



## **48SLPW SINGLE LID LOW PROFILE WIDE SIDE BOX SPECIFICATIONS** **WHITE POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

48-3/4" overall length, 18-3/16" wide at the top, 13" wide at the bottom and an overall depth of 13-3/16".  
8-3/4" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a white super durable polyester powder coat.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Small parts storage in the front of the box.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- A spring type lid prop assists in the opening and closing of the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 109 lbs.



## **48SLPWA SINGLE LID ALUMINUM LOW PROFILE WIDE SIDE BOX SPECIFICATIONS** **BRIGHT DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

49" overall length, 18-11/16" wide at the top, 13" wide at the bottom and an overall depth of 13-3/16".  
8-3/4" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 bright diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and welded in with full arc welds.
- Lid is constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with three 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Small parts storage in the front of the box.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with a gas pressure shock for one-hand opening of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 54 lbs.



## **48SLPWAB SINGLE LID ALUMINUM WIDE LOW PROFILE SIDE BOX SPECIFICATIONS** **BLACK DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

49" overall length, 18-11/16" wide at the top, 13" wide at the bottom and an overall depth of 13-3/16".  
8-3/4" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and welded in with full arc welds.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with three 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Small parts storage in the front of the box.
- Two keys are furnished per box.
- Lid is equipped with a gas pressure shock for one-hand opening of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Black boxes go through a five-stage zinc phosphate wash and are finished with a black super durable polyester powder coat.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 56 lbs.





## **48SLPWAU SINGLE LID ALUMINUM WIDE LOW PROFILE SIDE BOX SPECIFICATIONS** **WHITE DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

49" overall length, 18-11/16" wide at the top, 13" wide at the bottom and an overall depth of 13-3/16".  
8-3/4" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and welded in with full arc welds.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with three 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Small parts storage in the front of the box.
- Two keys are furnished per box.
- Lid is equipped with a gas pressure shock for one-hand opening of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- White boxes go through a five-stage zinc phosphate wash and are finished with a white super durable polyester powder coat.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 56 lbs.



## **48SLPWB SINGLE LID LOW PROFILE WIDE SIDE BOX SPECIFICATIONS** **BLACK POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

48-3/4" overall length, 18-3/16" wide at the top, 13" wide at the bottom and an overall depth of 13-3/16".  
8-3/4" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a black super durable polyester powder coat.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Small parts storage in the front of the box.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- A spring type lid prop assists in the opening and closing of the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 109 lbs.



## **50S SINGLE LID SIDE BOX SPECIFICATIONS** **WHITE POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

50-3/4" overall length, 13-3/16" wide at the top, 8" wide at the bottom and an overall depth of 13-3/16".

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a white super durable polyester powder coat.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Full length small parts storage in the front of the box.
- Full size, stainless steel paddle latch is recessed into the hull of the box.
- Two keys are furnished per box.
- A spring type lid prop assist in the opening and closing of the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 83 lbs.



## **50SA SINGLE LID ALUMINUM SIDE BOX SPECIFICATIONS** **BRIGHT DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

51" overall length, 13-11/16" wide at the top, 8" wide at bottom and an overall depth of 13-3/16".

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and welded in with full arc welds.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with three 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Full length small parts storage tray is in the front of the box.
- A full size, stainless steel paddle latch is recessed into the hull of the box.
- Two keys are furnished per box.
- Lid is equipped with a gas pressure shock for one-hand opening of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Black boxes go through a five-stage zinc phosphate wash and are finished with a black super durable polyester powder coat.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 47 lbs.



## **50SAB SINGLE LID ALUMINUM SIDE BOX SPECIFICATIONS** **BLACK DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

51" overall length, 13-11/16" wide at the top, 8" wide at bottom and an overall depth of 13-3/16".

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and welded in with full arc welds.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with three 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Full length small parts storage tray is in the front of the box.
- A full size, stainless steel paddle latch is recessed into the hull of the box.
- Two keys are furnished per box.
- Lid is equipped with a gas pressure shock for one-hand opening of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Black boxes go through a five-stage zinc phosphate wash and are finished with a black super durable polyester powder coat.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 47 lbs.



## **50SAW SINGLE LID ALUMINUM SIDE BOX SPECIFICATIONS** **WHITE DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

51" overall length, 13-11/16" wide at the top, 8" wide at bottom and an overall depth of 13-3/16".

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and welded in with full arc welds.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with three 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Full length small parts storage tray is in the front of the box.
- A full size, stainless steel paddle latch is recessed into the hull of the box.
- Two keys are furnished per box.
- Lid is equipped with a gas pressure shock for one-hand opening of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- White boxes go through a five-stage zinc phosphate wash and are finished with a white super durable polyester powder coat.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 47 lbs.



## **50SB SINGLE LID SIDE BOX SPECIFICATIONS** **BLACK POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

50-3/4" overall length, 13-3/16" wide at the top, 8" wide at the bottom and an overall depth of 13-3/16".

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a black super durable polyester powder coat.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Full length small parts storage in the front of the box.
- A full size, stainless steel paddle latch is recessed into the hull of the box.
- Two keys are furnished per box.
- A spring type lid prop assist in the opening and closing of the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around box opening.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 83 lbs.



## **50STS SINGLE LID "SLANT TOP" SIDE BOX SPECIFICATIONS** **WHITE POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

50-3/4" overall length, 13-3/16" wide at the top, 8" wide at the bottom and an overall depth of 13-1/8".

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a white super durable polyester powder coat.
- Lid constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Sliding tray 19-1/2" x 8-7/8" x 2-7/8", with white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Full length small parts storage in the front of the box.
- Full size, stainless steel paddle latch is recessed into the lid.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail, mounting instructions included.
- Weight: 86 lbs.





## **50STSB SINGLE LID "SLANT TOP" SIDE BOX SPECIFICATIONS** **BLACK POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

50-3/4" overall length, 13-3/16" wide at the top, 8" wide at the bottom and an overall depth of 13-1/8".

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a white super durable polyester powder coat.
- Lid constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Sliding tray 19-1/2" x 8-7/8", with white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Full length small parts storage in the front of the box.
- Full size, stainless steel paddle latch is recessed into the lid.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Attaching hardware is stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 86 lbs.



## **50SW SINGLE LID WIDE SIDE BOX SPECIFICATIONS** **WHITE POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

50-3/4" overall length, 18-3/16" wide at the top, 13" wide at the bottom and an overall depth of 13-3/16".

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a white super durable polyester powder coat.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Full length small parts storage in the front of the box.
- A full size, stainless steel paddle latch is recessed into the hull of the box.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 102 lbs.



## **50SWB SINGLE LID WIDE SIDE BOX SPECIFICATIONS** **BLACK POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

50-3/4" overall length, 18-3/16" wide at the top, 13" wide at the bottom and an overall depth of 13-3/16".

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a black super durable polyester powder coat.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Full length small parts storage in the front of the box.
- A full size, stainless steel paddle latch is recessed into the hull of the box.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 102 lbs.



## **61S SINGLE LID SIDE BOX SPECIFICATIONS** **WHITE POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

61-3/4" overall length, 13-3/16" wide at the top, 8" wide at the bottom and has an overall depth of 13-3/16".

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a white super durable polyester powder coat.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Full length small parts storage in the front of the box.
- A full size, stainless steel paddle latch is recessed into the hull of the box.
- Two keys are furnished per box.
- A spring type lid prop assist in the opening and closing of the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 99 lbs.



## **61SA SINGLE LID ALUMINUM SIDE BOX SPECIFICATIONS** **BRIGHT DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

62" overall length, 13-11/16" wide at the top, 8" wide at the bottom and an overall depth of 13-3/16".

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 bright diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and welded in with full arc welds.
- Lid is constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with three 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Full length small parts storage tray is in the front of the box.
- A full size, stainless steel paddle latch is recessed into the hull of the box.
- Two keys are furnished per box.
- Lid is equipped with a gas pressure shock for one-hand opening of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 53 lbs.



## **61SAB SINGLE LID ALUMINUM SIDE BOX SPECIFICATIONS** **BLACK DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

62" overall length, 13-11/16" wide at the top, 8" wide at the bottom and an overall depth of 13-3/16".

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and welded in with full arc welds.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with three 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Full length small parts storage tray is in the front of the box.
- A full size, stainless steel paddle latch is recessed into the hull of the box.
- Two keys are furnished per box.
- Lid is equipped with a gas pressure shock for one-hand opening of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Black boxes go through a five-stage zinc phosphate wash and are finished with a black super durable polyester powder coat.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 55 lbs.



## **61SAW SINGLE LID ALUMINUM SIDE BOX SPECIFICATIONS** **WHITE DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

62" overall length, 13-11/16" wide at the top, 8" wide at the bottom and an overall depth of 13-3/16".

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and welded in with full arc welds.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with three 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Full length small parts storage tray is in the front of the box.
- A full size, stainless steel paddle latch is recessed into the hull of the box.
- Two keys are furnished per box.
- Lid is equipped with a gas pressure shock for one-hand opening of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- White boxes go through a five-stage zinc phosphate wash and are finished with a white super durable polyester powder coat.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 55 lbs.



## **61SB SINGLE LID SIDE BOX SPECIFICATIONS** **BLACK POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

61-3/4" overall length, 13-3/16" wide at the top, 8" wide at the bottom and an overall depth of 13-3/16".

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a black super durable polyester powder coat.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Full length small parts storage in the front of the box.
- Full size, stainless steel paddle latch is recessed into the hull of the box.
- Two keys are furnished per box.
- A spring type lid prop assist in the opening and closing of the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 99 lbs.





## **61SLP SINGLE LID LOW PROFILE SIDE BOX SPECIFICATIONS** **WHITE POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

61-3/4" overall length, 13-3/16" wide at the top, 8" wide at the bottom and an overall depth of 13-3/16".  
8-3/4" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a white super durable polyester powder coat.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- A spring type lid prop assists in the opening and closing of the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 98 lbs.



## **61SLPA SINGLE LID ALUMINUM LOW PROFILE SIDE BOX SPECIFICATIONS** **BRIGHT DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

62" overall length, 13-11/16" wide at the top, 8" wide at the bottom and an overall depth of 13-3/16".  
8-3/4" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 bright diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and welded in with full arc welds.
- Lid is constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with three 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with a gas pressure shock for one-hand opening of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 58 lbs.



## **61SLPAB SINGLE LID ALUMINUM LOW PROFILE SIDE BOX SPECIFICATIONS** **BLACK DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

62" overall length, 13-11/16" wide at the top, 8" wide at the bottom and an overall depth of 13-3/16".  
8-3/4" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and welded in with full arc welds.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with three 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with a gas pressure shock for one-hand opening of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Black boxes go through a five-stage zinc phosphate wash and are finished with a black super durable polyester powder coat.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 60 lbs.



## **61SLPAW SINGLE LID ALUMINUM LOW PROFILE SIDE BOX SPECIFICATIONS** **WHITE DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

62" overall length, 13-11/16" wide at the top, 8" wide at the bottom and an overall depth of 13-3/16".  
8-3/4" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and welded in with full arc welds.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with three 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with a gas pressure shock for one-hand opening of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- White boxes go through a five-stage zinc phosphate wash and are finished with a white super durable polyester powder coat.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 60 lbs.



## **61SLPB SINGLE LID LOW PROFILE SIDE BOX SPECIFICATIONS** **BLACK POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

61-3/4" overall length, 13-3/16" wide at the top, 8" wide at the bottom and an overall depth of 13-3/16".  
8-3/4" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a black super durable polyester powder coat.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- A spring type lid prop assists in the opening and closing of the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 98 lbs.



## **61SLPW SINGLE LID LOW PROFILE WIDE SIDE BOX SPECIFICATIONS** **WHITE POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

61-3/4" overall length, 18-3/16" wide at the top, 13" wide at the bottom and an overall depth of 13-3/16".  
8-3/4" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a white super durable polyester powder coat.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Small parts storage in the front of the box.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- A spring type lid prop assists in the opening and closing of the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 129 lbs.



## **61SLPWA SINGLE LID ALUMINUM LOW PROFILE WIDE SIDE BOX SPECIFICATIONS** **BRIGHT DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

62" overall length, 18-11/16" wide at the top, 13" wide at the bottom and an overall depth of 13-3/16".  
8-3/4" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 bright diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and welded in with full arc welds.
- Lid is constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with three 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Small parts storage in the front of the box.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with a gas pressure shock for one-hand opening of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 65 lbs.



## **61SLPWAB SINGLE LID ALUMINUM WIDE LOW PROFILE SIDE BOX SPECIFICATIONS** **BLACK DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

62" overall length, 18-11/16" wide at the top, 13" wide at the bottom and an overall depth of 13-3/16".  
8-3/4" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and welded in with full arc welds.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with three 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Small parts storage in the front of the box.
- Two keys are furnished per box.
- Lid is equipped with a gas pressure shock for one-hand opening of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Black boxes go through a five-stage zinc phosphate wash and are finished with a black super durable polyester powder coat.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 67 lbs.





## **61SLPWAU SINGLE LID ALUMINUM WIDE LOW PROFILE SIDE BOX SPECIFICATIONS** **WHITE DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

62" overall length, 18-11/16" wide at the top, 13" wide at the bottom and an overall depth of 13-3/16".  
8-3/4" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and welded in with full arc welds.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with three 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Small parts storage in the front of the box.
- Two keys are furnished per box.
- Lid is equipped with a gas pressure shock for one-hand opening of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- White boxes go through a five-stage zinc phosphate wash and are finished with a white super durable polyester powder coat.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 67 lbs.



## **61SLPWB SINGLE LID LOW PROFILE WIDE SIDE BOX SPECIFICATIONS** **BLACK POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

61-3/4" overall length, 18-3/16" wide at the top, 13" wide at the bottom and an overall depth of 13-3/16".  
8-3/4" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a black super durable polyester powder coat.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Small parts storage in the front of the box.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- A spring type lid prop assists in the opening and closing of the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 129 lbs.



## **61STS SINGLE LID “SLANT TOP” SIDE BOX SPECIFICATIONS** **WHITE POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

61-3/4" overall length, 13-3/16" wide at the top, 8" wide at the bottom and an overall depth of 13-1/8".

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a white super durable polyester powder coat.
- Lid constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Sliding tray 19-1/2" x 8-7/8", with white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Full length small parts storage in the front of the box.
- Full size, stainless steel paddle latch is recessed into the lid.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Attaching hardware is stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 102 lbs.



## **61STSB SINGLE LID “SLANT TOP” SIDE BOX SPECIFICATIONS** **BLACK POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

61-3/4" overall length, 13-3/16" wide at the top, 8" wide at the bottom and an overall depth of 13-1/8".

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a white super durable polyester powder coat.
- Lid constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Sliding tray 19-1/2" x 8-7/8", with white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Full length small parts storage in the front of the box.
- Full size, stainless steel paddle latch is recessed into the lid.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Attaching hardware is stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 102 lbs.



## **61SWA SINGLE LID ALUMINUM SIDE BOX SPECIFICATIONS** **BRIGHT DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

62" overall length, 18-11/16" wide at the top, 13" wide at the bottom and an overall depth of 13-3/16".  
6-1/8" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 bright diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and welded in with full arc welds.
- Lid is constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with three 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Full length small parts storage tray is in the front of the box.
- A full size, stainless steel paddle latch is recessed into the hull of the box.
- Two keys are furnished per box.
- Lid is equipped with a gas pressure shock for one-hand opening of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 64 lbs.



## **61SWAB SINGLE LID ALUMINUM SIDE BOX SPECIFICATIONS** **BLACK DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

62" overall length, 18-11/16" wide at the top, 13" wide at the bottom and an overall depth of 13-3/16".  
6-1/8" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and welded in with full arc welds.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with three 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Full length small parts storage tray is in the front of the box.
- A full size, stainless steel paddle latch is recessed into the hull of the box.
- Two keys are furnished per box.
- Lid is equipped with a gas pressure shock for one-hand opening of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Black boxes go through a five-stage zinc phosphate wash and are finished with a black super durable polyester powder coat.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 66 lbs.



## **61SWAW SINGLE LID ALUMINUM SIDE BOX SPECIFICATIONS** **WHITE DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

62" overall length, 18-11/16" wide at the top, 13" wide at the bottom and an overall depth of 13-3/16".  
6-1/8" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and welded in with full arc welds.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with three 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Full length small parts storage tray is in the front of the box.
- A full size, stainless steel paddle latch is recessed into the hull of the box.
- Two keys are furnished per box.
- Lid is equipped with a gas pressure shock for one-hand opening of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- White boxes go through a five-stage zinc phosphate wash and are finished with a white super durable polyester powder coat.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 66 lbs.



## **65SLP SINGLE LID LOW PROFILE SIDE BOX SPECIFICATIONS** **WHITE POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

65-3/4" overall length, 13-3/16" wide at the top, 8" wide at the bottom and an overall depth of 13-3/16".  
8-3/4" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a white super durable polyester powder coat.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- A spring type lid prop assists in the opening and closing of the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 102 lbs.





## **65SLPA SINGLE LID ALUMINUM LOW PROFILE SIDE BOX SPECIFICATIONS** **BRIGHT DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

66" overall length, 13-11/16" wide at the top, 8" wide at the bottom and an overall depth of 13-3/16".  
8-3/4" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 bright diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and welded in with full arc welds.
- Lid is constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with three 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with a gas pressure shock for one-hand opening of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 64 lbs.



## **65SLPAB SINGLE LID ALUMINUM LOW PROFILE SIDE BOX SPECIFICATIONS** **BLACK DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

66" overall length, 13-11/16" wide at the top, 8" wide at the bottom and an overall depth of 13-3/16".  
8-3/4" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and welded in with full arc welds.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with three 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with a gas pressure shock for one-hand opening of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Black boxes go through a five-stage zinc phosphate wash and are finished with a black super durable polyester powder coat.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 66 lbs.



## **65SLPAW SINGLE LID ALUMINUM LOW PROFILE SIDE BOX SPECIFICATIONS** **WHITE DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

66" overall length, 13-11/16" wide at the top, 8" wide at the bottom and an overall depth of 13-3/16".  
8-3/4" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and welded in with full arc welds.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with three 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with a gas pressure shock for one-hand opening of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- White boxes go through a five-stage zinc phosphate wash and are finished with a white super durable polyester powder coat.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 66 lbs.



## **65SLPB SINGLE LID LOW PROFILE SIDE BOX SPECIFICATIONS** **BLACK POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

61-3/4" overall length, 13-3/16" wide at the top, 8" wide at the bottom and an overall depth of 13-3/16".  
8-3/4" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a black super durable polyester powder coat.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- A spring type lid prop assists in the opening and closing of the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 102 lbs.



## **65SLPW SINGLE LID LOW PROFILE WIDE SIDE BOX SPECIFICATIONS** **WHITE POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

65-3/4" overall length, 18-3/16" wide at the top, 13" wide at the bottom and an overall depth of 13-3/16".  
8-3/4" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a white super durable polyester powder coat.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Small parts storage in the front of the box.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- A spring type lid prop assists in the opening and closing of the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 134 lbs.



## **65SLPWA SINGLE LID ALUMINUM LOW PROFILE WIDE SIDE BOX SPECIFICATIONS** **BRIGHT DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

66" overall length, 18-11/16" wide at the top, 13" wide at the bottom and an overall depth of 13-3/16".  
8-3/4" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 bright diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and welded in with full arc welds.
- Lid is constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with three 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Small parts storage in the front of the box.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with a gas pressure shock for one-hand opening of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 70 lbs.



## **65SLPWAB SINGLE LID ALUMINUM WIDE LOW PROFILE SIDE BOX SPECIFICATIONS** **BLACK DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

66" overall length, 18-11/16" wide at the top, 13" wide at the bottom and an overall depth of 13-3/16".  
8-3/4" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and welded in with full arc welds.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with three 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Small parts storage in the front of the box.
- Two keys are furnished per box.
- Lid is equipped with a gas pressure shock for one-hand opening of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Black boxes go through a five-stage zinc phosphate wash and are finished with a black super durable polyester powder coat.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 72 lbs.



## **65SLPWAU SINGLE LID ALUMINUM WIDE LOW PROFILE SIDE BOX SPECIFICATIONS** **WHITE DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

66" overall length, 18-11/16" wide at the top, 13" wide at the bottom and an overall depth of 13-3/16".  
8-3/4" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and welded in with full arc welds.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with three 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Small parts storage in the front of the box.
- Two keys are furnished per box.
- Lid is equipped with a gas pressure shock for one-hand opening of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- White boxes go through a five-stage zinc phosphate wash and are finished with a white super durable polyester powder coat.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 72 lbs.





## **65SLPWB SINGLE LID LOW PROFILE WIDE SIDE BOX SPECIFICATIONS** **BLACK POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

65-3/4" overall length, 18-3/16" wide at the top, 13" wide at the bottom and an overall depth of 13-3/16".  
8-3/4" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a black super durable polyester powder coat.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Small parts storage in the front of the box.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- A spring type lid prop assists in the opening and closing of the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 134 lbs.



## **67S SINGLE LID SIDE BOX SPECIFICATIONS** **WHITE POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

67-3/4" overall length, 13-3/16" wide at the top, 8" wide at the bottom and an overall depth of 13-3/16".

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a white super durable polyester powder coat.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Full length small parts storage in the front of the box.
- Full size, stainless steel paddle latch is recessed into the hull of the box.
- Two keys are furnished per box.
- A spring type lid prop assist in the opening and closing of the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 107 lbs.



## **67SA SINGLE LID ALUMINUM SIDE BOX SPECIFICATIONS** **BRIGHT DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

68" overall length, 13-11/16" wide at the top, 8" wide at the bottom and an overall depth of 13-3/16".

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 bright diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and welded in with full arc welds.
- Lid is constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with three 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Full length small parts storage tray is in the front of the box.
- A full size, stainless steel paddle latch is recessed into the hull of the box.
- Two keys are furnished per box.
- Lid is equipped with a gas pressure shock for one-hand opening of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 57 lbs.



## **67SAB SINGLE LID ALUMINUM SIDE BOX SPECIFICATIONS** **BLACK DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

68" overall length, 13-11/16" wide at the top, 8" wide at the bottom and an overall depth of 13-3/16".

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and welded in with full arc welds.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with three 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Full length small parts storage tray is in the front of the box.
- A full size, stainless steel paddle latch is recessed into the hull of the box.
- Two keys are furnished per box.
- Lid is equipped with a gas pressure shock for one-hand opening of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Black boxes go through a five-stage zinc phosphate wash and are finished with a black super durable polyester powder coat.
- Weight: 59 lbs.



## **67SAW SINGLE LID ALUMINUM SIDE BOX SPECIFICATIONS** **WHITE DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

68" overall length, 13-11/16" wide at the top, 8" wide at the bottom and an overall depth of 13-3/16".

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and welded in with full arc welds.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with three 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Full length small parts storage tray is in the front of the box.
- A full size, stainless steel paddle latch is recessed into the hull of the box.
- Two keys are furnished per box.
- Lid is equipped with a gas pressure shock for one-hand opening of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- White boxes go through a five-stage zinc phosphate wash and are finished with a white super durable polyester powder coat.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 59 lbs.



## **67SB SINGLE LID SIDE BOX SPECIFICATIONS** **BLACK POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

67-3/4" overall length, 13-3/16" wide at the top, 8" wide at the bottom and an overall depth of 13-3/16".

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a black super durable polyester powder coat.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Full length small parts storage in the front of the box.
- Full size, stainless steel paddle latch is recessed into the hull of the box.
- Two keys are furnished per box.
- A spring type lid prop assist in the opening and closing of the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 107 lbs.



## **67STS SINGLE LID “SLANT TOP” SIDE BOX SPECIFICATIONS** **WHITE POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

67-3/4" overall length, 13-3/16" wide at the top, 8" wide at the bottom and an overall depth of 13-1/8".

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a white super durable polyester powder coat.
- Lid constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Sliding tray 19-1/2" x 8-7/8", with white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Full length small parts storage in the front of the box.
- Full size, stainless steel paddle latch is recessed into the lid.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Attaching hardware is stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 108 lbs.



## **67STSB SINGLE LID “SLANT TOP” SIDE BOX SPECIFICATIONS** **BLACK POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

67-3/4" overall length, 13-3/16" wide at the top, 8" wide at the bottom and an overall depth of 13-1/8".

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a black super durable polyester powder coat.
- Lid constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Sliding tray 19-1/2" x 8-7/8", with white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Full length small parts storage in the front of the box.
- Full size, stainless steel paddle latch is recessed into the lid.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Attaching hardware is stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 108 lbs.





## **67SW SINGLE LID WIDE SIDE BOX SPECIFICATIONS** **WHITE POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

67-3/4" overall length, 18-3/16" wide at the top, 13" wide at the bottom and an overall depth of 13-3/16".

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a white super durable polyester powder coat.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Full length small parts storage in the front of the box.
- A full size, stainless steel paddle latch is recessed into the hull of the box.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 133 lbs.



## **67SWA SINGLE LID ALUMINUM SIDE BOX SPECIFICATIONS** **BRIGHT DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

68" overall length, 18-11/16" wide at the top, 13" wide at the bottom and an overall depth of 13-3/16".  
6-1/8" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 bright diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and welded in with full arc welds.
- Lid is constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with three 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Full length small parts storage tray is in the front of the box.
- A full size, stainless steel paddle latch is recessed into the hull of the box.
- Two keys are furnished per box.
- Lid is equipped with a gas pressure shock for one-hand opening of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 71 lbs.



## **67SWAB SINGLE LID ALUMINUM SIDE BOX SPECIFICATIONS** **BLACK DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

68" overall length, 18-11/16" wide at the top, 13" wide at the bottom and an overall depth of 13-3/16".  
6-1/8" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and welded in with full arc welds.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with three 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Full length small parts storage tray is in the front of the box.
- A full size, stainless steel paddle latch is recessed into the hull of the box.
- Two keys are furnished per box.
- Lid is equipped with a gas pressure shock for one-hand opening of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Black boxes go through a five-stage zinc phosphate wash and are finished with a black super durable polyester powder coat.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 73 lbs.



## **67SWAW SINGLE LID ALUMINUM SIDE BOX SPECIFICATIONS** **WHITE DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

68" overall length, 18-11/16" wide at the top, 13" wide at the bottom and an overall depth of 13-3/16".  
6-1/8" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and welded in with full arc welds.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with three 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Full length small parts storage tray is in the front of the box.
- A full size, stainless steel paddle latch is recessed into the hull of the box.
- Two keys are furnished per box.
- Lid is equipped with a gas pressure shock for one-hand opening of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- White boxes go through a five-stage zinc phosphate wash and are finished with a white super durable polyester powder coat.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 73 lbs.



## **67SWB SINGLE LID WIDE SIDE BOX SPECIFICATIONS** **BLACK POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

67-3/4" overall length, 18-3/16" wide at the top, 13" wide at the bottom and an overall depth of 13-3/16".

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a black super durable polyester powder coat.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Full length small parts storage in the front of the box.
- A full size, stainless steel paddle latch is recessed into the hull of the box.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 133 lbs.



## **88S DOUBLE LID SIDE BOX SPECIFICATIONS** **WHITE POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

88-3/4" overall length, 13-3/16" wide at the top, 8" wide at the bottom and an overall depth of 13-3/16".

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a white super durable polyester powder coat.
- Lids are constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Each lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Full length small parts storage in the front of the box.
- Two full size stainless steel paddle latches are recessed into the hull of the box, one latch for each lid.
- Two keys are furnished per box.
- A spring type lid prop assists in the opening and closing of each lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail, mounting instructions included.
- Weight: 139 lbs.



## **88SB DOUBLE LID SIDE BOX SPECIFICATIONS** **BLACK POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

88-3/4" overall length, 13-3/16" wide at the top, 8" wide at the bottom and an overall depth of 13-3/16".

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a black super durable polyester powder coat.
- Lids are constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Each lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Full length small parts storage in the front of the box.
- Full size, stainless steel paddle latches are recessed into the hull of the box.
- Two keys are furnished per box.
- Spring type lid props assist in the opening and closing of the lids.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 139 lbs.



## **88SW DOUBLE LID WIDE SIDE BOX SPECIFICATIONS** **WHITE POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

88-3/4" overall length, 18-3/16" wide at the top, 13" wide at the bottom and an overall depth of 13-3/16".

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a white super durable polyester powder coat.
- Lids are constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Each lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Full length small parts storage in the front of the box.
- Two full size stainless steel paddle latches are recessed into the hull of the box, one latch for each lid.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of each lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail, mounting instructions included.
- Weight: 173 lbs.





## **88SWB DOUBLE LID WIDE SIDE BOX SPECIFICATIONS** **BLACK POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

88-3/4" overall length, 18-3/16" wide at the top, 13" wide at the bottom and an overall depth of 13-3/16".

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a black super durable polyester powder coat.
- Lids are constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Each lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Full length small parts storage in the front of the box.
- Full size stainless steel paddle latches are recessed into the hull of the box.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of each lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 173 lbs.



## **ALUMINUM "H" SERIES SINGLE DOOR UNDERBODY BOX SPECIFICATIONS** **BRIGHT DIAMOND TREADPLATE AND BLACK DIAMOND TREADPLATE**

### **BRIGHT DIAMOND TREADPLATE AND BLACK DIAMOND TREADPLATE.**

#### **TO INCLUDE THE FOLLOWING FEATURES:**

- .100 bright diamond treadplate aluminum construction.
- Horizontally hinged doors are constructed of .100 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Doors are attached to the hull of box with stainless steel pillow block type hinges with self-lubricating bushings and full length 5/16" stainless steel hinge pins.
- Hinges are riveted to the box.
- Door is held in the open position with heavy-duty machine chains.
- Chains are easily detachable to drop door down to 180°.
- Top panel of the box forms a drip rail over the door.
- A full size, stainless steel paddle latch is recessed into the door.
- Two keys are furnished per box.
- Doors can be closed with the latch in the locked position.
- Ribbed D-Bulb seal is installed in a recessed channel that runs the full perimeter of the door opening.
- Door has a formed knife edge on all 4 sides that contacts the seal when the door is closed.
- Black boxes go through a five-stage zinc phosphate wash and are finished with a black super durable polyester powder coat.



## **C56 SINGLE LID CROSSBOX SPECIFICATIONS** **WHITE POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

62-1/2" overall length, 20" wide, 17-7/16" deep.  
Approximate volume is 9.5 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and welded in with full arc welds.
- Lid is constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Sliding tray, 19-1/2" x 14-3/4" x 2-3/8", with white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while it is not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage zinc phosphate wash, anti-corrosion protection, and is finished with a white super durable polyester powder coat.
- Mounting hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail, mounting instructions included.
- Weight: 157 lbs.



## **C56A SINGLE LID ALUMINUM CROSSBOX SPECIFICATIONS** **BRIGHT DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

62-3/4" overall length, 20" wide, 17-9/16" deep.  
Approximate volume is 9.5 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 bright diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum, and welded in with full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with two gas shocks for one-hand opening of the box.
- Lid is constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Sliding tray, 19-1/2" x 14-3/4" x 2-3/8", with a white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail, mounting instructions included.
- Weight: 82 lbs.



## **C56AB SINGLE LID ALUMINUM CROSSBOX SPECIFICATIONS** **BLACK DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

62-3/4" overall length, 20" wide, 17-9/16" deep.  
Approximate volume is 9.5 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum, and welded in with full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with 2 gas pressure shocks for one-hand opening of the box.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Sliding tray, 19-1/2" x 14-3/4", with a white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Black boxes go through a five-stage zinc phosphate wash and are finished with a black super durable polyester powder coat.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 84 lbs.



## **C56AW SINGLE LID ALUMINUM CROSSBOX SPECIFICATIONS** **WHITE DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

62-3/4" overall length, 20" wide, 17-9/16" deep.  
Approximate volume is 9.5 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum, and welded in with full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with 2 gas pressure shocks for one-hand opening of the box.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Sliding tray, 19-1/2" x 14-3/4", with a white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- White boxes go through a five-stage zinc wash and are finished with a white super durable polyester powder coat.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 84 lbs.



## **C56B SINGLE LID CROSSBOX SPECIFICATIONS** **BLACK POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

62-1/2" overall length, 20" wide, 17-7/16" deep.  
Approximate volume is 9.5 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and welded in with full arc welds.
- Lid is constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Sliding tray, 19-1/2" x 14-3/4", with white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while it is not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage zinc phosphate wash, anti-corrosion protection, and is finished with a black super durable polyester powder coat.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 157 lbs.



## **C56LP SINGLE LID LOW PROFILE CROSSBOX SPECIFICATIONS** **WHITE POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

62-1/2" overall length, 20" wide, 14-11/16" deep.  
Approximate volume is 7.3 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and welded in with full arc welds.
- Lid is constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Sliding tray, 19-1/2" x 14-3/4", with white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while it is not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage zinc phosphate wash, anti-corrosion protection, and is finished with a white super durable polyester powder coat.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 146 lbs.





## **C56LPA SINGLE LID ALUMINUM LOW PROFILE CROSSBOX SPECIFICATIONS** **BRIGHT DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

62-3/4" overall length, 20" wide, 14-9/16" deep.  
Approximate volume is 7.3 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 bright diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum, and welded in with full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with 2 gas pressure shocks for one-hand opening of the box.
- Lid is constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Sliding tray, 19-1/2" x 14-3/4", with a white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 74 lbs.



## **C56LPAB SINGLE LID ALUMINUM LOW PROFILE CROSSBOX SPECIFICATIONS** **BLACK DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

62-3/4" overall length, 20" wide, 14-9/16" deep.  
Approximate volume is 7.3 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum, and welded in with full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with 2 gas pressure shocks for one-hand opening of the box.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Sliding tray, 19-1/2" x 14-3/4", with a white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Black boxes go through a five-stage zinc phosphate wash and are finished with a black super durable polyester powder coat.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 76 lbs.



## **C56LPAW SINGLE LID ALUMINUM LOW PROFILE CROSSBOX SPECIFICATIONS** **WHITE DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

62-3/4" overall length, 20" wide, 14-9/16" deep.  
Approximate volume is 7.3 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum, and welded in with full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with 2 gas pressure shocks for one-hand opening of the box.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Sliding tray, 19-1/2" x 14-3/4", with a white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- White boxes go through a five-stage zinc phosphate wash and are finished with a white super durable polyester powder coat.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 76 lbs.



## **C56LPB SINGLE LID LOW PROFILE CROSSBOX SPECIFICATIONS** **BLACK POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

62-1/2" overall length, 20" wide, 14-11/16" deep.  
Approximate volume is 7.3 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and welded in with full arc welds.
- Lid is constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Sliding tray, 19-1/2" x 14-3/4", with white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while it is not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage zinc phosphate wash, anti-corrosion protection, and is finished with a black super durable polyester powder coat.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 146 lbs.



## **C56LPD SINGLE LID LOW PROFILE DEEP CROSSBOX SPECIFICATIONS** **WHITE POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

62-1/2" overall length, 20" wide, 17-7/16" deep.  
Approximate volume is 8.5 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and welded in with full arc welds.
- Lid is constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Sliding tray, 19-1/2" x 14-3/4", with white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while it is not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage zinc phosphate wash, anti-corrosion protection, and is finished with a white super durable polyester powder coat.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 153 lbs.



**C56LPDA SINGLE LID ALUMINUM**  
**LOW PROFILE DEEP CROSSBOX SPECIFICATIONS**  
**BRIGHT DIAMOND TREADPLATE**

**BOX DIMENSIONS AS FOLLOWS:**

62-3/4" overall length, 20" wide, 17-5/16" deep.  
Approximate volume is 8.5 cubic feet.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 bright diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum, and welded in with full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with 2 gas pressure shocks for one-hand opening of the box.
- Lid is constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Sliding tray, 19-1/2" x 14-3/4", with a white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 77 lbs.



**C56LPDAB SINGLE LID ALUMINUM**  
**LOW PROFILE DEEP CROSSBOX SPECIFICATIONS**  
**BLACK DIAMOND TREADPLATE**

**BOX DIMENSIONS AS FOLLOWS:**

62-3/4" overall length, 20" wide, 17-5/16" deep.  
Approximate volume is 8.5 cubic feet.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum, and welded in with full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with 2 gas pressure shocks for one-hand opening of the box.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Sliding tray, 19-1/2" x 14-3/4", with a white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Black boxes go through a five-stage zinc phosphate wash and are finished with a black super durable polyester powder coat.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 79 lbs.



**C56LPDAW SINGLE LID ALUMINUM**  
**LOW PROFILE DEEP CROSSBOX SPECIFICATIONS**  
**WHITE DIAMOND TREADPLATE**

**BOX DIMENSIONS AS FOLLOWS:**

62-3/4" overall length, 20" wide, 17-5/16" deep.  
Approximate volume is 8.5 cubic feet.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum, and welded in with full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with 2 gas pressure shocks for one-hand opening of the box.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Sliding tray, 19-1/2" x 14-3/4", with a white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- White boxes go through a five-stage zinc phosphate wash and are finished with a white super durable polyester powder coat.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 79 lbs.





## **C56LPDB SINGLE LID LOW PROFILE DEEP CROSSBOX SPECIFICATIONS** **BLACK POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

62-1/2" overall length, 20" wide, 17-7/16" deep.  
Approximate volume is 8.5 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and welded in with full arc welds.
- Lid is constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Sliding tray, 19-1/2" x 14-3/4", with white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while it is not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage zinc phosphate wash, anti-corrosion protection, and is finished with a black super durable polyester powder coat.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 153 lbs.



## **C63 SINGLE LID CROSSBOX SPECIFICATIONS** **WHITE POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

71-1/4" overall length, 20" wide, 17-7/16" deep.  
Approximate volume is 12.75 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and welded in with full arc welds.
- Lid is constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Sliding tray, 29-1/4" x 19-1/4" x 2-3/8", with white super durable polyester powder coat finish.
- Tray comes with 6 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while it is not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage zinc phosphate wash, anti-corrosion protection, and is finished with a white super durable polyester powder coat.
- Mounting hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail, mounting instructions included.
- Weight: 178 lbs.



## **C63A SINGLE LID ALUMINUM CROSSBOX SPECIFICATIONS** **BRIGHT DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

71-3/4" overall length, 20" wide, 17-7/16" deep.  
Approximate volume is 12.75 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 bright diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum, and welded in with full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with two gas shocks for one-hand opening of the box.
- Lid is constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Sliding tray, 29-1/4" x 19-1/4" x 2-3/8", with a white super durable polyester powder coat finish.
- Tray comes with 6 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail, mounting instructions included.
- Weight: 97 lbs.



## **C63AB SINGLE LID ALUMINUM CROSSBOX SPECIFICATIONS** **BLACK DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

71-3/4" overall length, 20" wide, 17-7/16" deep.  
Approximate volume is 12.75 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum, and welded in with full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with 2 gas pressure shocks for one-hand opening of the box.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Sliding tray, 29-1/2" x 19-1/2", with a white super durable polyester powder coat finish.
- Tray comes with 6 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Black boxes go through a five-stage zinc phosphate wash and are finished with a black super durable polyester powder coat.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 99 lbs.



## **C63AW SINGLE LID ALUMINUM CROSSBOX SPECIFICATIONS** **WHITE DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

71-3/4" overall length, 20" wide, 17-7/16" deep.  
Approximate volume is 12.75 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum, and welded in with full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with 2 gas pressure shocks for one-hand opening of the box.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Sliding tray, 29-1/2" x 19-1/2", with a white super durable polyester powder coat finish.
- Tray comes with 6 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- White boxes go through a five-stage zinc phosphate wash and are finished with a white super durable polyester powder coat.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 99 lbs.



## **C63B SINGLE LID CROSSBOX SPECIFICATIONS** **BLACK POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

71-1/4" overall length, 20" wide, 17-7/16" deep.  
Approximate volume is 12.75 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and welded in with full arc welds.
- Lid is constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Sliding tray, 29-1/2" x 19-1/2", with white super durable polyester powder coat finish.
- Tray comes with 6 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while it is not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage zinc phosphate wash, anti-corrosion protection, and is finished with a black super durable polyester powder coat.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 178 lbs.



## **C63D SINGLE LID DEEP CROSSBOX SPECIFICATIONS** **WHITE POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

71-1/4" overall length, 20" wide, 25-11/16" deep.  
Approximate volume is 19.5 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and welded in with full arc welds.
- Lid is constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Sliding tray, 29-1/4" x 19-1/4" x 2-3/8", with white super durable polyester powder coat finish.
- Tray comes with 6 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while it is not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage zinc phosphate wash, anti-corrosion protection, and is finished with a white super durable polyester powder coat.
- Mounting hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail, mounting instructions included.
- Weight: 205 lbs.



## **C63DA SINGLE LID ALUMINUM DEEP CROSSBOX SPECIFICATIONS** **BRIGHT DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

71-3/4" overall length, 20" wide, 25-11/16" deep.  
Approximate volume is 19.5 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 bright diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum, and welded in with full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with two gas shocks for one-hand opening of the box.
- Lid is constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Lid is attached to the hull of the box with two 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Sliding tray, 29-1/4" x 19-1/4" x 2-3/8", with a white super durable polyester powder coat finish.
- Tray comes with 6 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail, mounting instructions included.
- Weight: 104 lbs.





## **C63DAB SINGLE LID ALUMINUM WIDE CROSSBOX SPECIFICATIONS** **BLACK DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

71-3/4" overall length, 20" wide, 25-11/16" deep.  
Approximate volume is 19.5 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum, and welded in with full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with 2 gas pressure shocks for one-hand opening of the box.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Sliding tray, 29-1/2" x 19-1/2", with a white super durable polyester powder coat finish.
- Tray comes with 6 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Black boxes go through a five-stage zinc phosphate wash and are finished with a black super durable polyester powder coat.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 106 lbs.



## **C63DAW SINGLE LID ALUMINUM WIDE CROSSBOX SPECIFICATIONS** **WHITE DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

71-3/4" overall length, 20" wide, 25-11/16" deep.  
Approximate volume is 19.5 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum, and welded in with full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with 2 gas pressure shocks for one-hand opening of the box.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Sliding tray, 29-1/2" x 19-1/2", with a white super durable polyester powder coat finish.
- Tray comes with 6 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- White boxes go through a five-stage zinc phosphate wash and are finished with a white super durable polyester powder coat.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 106 lbs.



## **C63DB SINGLE LID DEEP CROSSBOX SPECIFICATIONS** **BLACK POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

71-1/4" overall length, 20" wide, 25-11/16" deep.  
Approximate volume is 19.5 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and welded in with full arc welds.
- Lid is constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with four 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Sliding tray, 29-1/2" x 19-1/2", with white super durable polyester powder coat finish.
- Tray comes with 6 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while it is not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage zinc phosphate wash, anti-corrosion protection, and is finished with a black super durable polyester powder coat.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 205 lbs.



## **C63LP SINGLE LID LOW PROFILE CROSSBOX SPECIFICATIONS** **WHITE POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

71-1/4" overall length, 20" wide, 14-11/16" deep.  
Approximate volume is 9.1 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and welded in with full arc welds.
- Lid is constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Sliding tray, 29-1/2" x 14-3/4" x 2-3/8", with white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while it is not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage zinc phosphate wash, anti-corrosion protection, and is finished with a white super durable polyester powder coat.
- Mounting hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail, mounting instructions included.
- Weight: 170 lbs.



## **C63LPA SINGLE LID ALUMINUM LOW PROFILE CROSSBOX SPECIFICATIONS** **BRIGHT DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

71-3/4" overall length, 20" wide, 14-11/16" deep.  
Approximate volume is 9.1 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 bright diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum, and welded in with full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with two gas shocks for one-hand opening of the box.
- Lid is constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Sliding tray, 29-1/2" x 14-3/4" x 2-3/8", with a white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail, mounting instructions included.
- Weight: 86 lbs.



## **C63LPAB SINGLE LID ALUMINUM LOW PROFILE CROSSBOX SPECIFICATIONS** **BLACK DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

71-3/4" overall length, 20" wide, 14-11/16" deep.  
Approximate volume is 9.1 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum, and welded in with full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with 2 gas pressure shocks for one-hand opening of the box.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Sliding tray, 29-1/2" x 19-1/2", with a white super durable polyester powder coat finish.
- Tray comes with 6 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Black boxes go through a five-stage zinc phosphate wash and are finished with a black super durable polyester powder coat.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 88 lbs.



## **C63LPAW SINGLE LID ALUMINUM LOW PROFILE CROSSBOX SPECIFICATIONS** **WHITE DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

71-3/4" overall length, 20" wide, 14-11/16" deep.  
Approximate volume is 9.1 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum, and welded in with full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with 2 gas pressure shocks for one-hand opening of the box.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Sliding tray, 29-1/2" x 19-1/2", with a white super durable polyester powder coat finish.
- Tray comes with 6 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- White boxes go through a five-stage zinc phosphate wash and are finished with a white super durable polyester powder coat.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 88 lbs.



## **C63LPB SINGLE LID LOW PROFILE CROSSBOX SPECIFICATIONS** **BLACK POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

71-1/4" overall length, 20" wide, 14-11/16" deep.  
Approximate volume is 9.1 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and welded in with full arc welds.
- Lid is constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Sliding tray, 29-1/2" x 19-1/2", with white super durable polyester powder coat finish.
- Tray comes with 6 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while it is not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage zinc phosphate wash, anti-corrosion protection, and is finished with a black super durable polyester powder coat.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 170 lbs.





## **C63LPD SINGLE LID LOW PROFILE DEEP CROSSBOX SPECIFICATIONS** **WHITE POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

71-1/4" overall length, 20" wide, 17-7/16" deep.  
Approximate volume is 11 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and welded in with full arc welds.
- Lid is constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Sliding tray, 29-1/2" x 14-3/4" x 2-3/8", with white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while it is not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage zinc phosphate wash, anti-corrosion protection, and is finished with a white super durable polyester powder coat.
- Mounting hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail, mounting instructions included.
- Weight: 180 lbs.



**C63LPDA SINGLE LID ALUMINUM**  
**LOW PROFILE DEEP CROSSBOX SPECIFICATIONS**  
**BRIGHT DIAMOND TREADPLATE**

**BOX DIMENSIONS AS FOLLOWS:**

71-3/4" overall length, 20" wide, 17-7/16" deep.  
Approximate volume is 11 cubic feet.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 bright diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum, and welded in with full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with two gas shocks for one-hand opening of the box.
- Lid is constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Sliding tray, 29-1/2" x 14-3/4" x 2-3/8", with a white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail, mounting instructions included.
- Weight 90 lbs.



**C63LPDAB SINGLE LID ALUMINUM**  
**LOW PROFILE DEEP CROSSBOX SPECIFICATIONS**  
**BLACK DIAMOND TREADPLATE**

**BOX DIMENSIONS AS FOLLOWS:**

71-3/4" overall length, 20" wide, 17-7/16" deep.  
Approximate volume is 11 cubic feet.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum, and welded in with full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with 2 gas pressure shocks for one-hand opening of the box.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Sliding tray, 29-1/2" x 19-1/2", with a white super durable polyester powder coat finish.
- Tray comes with 6 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Black boxes go through a five-stage zinc phosphate wash and are finished with a black super durable polyester powder coat.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight 92 lbs.



## **C63LPDB SINGLE LID LOW PROFILE DEEP CROSSBOX SPECIFICATIONS** **BLACK POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

71-1/4" overall length, 20" wide, 17-7/16" deep.  
Approximate volume is 11 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and welded in with full arc welds.
- Lid is constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Sliding tray, 29-1/2" x 19-1/2", with white super durable polyester powder coat finish.
- Tray comes with 6 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while it is not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage zinc phosphate wash, anti-corrosion protection, and is finished with a black super durable polyester powder coat.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 180 lbs.



**C63LPNA SINGLE LID ALUMINUM**  
**LOW PROFILE NARROW CROSSBOX SPECIFICATIONS**  
**BRIGHT DIAMOND TREADPLATE**

**BOX DIMENSIONS AS FOLLOWS:**

71-3/4" overall length, 15-1/2" wide, 14-11/16" deep.  
Approximate volume is 6.8 cubic feet.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 bright diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum, and welded in with full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with 2 gas pressure shocks for one-hand opening of the box.
- Lid is constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Sliding tray, 19-1/2" x 14-3/4", with a white super durable polyester powder coat finish.
- Tray comes with 6 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 70 lbs.



**C63LPNAB SINGLE LID ALUMINUM**  
**LOW PROFILE NARROW CROSSBOX SPECIFICATIONS**  
**BLACK DIAMOND TREADPLATE**

**BOX DIMENSIONS AS FOLLOWS:**

71-3/4" overall length, 15-1/2" wide, 14-11/16" deep.  
Approximate volume is 6.8 cubic feet.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum, and welded in with full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with 2 gas pressure shocks for one-hand opening of the box.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Sliding tray, 19-1/2" x 14-3/4", with a white super durable polyester powder coat finish.
- Tray comes with 6 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Black boxes go through a five-stage zinc phosphate wash and are finished with a black super durable polyester powder coat.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 72 lbs.



**C63LPNAW SINGLE LID ALUMINUM**  
**LOW PROFILE NARROW CROSSBOX SPECIFICATIONS**  
**WHITE DIAMOND TREADPLATE**

**BOX DIMENSIONS AS FOLLOWS:**

71-3/4" overall length, 15-1/2" wide, 14-11/16" deep.  
Approximate volume is 6.8 cubic feet.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum, and welded in with full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with 2 gas pressure shocks for one-hand opening of the box.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Sliding tray, 19-1/2" x 14-3/4", with a white super durable polyester powder coat finish.
- Tray comes with 6 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- White boxes go through a five-stage zinc phosphate wash and are finished with a white super durable polyester powder coat.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 72 lbs.



## **C63S SINGLE LID SHALLOW CROSSBOX SPECIFICATIONS** **WHITE POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

71-1/4" overall length, 20" wide, 14-3/16" deep.  
Approximate volume is 10.5 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and welded in with full arc welds.
- Lid is constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Sliding tray, 29-1/4" x 19-1/4" x 2-3/8", with white super durable polyester powder coat finish.
- Tray comes with 6 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while it is not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage zinc phosphate wash, anti-corrosion protection, and is finished with a white super durable polyester powder coat.
- Mounting hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail, mounting instructions included.
- Weight: 174 lbs.





## **C63SA SINGLE LID SHALLOW ALUMINUM CROSSBOX SPECIFICATIONS** **BRIGHT DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

71-1/2" overall length, 20" wide, 14-3/16" deep.  
Approximate volume is 10.5 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 bright diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum, and welded in with full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with two gas shocks for one-hand opening of the box.
- Lid is constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Sliding tray, 29-1/4" x 19-1/4" x 2-3/8", with a white super durable polyester powder coat finish.
- Tray comes with 6 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail, mounting instructions included.
- Weight: 92 lbs.



## **C63SAB SINGLE LID SHALLOW ALUMINUM CROSSBOX SPECIFICATIONS** **BLACK DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

71-1/2" overall length, 20" wide, 14-3/16" deep.  
Approximate volume is 10.5 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum, and welded in with full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with 2 gas pressure shocks for one-hand opening of the box.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Sliding tray, 29-1/2" x 19-1/2", with a white super durable polyester powder coat finish.
- Tray comes with 6 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Black boxes go through a five-stage zinc phosphate wash and are finished with a black super durable polyester powder coat.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 94 lbs.



## **C63SAW SINGLE LID SHALLOW ALUMINUM CROSSBOX SPECIFICATIONS** **WHITE DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

71-1/2" overall length, 20" wide, 14-3/16" deep.  
Approximate volume is 10.5 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum, and welded in with full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with 2 gas pressure shocks for one-hand opening of the box.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Sliding tray, 29-1/2" x 19-1/2", with a white super durable polyester powder coat finish.
- Tray comes with 6 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- White boxes go through a five-stage zinc phosphate wash and are finished with a white super durable polyester powder coat.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 94 lbs.



## **C63SB SINGLE LID SHALLOW CROSSBOX SPECIFICATIONS** **BLACK POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

71-1/4" overall length, 20" wide, 14-3/16" deep.  
Approximate volume is 10.5 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and welded in with full arc welds.
- Lid is constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Sliding tray, 29-1/2" x 19-1/2", with white super durable polyester powder coat finish.
- Tray comes with 6 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while it is not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage zinc phosphate wash, anti-corrosion protection, and is finished with a black super durable polyester powder coat.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 174 lbs.



## **C63T SINGLE LID CROSSBOX SPECIFICATIONS** **WHITE POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

71-1/4" overall length, 20" wide, 7-3/16" deep.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and welded in with full arc welds.
- Lid is constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Box is slotted for dividers on 2" centers.
- Box comes with 3 adjustable dividers.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage zinc phosphate wash, anti-corrosion protection, and is finished with a white super durable polyester powder coat.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 130 lbs.



## **C63TB SINGLE LID CROSSBOX SPECIFICATIONS** **BLACK POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

71-1/4" overall length, 20" wide, 7-3/16" deep.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and welded in with full arc welds.
- Lid is constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Box is slotted for dividers on 2" centers.
- Box comes with 3 adjustable dividers.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage zinc phosphate wash, anti-corrosion protection, and is finished with a black super durable polyester powder coat.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 130 lbs.



## **C63W SINGLE LID WIDE CROSSBOX SPECIFICATIONS** **WHITE POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

71-1/4" overall length, 30" wide, 17-7/16" deep.  
Approximate volume is 19.4 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and welded in with full arc welds.
- Lid is constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Two double-spring type lid prop assemblies assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with four 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Sliding tray, 29-1/4" x 19-1/4" x 2-3/8", with white super durable polyester powder coat finish.
- Tray comes with 6 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while it is not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage zinc phosphate wash, anti-corrosion protection, and is finished with a white polyester powder coat.
- Mounting hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail, mounting instructions included.
- Weight: 231 lbs.



## **C63WA SINGLE LID ALUMINUM WIDE CROSSBOX SPECIFICATIONS** **BRIGHT DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

71-1/2" overall length, 30" wide, 17-7/16" deep.  
Approximate volume is 19.4 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 bright diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum, and welded in with full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with two gas shocks for one-hand opening of the box.
- Lid is constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Sliding tray, 29-1/4" x 19-1/4" x 2-3/8", with a white super durable polyester powder coat finish.
- Tray comes with 6 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail, mounting instructions included.
- Weight: 124 lbs.





## **C63WAB SINGLE LID ALUMINUM WIDE CROSSBOX SPECIFICATIONS** **BLACK POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

71-1/2" overall length, 30" wide, 17-7/16" deep.  
Approximate volume is 19.4 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum, and welded in with full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with 2 gas pressure shocks for one-hand opening of the box.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Sliding tray, 29-1/2" x 19-1/2", with a white super durable polyester powder coat finish.
- Tray comes with 6 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Black boxes go through a five-stage zinc phosphate wash and are finished with a black super durable polyester powder coat.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 126 lbs.



## **C63WAW SINGLE LID ALUMINUM WIDE CROSSBOX SPECIFICATIONS** **WHITE POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

71-1/2" overall length, 30" wide, 17-7/16" deep.  
Approximate volume is 19.4 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum, and welded in with full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with 2 gas pressure shocks for one-hand opening of the box.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Sliding tray, 29-1/2" x 19-1/2", with a white super durable polyester powder coat finish.
- Tray comes with 6 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- White boxes go through a five-stage zinc phosphate wash and are finished with a white super durable polyester powder coat.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 126 lbs.



## **C63WB SINGLE LID WIDE CROSSBOX SPECIFICATIONS** **BLACK POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

71-1/4" overall length, 30" wide, 17-7/16" deep.  
Approximate volume is 19.4 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and welded in with full arc welds.
- Lid is constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Four spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with four 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Sliding tray, 29-1/2" x 19-1/2", with white super durable polyester powder coat finish.
- Tray comes with 6 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while it is not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage zinc phosphate wash, anti-corrosion protection, and is finished with a black super durable polyester powder coat.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 231 lbs.



## **C63WD SINGLE LID WIDE AND DEEP CROSSBOX SPECIFICATIONS** **WHITE POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

71-1/4" overall length, 30" wide, 25-11/16" deep.  
Approximate volume is 27.5 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and welded in with full arc welds.
- Lid is constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Two double-spring type lid prop assemblies assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with four 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Sliding tray, 29-1/4" x 19-1/4" x 2-3/8", with white super durable polyester powder coat finish.
- Tray comes with 6 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while it is not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage zinc phosphate wash, anti-corrosion protection, and is finished with a white super durable polyester powder coat.
- Mounting hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail, mounting instructions included.
- Weight: 255 lbs.



**C63WDA SINGLE LID ALUMINUM  
WIDE AND DEEP CROSSBOX SPECIFICATIONS  
BRIGHT DIAMOND TREADPLATE**

**BOX DIMENSIONS AS FOLLOWS:**

71-1/2" overall length, 30" wide, 25-11/16" deep.  
Approximate volume is 27.5 cubic feet.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 bright diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum, and welded in with full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with two gas shocks for one-hand opening of the box.
- Lid is constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Sliding tray, 29-1/4" x 19-1/4" x 2-3/8", with a white super durable polyester powder coat finish.
- Tray comes with 6 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail, mounting instructions included.
- Weight: 134 lbs.



**C63WDAB SINGLE LID ALUMINUM**  
**WIDE AND DEEP CROSSBOX SPECIFICATIONS**  
**BLACK DIAMOND TREADPLATE**

**BOX DIMENSIONS AS FOLLOWS:**

71-1/2" overall length, 30" wide, 25-11/16" deep.  
Approximate volume is 27.5 cubic feet.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum, and welded in with full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with 2 gas pressure shocks for one-hand opening of the box.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Sliding tray, 29-1/2" x 19-1/2", with a white super durable polyester powder coat finish.
- Tray comes with 6 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Black boxes go through a five-stage zinc phosphate wash and are finished with a black super durable polyester powder coat.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 136 lbs.



**C63WDAW SINGLE LID ALUMINUM**  
**WIDE AND DEEP CROSSBOX SPECIFICATIONS**  
**WHITE DIAMOND TREADPLATE**

**BOX DIMENSIONS AS FOLLOWS:**

71-1/2" overall length, 30" wide, 25-11/16" deep.  
Approximate volume is 27.5 cubic feet.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum, and welded in with full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with 2 gas pressure shocks for one-hand opening of the box.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Sliding tray, 29-1/2" x 19-1/2", with a white super durable polyester powder coat finish.
- Tray comes with 6 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- White boxes go through a five-stage zinc phosphate wash and are finished with a white super durable polyester powder coat.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 136 lbs.



## **C63WDB SINGLE LID WIDE AND DEEP CROSSBOX SPECIFICATIONS** **BLACK POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

71-1/4" overall length, 30" wide, 25-11/16" deep.  
Approximate volume is 27.5 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and welded in with full arc welds.
- Lid is constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Four spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with four 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Sliding tray, 29-1/2" x 19-1/2", with white super durable polyester powder coat finish.
- Tray comes with 6 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while it is not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage zinc phosphate wash, anti-corrosion protection, and is finished with a black super durable polyester powder coat.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 255 lbs.





**C63WSA SINGLE LID ALUMINUM**  
**WIDE SHALLOW CROSSBOX SPECIFICATIONS**  
**BRIGHT DIAMOND TREADPLATE**

**BOX DIMENSIONS AS FOLLOWS:**

71-1/2" overall length, 30" wide, 14-3/16" deep.  
Approximate volume is 16 cubic feet.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 bright diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum, and welded in with full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with 2 gas pressure shocks for one-hand opening of the box.
- Lid is constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Sliding tray, 29-1/2" x 19-1/2", with a white super durable polyester powder coat finish.
- Tray comes with 6 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 116 lbs.



**C63WSAB SINGLE LID ALUMINUM**  
**WIDE SHALLOW CROSSBOX SPECIFICATIONS**  
**BLACK DIAMOND TREADPLATE**

**BOX DIMENSIONS AS FOLLOWS:**

71-1/2" overall length, 30" wide, 14-3/16" deep.  
Approximate volume is 16 cubic feet.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum, and welded in with full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with 2 gas pressure shocks for one-hand opening of the box.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Sliding tray, 29-1/2" x 19-1/2", with a white super durable polyester powder coat finish.
- Tray comes with 6 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Black boxes go through a five-stage zinc phosphate wash and are finished with a black super durable polyester powder coat.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 118 lbs.



**C63WSAW SINGLE LID ALUMINUM**  
**WIDE SHALLOW CROSSBOX SPECIFICATIONS**  
**WHITE DIAMOND TREADPLATE**

**BOX DIMENSIONS AS FOLLOWS:**

71-1/2" overall length, 30" wide, 14-3/16" deep.  
Approximate volume is 16 cubic feet.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum, and welded in with full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with 2 gas pressure shocks for one-hand opening of the box.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Sliding tray, 29-1/2" x 19-1/2", with a white super durable polyester powder coat finish.
- Tray comes with 6 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- White boxes go through a five-stage zinc phosphate wash and are finished with a white super durable polyester powder coat.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 118 lbs.



## **FD301024 FLOOR DRAWER SPECIFICATIONS** **WHITE POWDER COAT FINISH**

### **DIMENSIONS AS FOLLOWS:**

30-1/4" overall length, 11-5/8" overall height and 24-5/8" overall depth.  
6" drawer height

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14GA or thicker construction.
- Full size easy to grab paddle latch with 2 keys furnished.
- Drawers are easily removable and glide on heavy duty sealed roller bearings.
- Ribbed D-bulb seal completely around drawer opening.
- Anti slip strips are factory installed on top of unit for added traction.
- Quick and easy installation. Drawer removal not necessary for mounting. Hardware included.
- 1200 lb. top load weight rating (evenly distributed).
- Drawers and 2 full length dividers are slotted on 2" centers.
- Cross dividers are easily added or removed allowing flexible storage.
- Units go through a five-stage zinc phosphate wash, anti-corrosion protection and are finished with a super durable polyester powder coat.
- Weight: 153 lbs.



## **FD301024B FLOOR DRAWER SPECIFICATIONS** **BLACK POWDER COAT FINISH**

### **DIMENSIONS AS FOLLOWS:**

30-1/4" overall length, 11-5/8" overall height and 24-5/8" overall depth.  
6" drawer height

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 GA or thicker construction.
- Full size easy to grab paddle latch with 2 keys furnished.
- Drawers are easily removable and glide on heavy duty sealed roller bearings.
- Ribbed D-bulb seal completely around drawer opening.
- Anti slip strips are factory installed on top of unit for added traction.
- Quick and easy installation. Drawer removal not necessary for mounting. Hardware included.
- 1200 lb. top load weight rating (evenly distributed).
- Drawers and 2 full length dividers are slotted on 2" centers.
- Cross dividers are easily added or removed allowing flexible storage.
- Units go through a five-stage zinc phosphate wash, anti-corrosion protection and are finished with a super durable polyester powder coat.
- Weight: 153 lbs.



## **FD301048 FLOOR DRAWER SPECIFICATIONS** **WHITE POWDER COAT FINISH**

### **DIMENSIONS AS FOLLOWS:**

30-1/4" overall length, 11-5/8" overall height and 48-5/8" overall depth.  
6" drawer height

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 GA or thicker construction.
- Full size easy to grab paddle latch with 2 keys furnished.
- Drawers are easily removable and glide on heavy duty sealed roller bearings.
- Ribbed D-bulb seal completely around drawer opening.
- Anti slip strips are factory installed on top of unit for added traction.
- Quick and easy installation. Drawer removal not necessary for mounting. Hardware included.
- 1200 lb. top load weight rating (evenly distributed).
- Drawers and 2 full length dividers are slotted on 2" centers.
- Cross dividers are easily added or removed allowing flexible storage.
- Units go through a five-stage zinc phosphate wash, anti-corrosion protection and are finished with a super durable polyester powder coat.
- Weight: 248 lbs.



## **FD301048B FLOOR DRAWER SPECIFICATIONS** **BLACK POWDER COAT FINISH**

### **DIMENSIONS AS FOLLOWS:**

30-1/4" overall length, 11-5/8" overall height and 48-5/8" overall depth.  
6" drawer height

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 GA or thicker construction.
- Full size easy to grab paddle latch with 2 keys furnished.
- Drawers are easily removable and glide on heavy duty sealed roller bearings.
- Ribbed D-bulb seal completely around drawer opening.
- Anti slip strips are factory installed on top of unit for added traction.
- Quick and easy installation. Drawer removal not necessary for mounting. Hardware included.
- 1200 lb. top load weight rating (evenly distributed).
- Drawers and 2 full length dividers are slotted on 2" centers.
- Cross dividers are easily added or removed allowing flexible storage.
- Units go through a five-stage zinc phosphate wash, anti-corrosion protection and are finished with a super durable polyester powder coat.
- Weight: 248 lbs.



## **FD401024 FLOOR DRAWER SPECIFICATIONS** **WHITE POWDER COAT FINISH**

### **DIMENSIONS AS FOLLOWS:**

40-1/4" overall length, 11-5/8" overall height and 24-5/8" overall depth.  
6" drawer height

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 GA or thicker construction.
- Full size easy to grab paddle latch with 2 keys furnished.
- Drawers are easily removable and glide on heavy duty sealed roller bearings.
- Ribbed D-bulb seal completely around drawer opening.
- Anti slip strips are factory installed on top of unit for added traction.
- Quick and easy installation. Drawer removal not necessary for mounting. Hardware included.
- 1200 lb. top load weight rating (evenly distributed).
- Drawers and 2 full length dividers are slotted on 2" centers.
- Cross dividers are easily added or removed allowing flexible storage.
- Units go through a five-stage zinc phosphate wash, anti-corrosion protection and are finished with a super durable polyester powder coat.
- Weight: 186 lbs.





## **FD401024B FLOOR DRAWER SPECIFICATIONS** **BLACK POWDER COAT FINISH**

### **DIMENSIONS AS FOLLOWS:**

40-1/4" overall length, 11-5/8" overall height and 24-5/8" overall depth.  
6" drawer height

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 GA or thicker construction.
- Full size easy to grab paddle latch with 2 keys furnished.
- Drawers are easily removable and glide on heavy duty sealed roller bearings.
- Ribbed D-bulb seal completely around drawer opening.
- Anti slip strips are factory installed on top of unit for added traction.
- Quick and easy installation. Drawer removal not necessary for mounting. Hardware included.
- 1200 lb. top load weight rating (evenly distributed).
- Drawers and 2 full length dividers are slotted on 2" centers.
- Cross dividers are easily added or removed allowing flexible storage.
- Units go through a five-stage zinc phosphate wash, anti-corrosion protection and are finished with a super durable polyester powder coat.
- Weight: 186 lbs.



## **FD401048 FLOOR DRAWER SPECIFICATIONS** **WHITE POWDER COAT FINISH**

### **DIMENSIONS AS FOLLOWS:**

40-1/4" overall length, 11-5/8" overall height and 48-5/8" overall depth.  
6" drawer height

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 GA or thicker construction.
- Full size easy to grab paddle latch with 2 keys furnished.
- Drawers are easily removable and glide on heavy duty sealed roller bearings.
- Ribbed D-bulb seal completely around drawer opening.
- Anti slip strips are factory installed on top of unit for added traction.
- Quick and easy installation. Drawer removal not necessary for mounting. Hardware included.
- 1200 lb. top load weight rating (evenly distributed).
- Drawers and 2 full length dividers are slotted on 2" centers.
- Cross dividers are easily added or removed allowing flexible storage.
- Units go through a five-stage zinc phosphate wash, anti-corrosion protection and are finished with a super durable polyester powder coat.
- Weight: 290 lbs.



## **FD401048B FLOOR DRAWER SPECIFICATIONS** **BLACK POWDER COAT FINISH**

### **DIMENSIONS AS FOLLOWS:**

40-1/4" overall length, 11-5/8" overall height and 48-5/8" overall depth.  
6" drawer height

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 GA or thicker construction.
- Full size easy to grab paddle latch with 2 keys furnished.
- Drawers are easily removable and glide on heavy duty sealed roller bearings.
- Ribbed D-bulb seal completely around drawer opening.
- Anti slip strips are factory installed on top of unit for added traction.
- Quick and easy installation. Drawer removal not necessary for mounting. Hardware included.
- 1200 lb. top load weight rating (evenly distributed).
- Drawers and 2 full length dividers are slotted on 2" centers.
- Cross dividers are easily added or removed allowing flexible storage.
- Units go through a five-stage zinc phosphate wash, anti-corrosion protection and are finished with a super durable polyester powder coat.
- Weight: 290 lbs.



## **M36-1NMA SINGLE LID ALUMINUM, CHEST TYPE, BOX SPECIFICATIONS** **BRIGHT DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

37-3/16" overall length, 16" wide, 16-1/8" deep.  
Approximate volume is 4.8 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 bright diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and fully welded on all 4 sides.
- Lid is constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- A full size, stainless steel paddle latch is recessed into the hull of the box.
- Two keys are furnished per box.
- Lid is equipped with a gas pressure shock for one-hand opening of the box.
- Lid is attached to the hull of the box with two 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Offset in the rear of the lid allows flush mounting to the front of the pickup box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Attaching hardware is included.
- Weight: 39 lbs.



## **M36-1NMAB SINGLE LID ALUMINUM, CHEST TYPE, BOX SPECIFICATIONS** **BLACK DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

37-3/16" overall length, 16" wide, 16-1/8" deep.  
Approximate volume is 4.8 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and fully welded on all 4 sides.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- A full size, stainless steel paddle latch is recessed into the hull of the box.
- Two keys are furnished per box.
- Lid is equipped with a gas pressure shock for one-hand opening of the box.
- Lid is attached to the hull of the box with two 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Offset in the rear of the lid allows flush mounting to the front of the pickup box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Black boxes go through a five-stage zinc phosphate wash and are finished with a black super durable polyester powder coat.
- Attaching hardware is included.
- Weight: 41 lbs.



## **M36-1NMAW SINGLE LID ALUMINUM, CHEST TYPE, BOX SPECIFICATIONS** **WHITE DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

37-3/16" overall length, 16" wide, 16-1/8" deep.  
Approximate volume is 4.8 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and fully welded on all 4 sides.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- A full size, stainless steel paddle latch is recessed into the hull of the box.
- Two keys are furnished per box.
- Lid is equipped with a gas pressure shock for one-hand opening of the box.
- Lid is attached to the hull of the box with two 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Offset in the rear of the lid allows flush mounting to the front of the pickup box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- White boxes go through a five-stage zinc phosphate wash and are finished with a white super durable polyester powder coat.
- Attaching hardware is included.
- Weight: 41 lbs.



## **M45-1NM SINGLE LID CHEST TYPE BOX SPECIFICATIONS** **WHITE POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

45-3/4" overall length, 20" wide, 19-3/16" deep.  
Approximate volume is 10 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and fully welded on all 4 sides.
- Lid is constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Full size, stainless steel paddle latches are recessed into the hull of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Fixed tray, 45" x 6", welded into the back wall of the box.
- Tray comes with 3 fixed dividers.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage zinc phosphate wash, anti-corrosion protection, and is finished with a white super durable polyester powder coat.
- Attaching hardware is included.
- Weight: 131 lbs



## **M45-1NMA SINGLE LID ALUMINUM, CHEST TYPE, BOX SPECIFICATIONS** **BRIGHT DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

46-3/16" overall length, 20" wide, 19-1/4" deep.  
Approximate volume is 10 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 bright diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and fully welded on all 4 sides.
- Lid is constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Two full size, stainless steel paddle latches are recessed into the hull of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with 2 gas pressure shocks for one-hand opening of the box.
- Lid is attached to the hull of the box with three 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Fixed tray, 45" x 6", welded into the back wall of the box.
- Tray comes with 3 fixed dividers.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Attaching hardware is included.
- Weight: 67 lbs.





## **M45-1NMAB SINGLE LID ALUMINUM, CHEST TYPE, BOX SPECIFICATIONS** **BLACK DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

46-3/16" overall length, 20" wide, 19-1/4" deep.  
Approximate volume is 10 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and fully welded on all 4 sides.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Two full size, stainless steel paddle latches are recessed into the hull of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with 2 gas pressure shocks for one-hand opening of the box.
- Lid is attached to the hull of the box with three 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Fixed tray, 45" x 6", welded into the back wall of the box.
- Tray comes with 3 fixed dividers.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Black boxes go through a five-stage zinc phosphate wash and are finished with a black super durable polyester powder coat.
- Attaching hardware is included.
- Weight: 69 lbs.



## **M45-1NMAW SINGLE LID ALUMINUM, CHEST TYPE, BOX SPECIFICATIONS** **WHITE DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

46-3/16" overall length, 20" wide, 19-1/4" deep.  
Approximate volume is 10 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and fully welded on all 4 sides.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Two full size, stainless steel paddle latches are recessed into the hull of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with 2 gas pressure shocks for one-hand opening of the box.
- Lid is attached to the hull of the box with three 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Fixed tray, 45" x 6", welded into the back wall of the box.
- Tray comes with 3 fixed dividers.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- White boxes go through a five-stage zinc phosphate wash and are finished with a white super durable polyester powder coat.
- Attaching hardware is included.
- Weight: 69 lbs.



## **M45-1NMB SINGLE LID CHEST TYPE BOX SPECIFICATIONS** **BLACK POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

45-3/4" overall length, 20" wide, 19-3/16" deep.  
Approximate volume is 10 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and fully welded on all 4 sides.
- Lid is constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Full size, stainless steel paddle latches are recessed into the hull of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Fixed tray, 45" x 6", welded into the back wall of the box.
- Tray comes with 3 fixed dividers.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage zinc phosphate wash, anti-corrosion protection, and is finished with a black super durable polyester powder coat.
- Attaching hardware is included.
- Weight: 131 lbs.



## **M54-1 SINGLE LID BOX SPECIFICATIONS** **WHITE POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

62" overall length, 16" wide, 16-11/16" deep.  
Approximate volume is 8.25 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and welded in with full arc welds.
- Lid is constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- 10 gauge mounting brackets 12-5/8" x 4-1/4" welded to each end of the box.
- Welds are full arc welds, no spot welds.
- Full size, stainless steel paddle latches are recessed into the hull of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Fixed tray, 54" x 4", welded into the back wall of the box.
- Tray comes with 3 fixed dividers.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage zinc phosphate wash, anti-corrosion protection, and is finished with a white super durable polyester powder coat.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 129 lbs.



## **M54-1B SINGLE LID BOX SPECIFICATIONS** **BLACK POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

62" overall length, 16" wide, 16-11/16" deep.  
Approximate volume is 8.25 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and welded in with full arc welds.
- Lid is constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- 10 gauge mounting brackets 12-5/8" x 4-1/4" welded to each end of the box.
- Welds are full arc welds, no spot welds.
- Full size, stainless steel paddle latches are recessed into the hull of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Fixed tray, 54" x 4", welded into the back wall of the box.
- Tray comes with 3 fixed dividers.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage zinc phosphate wash, anti-corrosion protection, and is finished with a black super durable polyester powder coat.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 129 lbs.



## **M54-1NM SINGLE LID CHEST TYPE BOX SPECIFICATIONS** **WHITE POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

54-1/4" overall length, 16" wide, 16-11/16" deep.  
Approximate volume is 8.25 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and fully welded on all 4 sides.
- Lid is constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the hull of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Fixed tray, 54" x 4", welded into the back wall of the box.
- Tray comes with 3 fixed dividers.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage zinc phosphate wash, anti-corrosion protection, and is finished with a white super durable polyester powder coat.
- Attaching hardware is included.
- Weight: 123 lbs.



## **M54-1NMB SINGLE LID CHEST TYPE BOX SPECIFICATIONS** **BLACK POWER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

54-1/4" overall length, 16" wide, 16-11/16" deep.  
Approximate volume is 8.25 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and fully welded on all 4 sides.
- Lid is constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the hull of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Fixed tray, 54" x 4", welded into the back wall of the box.
- Tray comes with 3 fixed dividers.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage zinc phosphate wash, anti-corrosion protection, and is finished with a black super durable polyester powder coat.
- Attaching hardware is included.
- Weight: 123 lbs.



## **M54-2 DOUBLE LID BOX SPECIFICATIONS** **WHITE POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

62" overall length, 16" wide, 16-11/16" deep.  
Approximate volume is 8.25 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and welded in with full arc welds.
- Lids are constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- 10 gauge mounting brackets 12-5/8" x 4-1/4" welded to each end of the box.
- Welds are full arc welds, no spot welds.
- Full size, stainless steel paddle latches are recessed into the hull of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Spring type lid props assist in the opening and closing of the lids.
- Each lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Fixed tray, 54" x 4", welded into the back wall of the box.
- Tray comes with 3 fixed dividers.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage zinc phosphate wash, anti-corrosion protection, and is finished with a white super durable polyester powder coat.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 132 lbs.





## **M54-2B DOUBLE LID CHEST TYPE BOX SPECIFICATIONS** **BLACK POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

62" overall length, 16" wide, 16-11/16" deep.  
Approximate volume is 8.25 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and welded in with full arc welds.
- Lids are constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- 10 gauge mounting brackets 12-5/8" x 4-1/4" welded to each end of the box.
- Welds are full arc welds, no spot welds.
- Full size, stainless steel paddle latches are recessed into the hull of the box.
- Two keys are furnished per box.
- Spring type lid props assist in the opening and closing of the lids. Each lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Fixed tray, 54" x 4", welded into the back wall of the box. Tray comes with 3 fixed dividers.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage zinc phosphate wash, anti-corrosion protection, and is finished with a black super durable polyester powder coat.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the bed rail.
- Weight: 132 lbs.



## **M54-2NM DOUBLE LID CHEST TYPE BOX SPECIFICATIONS** **WHITE POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

54-1/4" overall length, 16" wide, 16-11/16" deep.  
Approximate volume is 8.25 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and fully welded on all 4 sides.
- Lids are constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Full size, stainless steel paddle latches are recessed into the hull of the box.
- Two keys are furnished per box.
- Spring type lid props assist in the opening and closing of the lids.
- Each lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Fixed tray, 54" x 4", welded into the back wall of the box.
- Tray comes with 3 fixed dividers.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage zinc phosphate wash, anti-corrosion protection, and is finished with a white super durable polyester powder coat.
- Attaching hardware is included.
- Weight: 126 lbs.



## **M54-2NMB DOUBLE LID CHEST TYPE BOX SPECIFICATIONS** **BLACK POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

54-1/4" overall length, 16" wide, 16-11/16" deep.  
Approximate volume is 8.25 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and fully welded on all 4 sides.
- Lids are constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Full size, stainless steel paddle latches are recessed into the hull of the box.
- Two keys are furnished per box.
- Spring type lid props assist in the opening and closing of the lids.
- Each lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Fixed tray, 54" x 4", welded into the back wall of the box.
- Tray comes with 3 fixed dividers.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage zinc phosphate wash, anti-corrosion protection, and is finished with a black super durable polyester powder coat.
- Attaching hardware is included.
- Weight: 126 lbs.



**M54U-1NM SINGLE LID CHEST TYPE BOX SPECIFICATIONS**  
**LOWER BOX FRONT DIAGONALLY TAPERED**  
**WHITE POWDER FINISH**

**BOX DIMENSIONS AS FOLLOWS:**

54-3/4" overall length, 20" wide, 19" deep.  
Approximate volume is 11.25 cubic feet.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and fully welded on all 4 sides.
- Lid is constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Full size, stainless steel paddle latches are recessed into the hull of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Offset in the rear of the lid is to allow flush mounting to the front of the pickup box.
- Lower front face of the box is diagonally tapered to accommodate wheel wells on short bed trucks.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage zinc phosphate wash, anti-corrosion protection, and is finished with a white super durable polyester powder coat.
- Attaching hardware is included.
- Weight: 133 lbs.



**M54U-1NMA SINGLE LID ALUMINUM, CHEST TYPE, BOX SPECIFICATIONS**  
**LOWER BOX FRONT DIAGONALLY TAPERED**  
**BRIGHT DIAMOND TREADPLATE**

**BOX DIMENSIONS AS FOLLOWS:**

55-3/16" overall length, 20" wide, 19-1/8" deep.  
Approximate volume is 11.25 cubic feet.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 bright diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and fully welded on all 4 sides.
- Lid is constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Two full size, stainless steel paddle latches are recessed into the hull of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with 2 gas pressure shocks for one-hand opening of the box.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Offset in the rear of the lid allows flush mounting to the front of the pickup box.
- Lower front face of the box is diagonally tapered to accommodate wheel wells on short bed trucks.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Attaching hardware is included.
- Weight: 67 lbs.



**M54U-1NMAB SINGLE LID ALUMINUM, CHEST TYPE, BOX SPECIFICATIONS**  
**LOWER BOX FRONT DIAGONALLY TAPERED**  
**BLACK POWDER FINISH**

**BOX DIMENSIONS AS FOLLOWS:**

55-3/16" overall length, 20" wide, 19-1/8" deep.  
Approximate volume is 11.25 cubic feet.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and fully welded on all 4 sides.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Two full size, stainless steel paddle latches are recessed into the hull of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with 2 gas pressure shocks for one-hand opening of the box.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Offset in the rear of the lid allows flush mounting to the front of the pickup box.
- Lower front face of the box is diagonally tapered to accommodate wheel wells on short bed trucks.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Black boxes go through a five-stage zinc phosphate wash and are finished with a black super durable polyester powder coat.
- Attaching hardware is included.
- Weight: 69 lbs.



**M54U-1NMAW SINGLE LID ALUMINUM, CHEST TYPE, BOX SPECIFICATIONS**  
**LOWER BOX FRONT DIAGONALLY TAPERED**  
**WHITE POWDER FINISH**

**BOX DIMENSIONS AS FOLLOWS:**

55-3/16" overall length, 20" wide, 19-1/8" deep.  
Approximate volume is 11.25 cubic feet.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and fully welded on all 4 sides.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Two full size, stainless steel paddle latches are recessed into the hull of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with 2 gas pressure shocks for one-hand opening of the box.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Offset in the rear of the lid allows flush mounting to the front of the pickup box.
- Lower front face of the box is diagonally tapered to accommodate wheel wells on short bed trucks.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- White boxes go through a five-stage zinc phosphate wash and are finished with a white super durable polyester powder coat.
- Attaching hardware is included.
- Weight: 69 lbs.



**M54U-1NMB SINGLE LID CHEST TYPE BOX SPECIFICATIONS**  
**LOWER BOX FRONT DIAGONALLY TAPERED**  
**BLACK POWDER FINISH**

**BOX DIMENSIONS AS FOLLOWS:**

54-3/4" overall length, 20" wide, 19-1/16" deep.  
Approximate volume is 11.25 cubic feet.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and fully welded on all 4 sides.
- Lid is constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Full size, stainless steel paddle latches are recessed into the hull of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Offset in the rear of the lid is to allow flush mounting to the front of the pickup box.
- Lower front face of the box is diagonally tapered to accommodate wheel wells on short bed trucks.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage zinc phosphate wash, anti-corrosion protection, and is finished with a black super durable polyester powder coat.
- Attaching hardware is included.
- Weight: 133 lbs.





**M58U-1NM SINGLE LID CHEST TYPE BOX SPECIFICATIONS**  
**LOWER BOX FRONT DIAGONALLY TAPERED**  
**WHITE POWDER FINISH**

**BOX DIMENSIONS AS FOLLOWS:**

58-3/4" overall length, 20" wide, 19-1/16" deep.  
Approximate volume is 12.25 cubic feet.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and fully welded on all 4 sides.
- Lid is constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Full size, stainless steel paddle latches are recessed into the hull of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Offset in the rear of the lid is to allow flush mounting to the front of the pickup box.
- Lower front face of the box is diagonally tapered to accommodate wheel wells on short bed trucks.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage zinc phosphate wash, anti-corrosion protection, and is finished with a white super durable polyester powder coat.
- Mounting hardware and mounting instructions included.
- Weight: 144 lbs.



**M58U-1NMA SINGLE LID, CHEST TYPE, ALUMINUM BOX SPECIFICATIONS**  
**LOWER BOX FRONT DIAGONALLY TAPERED**  
**BRIGHT DIAMOND TREADPLATE**

**BOX DIMENSIONS AS FOLLOWS:**

59-3/16" overall length, 20" wide, 19-1/8" deep.  
Approximate volume is 12.25 cubic feet.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 bright diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and fully welded on all 4 sides.
- Lid is constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Two full size stainless steel paddle latches are recessed into the hull of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with two gas shocks for one-hand opening of the box.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Offset in the rear of the lid allows flush mounting to the front of the pickup box.
- Lower front face of the box is diagonally tapered to accommodate wheel wells on short bed trucks.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware and mounting instructions included.
- Weight: 71 lbs.



**M58U-1NMAB SINGLE LID ALUMINUM, CHEST TYPE, BOX SPECIFICATIONS**  
**LOWER BOX FRONT DIAGONALLY TAPERED**  
**BLACK DIAMOND TREADPLATE**

**BOX DIMENSIONS AS FOLLOWS:**

59-3/16" overall length, 20" wide, 19-1/8" deep.  
Approximate volume is 12.25 cubic feet.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and fully welded on all 4 sides.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Two full size, stainless steel paddle latches are recessed into the hull of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with 2 gas pressure shocks for one-hand opening of the box.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Offset in the rear of the lid allows flush mounting to the front of the pickup box.
- Lower front face of the box is diagonally tapered to accommodate wheel wells on- short bed trucks.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Black boxes go through a five-stage zinc phosphate wash and are finished with a black super durable polyester powder coat.
- Attaching hardware is included.
- Weight: 73 lbs.



**M58U-1NMAW SINGLE LID ALUMINUM, CHEST TYPE, BOX SPECIFICATIONS**  
**LOWER BOX FRONT DIAGONALLY TAPERED**  
**WHITE DIAMOND TREADPLATE**

**BOX DIMENSIONS AS FOLLOWS:**

59-3/16" overall length, 20" wide, 19-1/8" deep.  
Approximate volume is 12.25 cubic feet.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and fully welded on all 4 sides.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Two full size, stainless steel paddle latches are recessed into the hull of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with 2 gas pressure shocks for one-hand opening of the box.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Offset in the rear of the lid allows flush mounting to the front of the pickup box.
- Lower front face of the box is diagonally tapered to accommodate wheel wells on- short bed trucks.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- White boxes go through a five-stage zinc phosphate wash and are finished with a white super durable polyester powder coat.
- Attaching hardware is included.
- Weight: 73 lbs.



**M58U-1NMB SINGLE LID CHEST TYPE BOX SPECIFICATIONS**  
**LOWER BOX FRONT DIAGONALLY TAPERED**  
**BLACK POWDER FINISH**

**BOX DIMENSIONS AS FOLLOWS:**

58-3/4" overall length, 20" wide, 19-1/16" deep.  
Approximate volume is 12.25 cubic feet.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and fully welded on all 4 sides.
- Lid is constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Full size, stainless steel paddle latches are recessed into the hull of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Offset in the rear of the lid is to allow flush mounting to the front of the pickup box.
- Lower front face of the box is diagonally tapered to accommodate wheel wells on short bed trucks.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage zinc phosphate wash, anti-corrosion protection, and is finished with a black super durable polyester powder coat.
- Attaching hardware is included.
- Weight: 144 lbs.



## **M60-1 SINGLE LID BOX SPECIFICATIONS** **WHITE POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

70-1/2" overall length, 20" wide, 19-3/16" deep.  
Approximate volume is 13.3 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and welded in with full arc welds.
- Lid is constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- 10 gauge mounting brackets 15-1/2" x 4-1/2" welded to each end of the box.
- Welds are full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the hull of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Fixed tray, 60" x 6", welded into the back wall of the box.
- Tray comes with 3 fixed dividers.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage zinc phosphate wash, anti-corrosion protection, and is finished with a white super durable polyester powder coat.
- Mounting hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail, mounting instructions included.
- Weight: 178 lbs.



## **M60-1B SINGLE LID BOX SPECIFICATIONS** **BLACK POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

70-1/2" overall length, 20" wide, 19-3/16" deep.  
Approximate volume is 13.3 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and welded in with full arc welds.
- Lid is constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- 10 gauge mounting brackets 15-1/2" x 4-1/2" welded to each end of the box.
- Welds are full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the hull of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Fixed tray, 60" x 6", welded into the back wall of the box.
- Tray comes with 3 fixed dividers.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage zinc phosphate wash, anti-corrosion protection, and is finished with a black super durable polyester powder coat.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the bed rail.
- Weight: 178 lbs.



## **M60-1NM SINGLE LID CHEST TYPE BOX SPECIFICATIONS** **WHITE POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

60-3/4" overall length, 20" wide, 19-3/16" deep.  
Approximate volume is 13.3 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and fully welded on all 4 sides.
- Lid is constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the hull of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Fixed tray, 60" x 6", welded into the back wall of the box.
- Tray comes with 3 fixed dividers.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage zinc phosphate wash, anti-corrosion protection, and is finished with a white super durable polyester powder coat.
- Mounting hardware and mounting instructions included.
- Weight: 168 lbs.





## **M60-1NMB SINGLE LID CHEST TYPE BOX SPECIFICATIONS** **BLACK POWER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

60-3/4" overall length, 20" wide, 19-3/16" deep.  
Approximate volume is 13.3 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and fully welded on all 4 sides.
- Lid is constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the hull of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Fixed tray, 60" x 6", welded into the back wall of the box.
- Tray comes with 3 fixed dividers.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage zinc phosphate wash, anti-corrosion protection, and is finished with a black super durable polyester powder coat.
- Attaching hardware is included.
- Weight: 168 lbs.



## **M60-2 DOUBLE LID CHEST TYPE BOX SPECIFICATIONS** **WHITE POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

70-1/2" overall length, 20" wide, 19-3/16" deep.  
Approximate volume is 13.3 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and welded in with full arc welds.
- Lids are constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- 10 gauge mounting brackets 15-1/2" x 4-1/2" welded to each end of the box.
- Welds are full arc welds, no spot welds.
- Full size, stainless steel paddle latches are recessed into the hull of the box, and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- A spring type lid prop assists in the opening and closing of each lid.
- Each lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Fixed tray, 60" x 6", welded into the back wall of the box.
- Tray comes with 3 fixed dividers.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage zinc phosphate wash, anti-corrosion protection, and is finished with a white super durable polyester powder coat.
- Mounting hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail, mounting instructions included.
- Weight: 180 lbs.



## **M60-2B DOUBLE LID CHEST TYPE BOX SPECIFICATIONS** **BLACK POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

70-1/2" overall length, 20" wide, 19-3/16" deep.  
Approximate volume is 13.3 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and welded in with full arc welds.
- Lids are constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- 10 gauge mounting brackets 15-1/2" x 4-1/2" welded to each end of the box.
- Welds are full arc welds, no spot welds.
- Full size, stainless steel paddle latches are recessed into the hull of the box, and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Spring type lid props assist in the opening and closing of the lids.
- Each lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Fixed tray, 60" x 6", welded into the back wall of the box.
- Tray comes with 3 fixed dividers.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage zinc phosphate wash, anti-corrosion protection, and is finished with a black super durable polyester powder coat.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 180 lbs.



## **M60-2NM DOUBLE LID CHEST TYPE BOX SPECIFICATIONS** **WHITE POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

60-3/4" overall length, 20" wide, 19-3/16" deep.  
Approximate volume is 13.3 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and fully welded on all 4 sides.
- Lids are constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Full size, stainless steel paddle latches are recessed into the hull of the box.
- Two keys are furnished per box.
- A spring type lid prop assists in the opening and closing of each lid.
- Each lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Fixed tray, 60" x 6", welded into the back wall of the box.
- Tray comes with 3 fixed dividers.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage zinc phosphate wash, anti-corrosion protection, and is finished with a white super durable polyester powder coat.
- Mounting hardware and mounting instructions included.
- Weight: 171 lbs.



## **M60-2NMB DOUBLE LID CHEST TYPE BOX SPECIFICATIONS** **BLACK POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

60-3/4" overall length, 20" wide, 19-3/16" deep.  
Approximate volume is 13.3 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and fully welded on all 4 sides.
- Lids are constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Full size, stainless steel paddle latches are recessed into the hull of the box.
- Two keys are furnished per box.
- Spring type lid props assist in the opening and closing of the lids.
- Each lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Fixed tray, 60" x 6", welded into the back wall of the box.
- Tray comes with 3 fixed dividers.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage zinc phosphate wash, anti-corrosion protection, and is finished with a black super durable polyester powder coat.
- Attaching hardware is included.
- Weight: 171 lbs.



## **M60FW-1NM SINGLE LID CHEST TYPE BOX SPECIFICATIONS** **WHITE POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

60-3/4" overall length, 23" wide, 19-3/16" deep.  
Approximate volume is 15.3 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and fully welded on all 4 sides.
- Lid is constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Full size, stainless steel paddle latches are recessed into the hull of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Offset in the rear of the lid allows flush mounting to the front of the pickup box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage zinc phosphate wash, anti-corrosion protection, and is finished with a white super durable polyester powder coat.
- Mounting hardware and mounting instructions included.
- Weight: 164 lbs.



## **M60FW-1NMA SINGLE LID ALUMINUM, CHEST TYPE, BOX SPECIFICATIONS** **BRIGHT DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

61-3/16" overall length, 23" wide, 19-1/4" deep.  
Approximate volume is 15.3 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 bright diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and fully welded on all 4 sides.
- Lid is constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Two full size stainless steel paddle latches are recessed into the hull of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with two gas shocks for one-hand opening of the box.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Offset in the rear of the lid allows flush mounting to the front of the pickup box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware and mounting instructions included.
- Weight: 86 lbs.



## **M60FW-1NMAB SINGLE LID ALUMINUM, CHEST TYPE, BOX SPECIFICATIONS** **BLACK DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

61-3/16" overall length, 23" wide, 19-1/4" deep.  
Approximate volume is 15.3 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and fully welded on all 4 sides.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Two full size, stainless steel paddle latches are recessed into the hull of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with 2 gas pressure shocks for one-hand opening of the box.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Offset in the rear of the lid allows flush mounting to the front of the pickup box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Black boxes go through a five-stage zinc phosphate wash and are finished with a black super durable polyester powder coat.
- Attaching hardware is included.
- Weight: 88 lbs.





## **M60FW-1NMAW SINGLE LID ALUMINUM, CHEST TYPE, BOX SPECIFICATIONS** **WHITE DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

61-3/16" overall length, 23" wide, 19-1/4" deep.  
Approximate volume is 15.3 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and fully welded on all 4 sides.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Two full size, stainless steel paddle latches are recessed into the hull of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with 2 gas pressure shocks for one-hand opening of the box.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Offset in the rear of the lid allows flush mounting to the front of the pickup box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- White boxes go through a five-stage zinc phosphate wash and are finished with a white super durable polyester powder coat.
- Attaching hardware is included.
- Weight: 88 lbs.



## **M60FW-1NMB SINGLE LID CHEST TYPE BOX SPECIFICATIONS** **BLACK POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

60-3/4" overall length, 23" wide, 19-3/16" deep.  
Approximate volume is 15.3 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and fully welded on all 4 sides.
- Lid is constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Full size, stainless steel paddle latches are recessed into the hull of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Offset in the rear of the lid allows flush mounting to the front of the pickup box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage zinc phosphate wash, anti-corrosion protection, and is finished with a black super durable polyester powder coat.
- Attaching hardware is included.
- Weight: 164 lbs.



**M60SB-1NM SINGLE LID CHEST TYPE BOX SPECIFICATIONS**  
**END OFFSETS FOR INSTALLATION OVER WHEEL WELL**  
**WHITE POWDER FINISH**

**BOX DIMENSIONS AS FOLLOWS:**

60-3/4" overall length, 23" wide, 19-3/16" deep.  
Approximate volume is 13 cubic feet.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and fully welded on all 4 sides.
- Lid is constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Full size, stainless steel paddle latches are recessed into the hull of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Offset in the rear of the lid to allow flush mounting to the front of the pickup box.
- 6" x 9-1/2" recess in the lower ends of the box to clear the wheel wells in short bed trucks.
- Small part tray 23" long, 6" wide, and 4" deep in each end of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage zinc phosphate wash, anti-corrosion protection, and is finished with a white super durable polyester powder coat.
- Mounting hardware and mounting instructions included.
- Weight: 172 lbs.



**M60SB-1NMA SINGLE LID ALUMINUM, CHEST TYPE, BOX SPECIFICATIONS**  
**END OFFSETS FOR INSTALLATION OVER WHEEL WELL**  
**BRIGHT DIAMOND TREADPLATE**

**BOX DIMENSIONS AS FOLLOWS:**

61-3/16" overall length, 23" wide, 19-1/4" deep.  
Approximate volume is 13 cubic feet.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 bright diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and fully welded on all 4 sides.
- Lid is constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Two full size stainless steel paddle latches are recessed into the hull of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with two gas shocks for one-hand opening of the box.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Offset in the rear of the lid to allow flush mounting to the front of the pickup box.
- 6" x 9-1/2" recess in the lower ends of the box to clear the wheel wells in short bed trucks.
- Small part tray 23" long, 6" wide, and 4" deep in each end of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware and mounting instructions included.
- Weight: 82 lbs.



**M60SB-1NMAB SINGLE LID ALUMINUM, CHEST TYPE, BOX SPECIFICATIONS**  
**END OFFSETS FOR INSTALLATION OVER WHEEL WELL**  
**BLACK DIAMOND TREADPLATE**

**BOX DIMENSIONS AS FOLLOWS:**

61-3/16" overall length, 23" wide, 19-1/4" deep.  
Approximate volume is 13 cubic feet.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and fully welded on all 4 sides.
- Lid is constructed of .080 diamond treadplate aluminum with inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Two full size, stainless steel paddle latches are recessed into the hull of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with 2 gas pressure shocks for one hand opening of the box.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Offset in the rear of the lid to allow flush mounting to the front of the pickup box.
- 6" x 9-1/2" recess in the lower ends of the box to clear the wheel wells in short bed trucks.
- Small part tray 23" long, 6" wide, and 4" deep in each end of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Black boxes go through a five-stage zinc phosphate wash, and are finished with a black super durable polyester powder coat.
- Attaching hardware is included.
- Weight: 84 lbs.



**M60SB-1NMAW SINGLE LID ALUMINUM, CHEST TYPE, BOX SPECIFICATIONS**  
**END OFFSETS FOR INSTALLATION OVER WHEEL WELL**  
**WHITE DIAMOND TREADPLATE**

**BOX DIMENSIONS AS FOLLOWS:**

61-3/16" overall length, 23" wide, 19-1/4" deep.  
Approximate volume is 13 cubic feet.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and fully welded on all 4 sides.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Two full size, stainless steel paddle latches are recessed into the hull of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with 2 gas pressure shocks for one-hand opening of the box.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Offset in the rear of the lid to allow flush mounting to the front of the pickup box.
- 6" x 9-1/2" recess in the lower ends of the box to clear the wheel wells in short bed trucks.
- Small part tray 23" long, 6" wide, and 4" deep in each end of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- White boxes go through a five-stage zinc phosphate wash and are finished with a white super durable polyester powder coat.
- Attaching hardware is included.
- Weight: 84 lbs.



**M60SB-1NMB SINGLE LID CHEST TYPE BOX SPECIFICATIONS**  
**END OFFSETS FOR INSTALLATION OVER WHEEL WELL**  
**BLACK POWDER FINISH**

**BOX DIMENSIONS AS FOLLOWS:**

60-3/4" overall length, 23" wide, 19-3/16" deep.  
Approximate volume is 13 cubic feet.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and fully welded on all 4 sides.
- Lid is constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the hull of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Offset in the rear of the lid to allow flush mounting to the front of the pickup box.
- 6" x 9-1/2" recess in the lower ends of the box to clear the wheel wells in short bed trucks.
- Small part tray 23" long, 6" wide, and 4" deep in each end of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage zinc phosphate wash, anti-corrosion protection, and is finished with a black super durable polyester powder coat.
- Attaching hardware is included.
- Weight: 172 lbs.



## **MTB60-1NM SINGLE LID CHEST TYPE BOX SPECIFICATIONS** **WHITE POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

60-3/4" overall length, 23" wide, 24-3/16" deep.  
Approximate volume is 19.3 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and fully welded on all 4 sides.
- Lid is constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Full size, stainless steel paddle latches are recessed into the hull of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Offset in the rear of the lid allows flush mounting to the front of the pickup box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage zinc phosphate wash, anti-corrosion protection, and is finished with a white super durable polyester powder coat.
- Attaching hardware is included.
- Weight: 182 lbs.





## **MTB60-1NMA SINGLE LID ALUMINUM, CHEST TYPE, BOX SPECIFICATIONS** **BRIGHT DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

61-3/16" overall length, 23" wide, 24-1/4" deep.  
Approximate volume is 19.3 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 bright diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and fully welded on all 4 sides.
- Lid is constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Two full size, stainless steel paddle latches are recessed into the hull of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with 2 gas pressure shocks for one-hand opening of the box.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Offset in the rear of the lid allows flush mounting to the front of the pickup box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Attaching hardware is included.
- Weight: 91 lbs.



## **MTB60-1NMAB SINGLE LID ALUMINUM, CHEST TYPE, BOX SPECIFICATIONS** **BLACK DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

61-3/16" overall length, 23" wide, 24-1/4" deep.  
Approximate volume is 13 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and fully welded on all 4 sides.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Two full size, stainless steel paddle latches are recessed into the hull of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with 2 gas pressure shocks for one-hand opening of the box.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Black boxes go through a five-stage zinc phosphate wash and are finished with a black super durable polyester powder coat.
- Attaching hardware is included.
- Weight: 93 lbs.



## **MTB60-1NMAW SINGLE LID ALUMINUM, CHEST TYPE, BOX SPECIFICATIONS** **WHITE DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

61-3/16" overall length, 23" wide, 24-1/4" deep.  
Approximate volume is 19.3 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and fully welded on all 4 sides.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Two full size, stainless steel paddle latches are recessed into the hull of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with 2 gas pressure shocks for one-hand opening of the box.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Offset in the rear of the lid allows flush mounting to the front of the pickup box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- White boxes go through a five-stage zinc phosphate wash and are finished with a white super durable polyester powder coat.
- Attaching hardware is included.
- Weight: 93 lbs.



## **MTB60-1NMB SINGLE LID CHEST TYPE BOX SPECIFICATIONS** **BLACK POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

60-3/4" overall length, 23" wide, 24-3/16" deep.  
Approximate volume is 19.3 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and fully welded on all 4 sides.
- Lid is constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Full size, stainless steel paddle latches are recessed into the hull of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Offset in the rear of the lid allows flush mounting to the front of the pickup box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage zinc phosphate wash, anti-corrosion protection, and is finished with a black super durable polyester powder coat.
- Attaching hardware is included.
- Weight: 182 lbs.



## **RG10 REAR GRILLE SPECIFICATIONS** **WHITE POWDER FINISH**

### **REAR GRILL DIMENSIONS AS FOLLOWS:**

68" overall length, 9-1/4" wide including brackets, and 27-3/4" tall.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a white super durable polyester powder coat.
- End plates are 1/2" x 3" cold rolled steel flatbar.
- Upper crossbar is 2" x 2" square tubing with .065 wall.
- Welds are full arc welds, no spot welds.
- Mounting brackets are of 3/16" steel construction.
- Mounting hardware and instructions are included.
- Weight: 47 lbs.



## **RG10B REAR GRILLE SPECIFICATIONS** **BLACK POWDER FINISH**

### **REAR GRILL DIMENSIONS AS FOLLOWS:**

68" overall length, 9-1/4" wide including brackets, and 27-3/4" tall.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a black super durable polyester powder coat.
- End plates are 1/2" x 3" cold rolled steel flatbar.
- Upper crossbar is 2" x 2" square tubing with .065 wall.
- Welds are full arc welds, no spot welds.
- Mounting brackets are of 3/16" steel construction.
- Mounting hardware and instructions are included.
- Weight: 47 lbs.



## **RG11 REAR GRILLE SPECIFICATIONS** **WHITE POWDER FINISH**

### **REAR GRILL DIMENSIONS AS FOLLOWS:**

68" overall length, 9-1/4" wide including brackets, and 29-1/4" tall.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a white super durable polyester powder coat.
- End plates are 1/2" x 3" cold rolled steel flatbar.
- Upper crossbar is 2" x 2" square tubing with .065 wall.
- Welds are full arc welds, no spot welds.
- Mounting brackets are of 3/16" steel construction.
- Mounting hardware and instructions are included.
- Weight: 47 lbs.



## **RG11B REAR GRILLE SPECIFICATIONS** **BLACK POWDER FINISH**

### **REAR GRILL DIMENSIONS AS FOLLOWS:**

68" overall length, 9-1/4" wide including brackets, and 29-1/4" tall.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a black super durable polyester powder coat.
- End plates are 1/2" x 3" cold rolled steel flatbar.
- Upper crossbar is 2" x 2" square tubing with .065 wall.
- Welds are full arc welds, no spot welds.
- Mounting brackets are of 3/16" steel construction.
- Mounting hardware and instructions are included.
- Weight: 47 lbs.





## **RG15 REAR GRILLE SPECIFICATIONS** **WHITE POWDER FINISH**

### **REAR GRILL DIMENSIONS AS FOLLOWS:**

71" overall length, 9-1/4" wide including brackets, and 26-1/8" tall.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a white super durable polyester powder coat.
- End plates are 1/2" x 3" cold rolled steel flatbar.
- Upper crossbar is 2" x 2" square tubing with .065 wall.
- Welds are full arc welds, no spot welds.
- Mounting brackets are of 3/16" steel construction.
- Mounting hardware and instructions are included.
- Weight: 47 lbs.



## **RG15B REAR GRILLE SPECIFICATIONS** **BLACK POWDER FINISH**

### **REAR GRILL DIMENSIONS AS FOLLOWS:**

71" overall length, 9-1/4" wide including brackets, and 26-1/8" tall.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a black super durable polyester powder coat.
- End plates are 1/2" x 3" cold rolled steel flatbar.
- Upper crossbar is 2" x 2" square tubing with .065 wall.
- Welds are full arc welds, no spot welds.
- Mounting brackets are of 3/16" steel construction.
- Mounting hardware and instructions are included.
- Weight: 47 lbs.



## **ST56U DOUBLE LID “SLANT TOP” CROSSBOX SPECIFICATIONS** **WHITE POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

62-1/2" overall length, 20" wide, 17-7/16" deep.  
Approximate volume is 11 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and welded in with full arc welds.
- Lids are constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Each lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- A full size, stainless steel paddle latch is recessed into each lid.
- A spring type lid prop assists in the opening and closing of each lid.
- 2 keys are furnished per box.
- Sliding tray 19-1/2" x 14-3/4" x 2-3/8" with white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Box is equipped with tray stops to keep tray centered while not being used.
- Ribbed D-Bulb seal is installed in each lid to seal against the flange around the box opening.
- Box goes through a five-stage zinc phosphate wash, anti-corrosion protection, and is finished with a white super durable polyester powder coat.
- Mounting hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail, mounting instructions included.
- Weight: 152 lbs.



## **ST56UB DOUBLE LID “SLANT TOP” CROSSBOX SPECIFICATIONS** **BLACK POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

62-1/2" overall length, 20" wide, 17-7/16" deep.  
Approximate volume is 11 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and welded in with full arc welds.
- Lids are constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Each lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- A full size stainless steel paddle latch is recessed into each lid.
- Spring type lid props assist in the opening and closing of each lid.
- 2 keys are furnished per box.
- Sliding tray 19-1/2" x 14-3/4" with white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Box is equipped with tray stops to keep tray centered while not being used.
- Ribbed D-Bulb seal is installed in each lid to seal against the flange around the box opening.
- Box goes through a five-stage zinc phosphate wash, anti-corrosion protection, and is finished with a white super durable polyester powder coat.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 152 lbs.



## **ST63 DOUBLE LID "SLANT TOP" CROSSBOX SPECIFICATIONS** **WHITE POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

70" overall length, 20" wide, 17-7/16" deep.  
Approximate volume is 12.5 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and welded in with full arc welds.
- Lids are constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Each lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- A full size, stainless steel paddle latch is recessed into each lid.
- 2 keys are furnished per box.
- A spring type lid prop assists in the opening and closing of each lid.
- Sliding tray 29-1/4" x 19-1/4" x 2-3/8" with white super durable polyester powder coat finish.
- Tray comes with 6 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while it is not being used.
- Ribbed D-Bulb seal is installed in each lid to seal against the flange around the box opening.
- Box goes through a five-stage zinc phosphate wash, anti-corrosion protection, and is finished with a white super durable polyester powder coat.
- Mounting hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail, mounting instructions included.
- Weight: 175 lbs.



## **ST63A DOUBLE LID "SLANT TOP" CROSSBOX SPECIFICATIONS** **BRIGHT DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

70-1/8" overall length, 20" wide, 17-7/16" deep.  
Approximate volume is 13 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 bright diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum, and welded in with full arc welds, no spot welds.
- Lids are constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Each lid is attached to the hull of the box with two 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- A full size, stainless steel paddle latch is recessed into each lid.
- Two keys are furnished per box.
- Each lid is equipped with a gas shock for one-hand opening of the box.
- Sliding tray 29-1/4" x 19-1/4" x 2-3/8" with a white super durable polyester powder coat finish.
- Tray comes with 6 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail, mounting instructions included.
- Weight: 88 lbs.



## **ST63AB DOUBLE LID “SLANT TOP” CROSSBOX SPECIFICATIONS** **BLACK DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

70-1/8" overall length, 20" wide, 17-7/16" deep.  
Approximate volume is 13 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 bright diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum, and welded in with full arc welds, no spot welds.
- Lids are constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Each lid is attached to the hull of the box with two 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- A full size, stainless steel paddle latch is recessed into each lid.
- Two keys are furnished per box.
- Each lid is equipped with a gas pressure shock for one-hand opening of the box.
- Sliding tray 29-1/2" x 19-1/2" with a white super durable polyester powder coat finish.
- Tray comes with 6 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Black boxes go through a five-stage zinc phosphate wash and are finished with a black super durable polyester powder coat.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 88 lbs.



## **ST63AW DOUBLE LID "SLANT TOP" CROSSBOX SPECIFICATIONS** **WHITE DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

70-1/8" overall length, 20" wide, 17-7/16" deep.  
Approximate volume is 13 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 bright diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum, and welded in with full arc welds, no spot welds.
- Lids are constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Each lid is attached to the hull of the box with two 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- A full size, stainless steel paddle latch is recessed into each lid.
- Two keys are furnished per box.
- Each lid is equipped with a gas pressure shock for one-hand opening of the box.
- Sliding tray 29-1/2" x 19-1/2" with a white super durable polyester powder coat finish.
- Tray comes with 6 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- White boxes go through a five-stage zinc phosphate wash and are finished with a white super durable polyester powder coat.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 88 lbs.





## **ST63B DOUBLE LID "SLANT TOP" CROSSBOX SPECIFICATIONS** **BLACK POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

70" overall length, 20" wide, 17-7/16" deep.  
Approximate volume is 12.5 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and welded in with full arc welds.
- Lids are constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Each lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- A full size stainless steel paddle latch is recessed into each lid.
- 2 keys are furnished per box.
- Spring type lid props assist in the opening and closing of each lid.
- Sliding tray 29-1/2" x 19-1/2" with white super durable polyester powder coat finish.
- Tray comes with 6 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while it is not being used.
- Ribbed D-Bulb seal is installed in each lid to seal against the flange around the box opening.
- Box goes through a five-stage zinc phosphate wash, anti-corrosion protection, and is finished with a white super durable polyester powder coat.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 175 lbs.



## **ST63W DOUBLE LID WIDE “SLANT TOP” CROSSBOX SPECIFICATIONS** **WHITE POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

70" overall length, 30" wide, 17-7/16" deep.  
Approximate volume is 18.75 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and welded in with full arc welds.
- Lids are constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Each lid is attached to the hull of the box with four 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- A full size, stainless steel paddle latch is recessed into each lid.
- 2 keys are furnished per box.
- A double-spring type lid prop assembly assists in the opening and closing of each lid.
- Sliding tray 29-1/4" x 19-1/4" x 2-3/8" with white super durable polyester powder coat finish.
- Tray comes with 6 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage zinc phosphate wash, anti-corrosion protection, and is finished with a white super durable polyester powder coat.
- Mounting hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail, mounting instructions included.
- Weight: 219 lbs.



## **ST63WB DOUBLE LID WIDE “SLANT TOP” CROSSBOX SPECIFICATIONS** **BLACK POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

70" overall length, 30" wide, 17-7/16" deep.  
Approximate volume is 18.75 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and welded in with full arc welds.
- Lids are constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Each lid is attached to the hull of the box with four 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- A full size stainless steel paddle latch is recessed into each lid.
- 2 keys are furnished per box.
- Spring type lid props assist in the opening and closing of each lid.
- Sliding tray 29-1/2" x 19-1/2" with white super durable polyester powder coat finish.
- Tray comes with 6 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage zinc phosphate wash, anti-corrosion protection, and is finished with a white super durable polyester powder coat.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 219 lbs.



**ST63WD DOUBLE LID WIDE AND DEEP**  
**“SLANT TOP” CROSSBOX SPECIFICATIONS**  
**WHITE POWDER FINISH**

**BOX DIMENSIONS AS FOLLOWS:**

70" overall length, 30" wide, 25-11/16" deep.  
Approximate volume is 26.5 cubic feet.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and welded in with full arc welds.
- Lids are constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Each lid is attached to the hull of the box with four 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- A full size, stainless steel paddle latch is recessed into each lid.
- 2 keys are furnished per box.
- A double-spring type lid prop assembly assists in the opening and closing of each lid.
- Sliding tray 29-1/4" x 19-1/4" x 2-3/8" with white super durable polyester powder coat finish.
- Tray comes with 6 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage zinc phosphate wash, anti-corrosion protection, and is finished with a white super durable polyester powder coat.
- Mounting hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail, mounting instructions included.
- Weight: 248 lbs.



**ST63WDB DOUBLE LID WIDE AND DEEP**  
**“SLANT TOP” CROSSBOX SPECIFICATIONS**  
**BLACK POWDER FINISH**

**BOX DIMENSIONS AS FOLLOWS:**

70" overall length, 30" wide, 25-11/16" deep.  
Approximate volume is 26.5 cubic feet.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and welded in with full arc welds.
- Lids are constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Each lid is attached to the hull of the box with four 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- A full size stainless steel paddle latch is recessed into each lid.
- 2 keys are furnished per box.
- Spring type lid props assist in the opening and closing of each lid.
- Sliding tray 29-1/2" x 19-1/2" with white super durable polyester powder coat finish.
- Tray comes with 6 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage zinc phosphate wash, anti-corrosion protection, and is finished with a white super durable polyester powder coat.
- Attaching hardware is a stainless steel clip system that eliminates drilling through the pickup bed rail.
- Weight: 248 lbs.



## **TC10814 SINGLE LID TOP OPENING SIDE BOX SPECIFICATIONS** **WHITE POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

108-3/4" overall length, 14-1/2" wide, and 7-1/4" overall depth.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a white super durable polyester powder coat.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with four 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Box is slotted on 2" centers for dividers.
- Box comes with 8 adjustable dividers.
- A full size, stainless steel paddle latch is recessed into the hull of the box.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage zinc phosphate wash and is finished with a white super durable polyester powder coat.
- Weight: 165 lbs.



## **TC10814B SINGLE LID TOP OPENING SIDE BOX SPECIFICATIONS** **BLACK POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

108-3/4" overall length, 14-1/2" wide, and 7-1/4" overall depth.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a white super durable polyester powder coat.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with four 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Box is slotted on 2" centers for dividers.
- Box comes with 8 adjustable dividers.
- A full size, stainless steel paddle latch is recessed into the hull of the box.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage zinc phosphate wash and is finished with a black super durable polyester powder coat.
- Weight: 165 lbs.



## **TC10820 SINGLE LID TOP OPENING SIDE BOX SPECIFICATIONS** **WHITE POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

108-3/4" overall length, 20" wide, and 7-1/4" overall depth.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a white super durable polyester powder coat.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with four 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Box is slotted on 2" centers for dividers.
- Box comes with 8 adjustable dividers.
- A full size, stainless steel paddle latch is recessed into the hull of the box.
- Two keys are furnished per box.
- Three spring type lid props assist in the opening and closing of the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening
- Box goes through a five-stage zinc phosphate wash and is finished with a white super durable polyester powder coat..
- Weight: 195 lbs.





## **TC10820B SINGLE LID TOP OPENING SIDE BOX SPECIFICATIONS** **BLACK POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

108-3/4" overall length, 20" wide, and 7-1/4" overall depth.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a white super durable polyester powder coat.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with four 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Box is slotted on 2" centers for dividers.
- Box comes with 8 adjustable dividers.
- A full size, stainless steel paddle latch is recessed into the hull of the box.
- Two keys are furnished per box.
- Three spring type lid props assist in the opening and closing of the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage phosphate wash and is finished with a black super durable polyester powder coat.
- Weight: 195 lbs.



## **TC9614 SINGLE LID TOP OPENING SIDE BOX SPECIFICATIONS** **WHITE POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

96-3/4" overall length, 14-1/2" wide, and 7-1/4" overall depth.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a white super durable polyester powder coat.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with four 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Box is slotted on 2" centers for dividers.
- Box comes with 8 adjustable dividers.
- A full size, stainless steel paddle latch is recessed into the hull of the box.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage zinc phosphate wash and is finished with a white super durable polyester powder coat.
- Weight: 149 lbs.



## **TC9614B SINGLE LID TOP OPENING SIDE BOX SPECIFICATIONS** **BLACK POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

96-3/4" overall length, 14-1/2" wide, and 7-1/4" overall depth.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a white super durable polyester powder coat.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with four 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Box is slotted on 2" centers for dividers.
- Box comes with 8 adjustable dividers.
- A full size, stainless steel paddle latch is recessed into the hull of the box.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage zinc phosphate wash and is finished with a black super durable powder coat.
- Weight: 149 lbs.



## **TC9620 SINGLE LID TOP OPENING SIDE BOX SPECIFICATIONS** **WHITE POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

96-3/4" overall length, 20" wide, and 7-1/4" overall depth.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a white super durable polyester powder coat.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with four 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Box is slotted on 2" centers for dividers.
- Box comes with 8 adjustable dividers.
- A full size, stainless steel paddle latch is recessed into the hull of the box.
- Two keys are furnished per box.
- Three spring type lid props assist in the opening and closing of the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage zinc phosphate wash and is finished with a white super durable powder coat.
- Weight: 176 lbs.



## **TC9620B SINGLE LID TOP OPENING SIDE BOX SPECIFICATIONS** **BLACK POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

96-3/4" overall length, 20" wide, and 7-1/4" overall depth.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a white super durable polyester powder coat.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with four 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Box is slotted on 2" centers for dividers.
- Box comes with 8 adjustable dividers.
- A full size, stainless steel paddle latch is recessed into the hull of the box.
- Two keys are furnished per box.
- Three spring type lid props assist in the opening and closing of the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening
- Box goes through a five-stage zinc phosphate wash and is finished with a black super durable powder coat..
- Weight: 176 lbs.



## **RKI TRAY FLDOUT SPECIFICATIONS** **WHITE POWDER FINISH**

### **TRAY DIMENSIONS AS FOLLOWS:**

28-1/8" overall length, 10-3/8" wide, 2-7/8" deep TRAY SIZE.

29-3/8" overall length, 11-3/8" wide, 10-3/8" deep OVERALL CABINET SIZE.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Two tray fold-out assembly.
- Trays are constructed of 22 gauge cold rolled steel.
- Fold-out assembly comes with 12 dividers.
- Trays go through a five-stage zinc phosphate wash, anti-corrosion protection, and are finished with a white super durable polyester powder coat.
- Weight: 29 lbs.

**TRAY FLDOUT is OPTIONAL for US and UST boxes. TRAY FLDOUT can also be used in some Service Body applications.**



## **RKI TRAY M SPECIFICATIONS** **WHITE POWDER FINISH**

### **TRAY DIMENSIONS AS FOLLOWS:**

22-1/4" overall length, 19-1/4" wide, 2-3/8" deep.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Tray is constructed of 22 gauge cold rolled steel.
- Tray comes with 4 dividers.
- Trays go through a five-stage zinc phosphate wash, anti-corrosion protection, and are finished with a white super durable polyester powder coat.
- Weight: 10 lbs.

### **TRAY M is OPTIONAL for THE FOLLOWING BOXES:**

M54U-1NM, M58U-1NM, M60FW-1NM, M60SB-1NM, MTB60-1NM  
M54U-1NMA, M58U-1NMA, M60FW-1NMA, M60SB-1NMA, MTB60-1NMA



## **RIKI TRAY SLPW SPECIFICATIONS** **WHITE POWDER FINISH**

### **TRAY DIMENSIONS AS FOLLOWS:**

12-3/8" overall length, 11-5/8" wide, 2-3/8" deep.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Tray is constructed of 22 gauge cold rolled steel.
- Tray comes with 2 dividers.
- Trays go through a five-stage zinc phosphate wash, anti-corrosion protection, and are finished with a white super durable polyester powder coat.
- Weight: 4 lbs.

**TRAY SLPW is OPTIONAL for SLPW boxes.**





## **RIKI TRAY ST SPECIFICATIONS** **WHITE POWDER FINISH**

### **TRAY DIMENSIONS AS FOLLOWS:**

29-1/4" overall length, 19-1/4" wide, 2-3/8" deep.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Tray is constructed of 22 gauge cold rolled steel.
- Tray comes with 6 adjustable dividers.
- Trays go through a five-stage zinc phosphate wash, anti-corrosion protection, and are finished with a white super durable polyester powder coat.
- Weight: 13 lbs.

### **TRAY ST STANDARD IN THE FOLLOWING BOXES:**

ST63, ST63W, ST63WD, ST63A  
C63, C63D, C63LP, C63LPD, C63S, C63W, C63WD  
C63A, C63DA, C63LPA, C63LPDA, C63SA, C63WA, C63WDA, C63WSA



## **RIKI TRAY STS SPECIFICATIONS** **WHITE POWDER FINISH**

### **TRAY DIMENSIONS AS FOLLOWS:**

19-1/2" overall length, 8-7/8" wide, 2-3/8" deep.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Tray is constructed of 22 gauge cold rolled steel.
- Tray comes with 4 adjustable dividers.
- Trays go through a five-stage zinc phosphate wash, anti-corrosion protection, and are finished with a white super durable polyester powder coat.
- Weight: 6 lbs.

### **TRAY ST STANDARD IN THE FOLLOWING BOXES:**

50STS, 61STS, 67STS



## **RKI TRAY SW SPECIFICATIONS** **WHITE POWDER FINISH**

### **TRAY DIMENSIONS AS FOLLOWS:**

19-1/2" overall length, 14-3/8" wide, 2-3/8" deep.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Tray is constructed of 22 gauge cold rolled steel.
- Tray comes with 4 dividers.
- Trays go through a five-stage zinc phosphate wash, anti-corrosion protection, and are finished with a white super durable polyester powder coat.
- Weight: 8 lbs.

### **TRAY SW INCLUDED WITH THE FOLLOWING BOXES:**

ST56U  
C56, C56LP, C56LPD  
C56A, C56LPA, C56LPDA, C63LPNA

The TRAY STS can also be used in any of the above RKI 20" wide Truck Boxes to give the user more vertical storage space.

**TRAY SW is OPTIONAL for ALL S-Series truck boxes except low profile models.**



## **RIKI TRAY US SPECIFICATIONS** **WHITE POWDER FINISH**

### **TRAY DIMENSIONS AS FOLLOWS:**

41-1/2" overall length, 8-7/8" wide, 2-3/8" deep.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Tray is constructed of 22 gauge cold rolled steel.
- Tray comes with 8 dividers.
- Trays go through a five-stage zinc phosphate wash, anti-corrosion protection, and are finished with a white super durable polyester powder coat.
- Weight: 12 lbs.

**TRAY US is OPTIONAL for US and UST boxes.**



## **US48A SINGLE DOOR ALUMINUM UPPER SIDE BOX SPECIFICATIONS** **BRIGHT DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

48" overall length, 16-1/2" overall height, and 12-1/2" overall depth.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Box is constructed of .080 bright diamond treadplate aluminum.
- Welds are full arc welds, no spot welds.
- Door is constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Door is attached to the hull of the box with 3 stainless steel pillow block type hinges with self-lubricating bushings and full length 5/16" stainless steel hinge pins.
- Hinges are riveted to the box.
- Top panel of the box forms a drip rail over the door.
- Door has heavy duty machine chain to hold it in the horizontal position.
- Chains detach to swing the door down to 180°.
- A full size stainless steel paddle latch is recessed into the door.
- Door can be closed with the latch in the locked position.
- Two keys are furnished per box.
- Ribbed D-Bulb seal is installed in a recessed channel that runs the full perimeter of the door opening.
- Door has a formed knife edge on all 4 sides that contacts the seal when the door is closed.
- Weight: 47 lbs.



## **US48AB SINGLE DOOR ALUMINUM UPPER SIDE BOX SPECIFICATIONS** **BLACK DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

48" overall length, 16-1/2" overall height, and 12-1/2" overall depth.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Box is constructed of .080 bright diamond treadplate aluminum.
- Welds are full arc welds, no spot welds.
- Door is constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Door is attached to the hull of the box with 3 stainless steel pillow block type hinges with self-lubricating bushings and full length 5/16" stainless steel hinge pins.
- Hinges are riveted to the box.
- Top panel of the box forms a drip rail over the door.
- Door has heavy duty machine chain to hold it in the horizontal position.
- Chains detach to swing the door down to 180°.
- A full size stainless steel paddle latch is recessed into the door.
- Door can be closed with the latch in the locked position.
- Two keys are furnished per box.
- Ribbed D-Bulb seal is installed in a recessed channel that runs the full perimeter of the door opening.
- Box goes through a five-stage zinc phosphate wash and is finished with a black super durable powder coat.
- Door has a formed knife edge on all 4 sides that contacts the seal when the door is closed.
- Weight: 47 lbs.



## **US48AW SINGLE DOOR ALUMINUM UPPER SIDE BOX SPECIFICATIONS** **WHITE DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

48" overall length, 16-1/2" overall height, and 12-1/2" overall depth.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Box is constructed of .080 bright diamond treadplate aluminum.
- Welds are full arc welds, no spot welds.
- Door is constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Door is attached to the hull of the box with 3 stainless steel pillow block type hinges with self-lubricating bushings and full length 5/16" stainless steel hinge pins.
- Hinges are riveted to the box.
- Top panel of the box forms a drip rail over the door.
- Door has heavy duty machine chain to hold it in the horizontal position.
- Chains detach to swing the door down to 180°.
- A full size stainless steel paddle latch is recessed into the door.
- Door can be closed with the latch in the locked position.
- Two keys are furnished per box.
- Ribbed D-Bulb seal is installed in a recessed channel that runs the full perimeter of the door opening.
- Box goes through a five-stage zinc phosphate wash and is finished with a white super durable powder coat.
- Door has a formed knife edge on all 4 sides that contacts the seal when the door is closed.
- Weight: 47 lbs.



## **US48C SINGLE DOOR UPPER SIDE BOX SPECIFICATIONS** **WHITE POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

48" overall length, 16-1/2" overall height, and 12-1/2" overall depth.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a white super durable polyester powder coat.
- Welds are full arc welds, no spot welds.
- Door is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Door is attached to the hull of the box with 3 stainless steel pillow block type hinges with self-lubricating bushings and 5/16" stainless steel hinge pins.
- Hinges are welded to the box.
- Top panel of the box forms a drip rail over the door.
- Door has heavy duty machine chain to hold it in the horizontal position.
- Chain detaches to swing the door down to 180°.
- A full size stainless steel paddle latch is recessed into the door.
- Door can be closed with the latch in the locked position.
- Two keys are furnished per box.
- Ribbed D-Bulb seal is installed in a full perimeter channel around the door opening.
- A knife edge is formed into the door to contact the seal in the door channel.
- Weight: 98 lbs.





## **US48CB SINGLE DOOR UPPER SIDE BOX SPECIFICATIONS** **BLACK POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

48" overall length, 16-1/2" overall height, and 12-1/2" overall depth.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a white super durable polyester powder coat.
- Welds are full arc welds, no spot welds.
- Door is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Door is attached to the hull of the box with 3 stainless steel pillow block type hinges with self-lubricating bushings and 5/16" stainless steel hinge pins.
- Hinges are welded to the box.
- Top panel of the box forms a drip rail over the door.
- Door has heavy duty machine chain to hold it in the horizontal position.
- Chain detaches to swing the door down to 180°.
- A full size stainless steel paddle latch is recessed into the door.
- Door can be closed with the latch in the locked position.
- Two keys are furnished per box.
- Ribbed D-Bulb seal is installed in a full perimeter channel around the door opening.
- A knife edge is formed into the door to contact the seal in the door channel.
- Weight: 98 lbs.



## **US72A TWO DOOR ALUMINUM UPPER SIDE BOX SPECIFICATIONS** **BRIGHT DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

72" overall length, 16-1/2" overall height, and 12-1/2" overall depth.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Box is constructed of .080 bright diamond treadplate aluminum.
- Welds are full arc welds, no spot welds.
- Doors are constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Each door is attached to the hull of the box with 3 stainless steel pillow block type hinges with self-lubricating bushings and full length 5/16" stainless steel hinge pins.
- Hinges are riveted to the box.
- Top panel of the box forms a drip rail over the door.
- Doors have heavy duty machine chain to hold them in the horizontal position.
- Chains detach to swing the doors down to 180°.
- A full size stainless steel paddle latch is recessed into each door.
- Doors can be closed with the latch in the locked position.
- Two keys are furnished per box.
- Ribbed D-Bulb seal is installed in a recessed channel that runs the full perimeter of the door opening.
- Door has a formed knife edge on all 4 sides that contacts the seal when the door is closed.
- Weight: 68 lbs.



## **US72AB TWO DOOR ALUMINUM UPPER SIDE BOX SPECIFICATIONS** **BLACK DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

72" overall length, 16-1/2" overall height, and 12-1/2" overall depth.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Box is constructed of .080 bright diamond treadplate aluminum.
- Welds are full arc welds, no spot welds.
- Doors are constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Each door is attached to the hull of the box with 3 stainless steel pillow block type hinges with self-lubricating bushings and full length 5/16" stainless steel hinge pins.
- Hinges are riveted to the box.
- Top panel of the box forms a drip rail over the door.
- Doors have heavy duty machine chain to hold them in the horizontal position.
- Chains detach to swing the doors down to 180°.
- A full size stainless steel paddle latch is recessed into each door.
- Doors can be closed with the latch in the locked position.
- Two keys are furnished per box.
- Ribbed D-Bulb seal is installed in a recessed channel that runs the full perimeter of the door opening.
- Box goes through a five-stage zinc phosphate wash and is finished with a black super durable powder coat.
- Door has a formed knife edge on all 4 sides that contacts the seal when the door is closed.
- Weight: 68 lbs.



## **US72AW TWO DOOR ALUMINUM UPPER SIDE BOX SPECIFICATIONS** **WHITE DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

72" overall length, 16-1/2" overall height, and 12-1/2" overall depth.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Box is constructed of .080 bright diamond treadplate aluminum.
- Welds are full arc welds, no spot welds.
- Doors are constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Each door is attached to the hull of the box with 3 stainless steel pillow block type hinges with self-lubricating bushings and full length 5/16" stainless steel hinge pins.
- Hinges are riveted to the box.
- Top panel of the box forms a drip rail over the door.
- Doors have heavy duty machine chain to hold them in the horizontal position.
- Chains detach to swing the doors down to 180°.
- A full size stainless steel paddle latch is recessed into each door.
- Doors can be closed with the latch in the locked position.
- Two keys are furnished per box.
- Ribbed D-Bulb seal is installed in a recessed channel that runs the full perimeter of the door opening.
- Box goes through a five-stage zinc phosphate wash and is finished with a white super durable powder coat.
- Door has a formed knife edge on all 4 sides that contacts the seal when the door is closed.
- Weight: 68 lbs.



## **US72C TWO DOOR UPPER SIDE BOX SPECIFICATIONS** **WHITE POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOW:**

72" overall length, 16-1/2" overall height, and 12-1/2" overall depth.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a white super durable polyester powder coat.
- Welds are full arc welds, no spot welds.
- Doors are constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Each door is attached to the hull of the box with 3 stainless steel pillow block type hinges with self-lubricating bushings and 5/16" stainless steel hinge pins.
- Hinges are welded to the box.
- Top panel of the box forms a drip rail over the doors.
- Doors have heavy duty machine chain to hold them in the horizontal position.
- Chain detaches to swing the door down to 180°.
- A full size stainless steel paddle latch is recessed into each door.
- Doors can be closed with the latch in the locked position.
- Two keys are furnished per box.
- Ribbed D-Bulb seal is installed in a full perimeter channel around the door facing.
- A knife edge is formed into the door to contact the seal in the door channel.
- Weight: 138 lbs.



## **US72CB TWO DOOR UPPER SIDE BOX SPECIFICATIONS** **BLACK POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOW:**

72" overall length, 16-1/2" overall height, and 12-1/2" overall depth.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a white super durable polyester powder coat.
- Welds are full arc welds, no spot welds.
- Doors are constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Each door is attached to the hull of the box with 3 stainless steel pillow block type hinges with self-lubricating bushings and 5/16" stainless steel hinge pins.
- Hinges are welded to the box.
- Top panel of the box forms a drip rail over the doors.
- Doors have heavy duty machine chain to hold them in the horizontal position.
- Chain detaches to swing the door down to 180°.
- A full size stainless steel paddle latch is recessed into each door.
- Doors can be closed with the latch in the locked position.
- Two keys are furnished per box.
- Ribbed D-Bulb seal is installed in a full perimeter channel around the door facing.
- A knife edge is formed into the door to contact the seal in the door channel.
- Weight: 138 lbs.



## **US78C TWO DOOR UPPER SIDE BOX SPECIFICATIONS** **WHITE POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOW:**

72" overall length, 16-1/2" overall height, and 12-1/2" overall depth.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a white super durable polyester powder coat.
- Welds are full arc welds, no spot welds.
- Doors are constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Each door is attached to the hull of the box with 3 stainless steel pillow block type hinges with self-lubricating bushings and 5/16" stainless steel hinge pins.
- Hinges are welded to the box.
- Top panel of the box forms a drip rail over the doors.
- Doors have heavy duty machine chain to hold them in the horizontal position.
- Chain detaches to swing the door down to 180°.
- A full size stainless steel paddle latch is recessed into each door.
- Doors can be closed with the latch in the locked position.
- Two keys are furnished per box.
- Ribbed D-Bulb seal is installed in a full perimeter channel around the door facing.
- A knife edge is formed into the door to contact the seal in the door channel.
- Weight: 150 lbs.



## **US78CB TWO DOOR UPPER SIDE BOX SPECIFICATIONS** **BLACK POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOW:**

72" overall length, 16-1/2" overall height, and 12-1/2" overall depth.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a black super durable polyester powder coat.
- Welds are full arc welds, no spot welds.
- Doors are constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Each door is attached to the hull of the box with 3 stainless steel pillow block type hinges with self-lubricating bushings and 5/16" stainless steel hinge pins.
- Hinges are welded to the box.
- Top panel of the box forms a drip rail over the doors.
- Doors have heavy duty machine chain to hold them in the horizontal position.
- Chain detaches to swing the door down to 180°.
- A full size stainless steel paddle latch is recessed into each door.
- Doors can be closed with the latch in the locked position.
- Two keys are furnished per box.
- Ribbed D-Bulb seal is installed in a full perimeter channel around the door facing.
- A knife edge is formed into the door to contact the seal in the door channel.
- Weight: 150 lbs.





## **US90A TWO DOOR ALUMINUM UPPER SIDE BOX SPECIFICATIONS** **BRIGHT DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

90" overall length, 16-1/2" overall height, and 12-1/2" overall depth.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Box is constructed of .080 bright diamond treadplate aluminum.
- Welds are full arc welds, no spot welds.
- Doors are constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Each door is attached to the hull of the box with 3 stainless steel pillow block type hinges with self-lubricating bushings and full length 5/16" stainless steel hinge pins.
- Hinges are riveted to the box.
- Top panel of the box forms a drip rail over the door.
- Doors have heavy duty machine chain to hold them in the horizontal position.
- Chains detach to swing the doors down to 180°.
- A full size stainless steel paddle latch is recessed into each door.
- Doors can be closed with the latch in the locked position.
- Two keys are furnished per box.
- Ribbed D-Bulb seal is installed in a recessed channel that runs the full perimeter of the door opening.
- Door has a formed knife edge on all 4 sides that contacts the seal when the door is closed.
- Weight: 82 lbs.



## **US90AB TWO DOOR ALUMINUM UPPER SIDE BOX SPECIFICATIONS** **BLACK DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

90" overall length, 16-1/2" overall height, and 12-1/2" overall depth.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Box is constructed of .080 bright diamond treadplate aluminum.
- Welds are full arc welds, no spot welds.
- Doors are constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Each door is attached to the hull of the box with 3 stainless steel pillow block type hinges with self-lubricating bushings and full length 5/16" stainless steel hinge pins.
- Hinges are riveted to the box.
- Top panel of the box forms a drip rail over the door.
- Doors have heavy duty machine chain to hold them in the horizontal position.
- Chains detach to swing the doors down to 180°.
- A full size stainless steel paddle latch is recessed into each door.
- Doors can be closed with the latch in the locked position.
- Two keys are furnished per box.
- Ribbed D-Bulb seal is installed in a recessed channel that runs the full perimeter of the door opening.
- Box goes through a five-stage zinc phosphate wash and is finished with a black super durable powder coat.
- Door has a formed knife edge on all 4 sides that contacts the seal when the door is closed.
- Weight: 82 lbs.



## **US90AW TWO DOOR ALUMINUM UPPER SIDE BOX SPECIFICATIONS** **WHITE DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

90" overall length, 16-1/2" overall height, and 12-1/2" overall depth.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Box is constructed of .080 bright diamond treadplate aluminum.
- Welds are full arc welds, no spot welds.
- Doors are constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Each door is attached to the hull of the box with 3 stainless steel pillow block type hinges with self-lubricating bushings and full length 5/16" stainless steel hinge pins.
- Hinges are riveted to the box.
- Top panel of the box forms a drip rail over the door.
- Doors have heavy duty machine chain to hold them in the horizontal position.
- Chains detach to swing the doors down to 180°.
- A full size stainless steel paddle latch is recessed into each door.
- Doors can be closed with the latch in the locked position.
- Two keys are furnished per box.
- Ribbed D-Bulb seal is installed in a recessed channel that runs the full perimeter of the door opening.
- Box goes through a five-stage zinc phosphate wash and is finished with a white super durable powder coat.
- Door has a formed knife edge on all 4 sides that contacts the seal when the door is closed.
- Weight: 82 lbs.



## **US90C TWO DOOR UPPER SIDE BOX SPECIFICATIONS** **WHITE POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

90" overall length, 16-1/2" overall height, and 12-1/2" overall depth.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a white super durable polyester powder coat.
- Welds are full arc welds, no spot welds.
- Doors are constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Each door is attached to the hull of the box with 3 stainless steel pillow block type hinges with self-lubricating bushings and 5/16" stainless steel hinge pins.
- Hinges are welded to the box.
- Top panel of the box forms a drip rail over the doors.
- Doors have heavy duty machine chain to hold them in the horizontal position.
- Chain detaches to swing the door down to 180°.
- A full size stainless steel paddle latch is recessed into each door.
- Doors can be closed with the latch in the locked position.
- Two keys are furnished per box.
- Ribbed D-Bulb seal is installed in a full perimeter channel around the door opening.
- A knife edge is formed into the door to contact the seal in the door channel.
- Weight: 168 lbs.



## **US90CB TWO DOOR UPPER SIDE BOX SPECIFICATIONS** **BLACK POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

90" overall length, 16-1/2" overall height, and 12-1/2" overall depth.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a black super durable polyester powder coat.
- Welds are full arc welds, no spot welds.
- Doors are constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Each door is attached to the hull of the box with 3 stainless steel pillow block type hinges with self-lubricating bushings and 5/16" stainless steel hinge pins.
- Hinges are welded to the box.
- Top panel of the box forms a drip rail over the doors.
- Doors have heavy duty machine chain to hold them in the horizontal position.
- Chain detaches to swing the door down to 180°.
- A full size stainless steel paddle latch is recessed into each door.
- Doors can be closed with the latch in the locked position.
- Two keys are furnished per box.
- Ribbed D-Bulb seal is installed in a full perimeter channel around the door opening.
- A knife edge is formed into the door to contact the seal in the door channel.
- Weight: 168 lbs.



## **US96A TWO DOOR ALUMINUM UPPER SIDE BOX SPECIFICATIONS** **BRIGHT DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

96" overall length, 16-1/2" overall height, and 12-1/2" overall depth.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Box is constructed of .080 bright diamond treadplate aluminum.
- Welds are full arc welds, no spot welds.
- Doors are constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Each door is attached to the hull of the box with 3 stainless steel pillow block type hinges with self-lubricating bushings and full length 5/16" stainless steel hinge pins.
- Hinges are riveted to the box.
- Top panel of the box forms a drip rail over the door.
- Doors are held in the open position with heavy-duty machine chains.
- Chains are easily detachable to drop doors down to 180°.
- A full size, stainless steel paddle latch is recessed into each door.
- Doors can be closed with the latch in the locked position.
- Two keys are furnished per box.
- Ribbed D-Bulb seal is installed in a recessed channel that runs the full perimeter of the door opening.
- Door has a formed knife edge on all 4 sides that contacts the seal when the door is closed.
- Mounting hardware and mounting instructions included.
- Weight: 87 lbs.



## **US96AB TWO DOOR ALUMINUM UPPER SIDE BOX SPECIFICATIONS** **BLACK DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

96" overall length, 16-1/2" overall height, and 12-1/2" overall depth.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Box is constructed of .080 bright diamond treadplate aluminum.
- Welds are full arc welds, no spot welds.
- Doors are constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Each door is attached to the hull of the box with 3 stainless steel pillow block type hinges with self-lubricating bushings and full length 5/16" stainless steel hinge pins.
- Hinges are riveted to the box.
- Top panel of the box forms a drip rail over the door.
- Doors are held in the open horizontal position with heavy duty machine chain.
- Chains are easily detachable to drop the door down to 180°.
- A full size stainless steel paddle latch is recessed into each door.
- Doors can be closed with the latch in the locked position.
- Two keys are furnished per box.
- Ribbed D-Bulb seal is installed in a recessed channel that runs the full perimeter of the door opening.
- Box goes through a five-stage zinc phosphate wash and is finished with a black super durable powder coat.
- Door has a formed knife edge on all 4 sides that contacts the seal when the door is closed.
- Weight: 87 lbs.



## **US96AW TWO DOOR ALUMINUM UPPER SIDE BOX SPECIFICATIONS** **WHITE DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

96" overall length, 16-1/2" overall height, and 12-1/2" overall depth.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Box is constructed of .080 bright diamond treadplate aluminum.
- Welds are full arc welds, no spot welds.
- Doors are constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Each door is attached to the hull of the box with 3 stainless steel pillow block type hinges with self-lubricating bushings and full length 5/16" stainless steel hinge pins.
- Hinges are riveted to the box.
- Top panel of the box forms a drip rail over the door.
- Doors are held in the open horizontal position with heavy duty machine chain.
- Chains are easily detachable to drop the door down to 180°.
- A full size stainless steel paddle latch is recessed into each door.
- Doors can be closed with the latch in the locked position.
- Two keys are furnished per box.
- Ribbed D-Bulb seal is installed in a recessed channel that runs the full perimeter of the door opening.
- Box goes through a five-stage zinc phosphate wash and is finished with a white super durable powder coat.
- Door has a formed knife edge on all 4 sides that contacts the seal when the door is closed.
- Weight: 87 lbs.





## **US96C TWO DOOR UPPER SIDE BOX SPECIFICATIONS** **WHITE POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

96" overall length, 16-1/2" overall height, and 12-1/2" overall depth.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a white super durable polyester powder coat.
- Welds are full arc welds, no spot welds.
- Doors are constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Doors are attached to the hull of the box with 3 stainless steel pillow block type hinges with self-lubricating bushings and 5/16" stainless steel hinge pins.
- Hinges are welded to the box.
- Top panel of the box forms a drip rail over the doors.
- Doors are held in the open position with heavy-duty machine chains.
- Chains are easily detachable to drop doors down to 180°.
- A full size, stainless steel paddle latch is recessed into each door.
- Doors can be closed with the latch in the locked position.
- Two keys are furnished per box.
- Ribbed D-Bulb seal is installed in a full perimeter channel around the door opening.
- A knife edge is formed into the door to contact the seal in the door channel.
- Mounting hardware and mounting instructions included.
- Weight: 176 lbs.



## **US96CB TWO DOOR UPPER SIDE BOX SPECIFICATIONS** **BLACK POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

96" overall length, 16-1/2" overall height, and 12-1/2" overall depth.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a black super durable polyester powder coat.
- Welds are full arc welds, no spot welds.
- Doors are constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Doors are attached to the hull of the box with 3 stainless steel pillow block type hinges with self-lubricating bushings and 5/16" stainless steel hinge pins.
- Hinges are welded to the box.
- Top panel of the box forms a drip rail over the doors.
- Doors have heavy duty machine chain to hold them in the horizontal position.
- Chain detaches to swing the door down to 180°.
- A full size stainless steel paddle latch is recessed into each door.
- Doors can be closed with the latch in the locked position.
- Two keys are furnished per box.
- Ribbed D-Bulb seal is installed in a full perimeter channel around the door opening.
- A knife edge is formed into the door to contact the seal in the door channel.
- Weight: 176 lbs.



## **UST48C SINGLE DOOR UPPER SIDE BOX SPECIFICATIONS** **WITH INTEGRAL TOP OPENING COMPARTMENT** **WHITE POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

48-1/2" overall length, 20-1/8" overall height, and 14-1/2" overall depth.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of box is constructed of 14 gauge cold rolled steel.
- Welds are full arc welds, no spot welds.
- Box incorporates a 4-1/2" deep top opening compartment.
- Top opening compartment has adjustable divider slots on 2" centers.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with three 4" stainless steel butt hinges that are welded to the hull of the box and the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the top compartment opening.
- Lid design forms a drip rail over the doors.
- 8 dividers are furnished for top opening compartment.
- Front horizontally hinged door is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Door is attached to the hull of the box with 3 stainless steel pillow block type hinges with self-lubricating bushings and 5/16" stainless steel hinge pins.
- Hinges are welded to the box.
- Door has heavy duty machine chain to hold it in the horizontal position.
- Chain detaches to swing the door down to 180°.
- A full size stainless steel paddle latch is recessed into each door.
- Door can be closed with the latch in the locked position.
- Two keys are furnished per box.
- Ribbed D-Bulb seal is installed in a full perimeter channel around the door opening.
- A knife edge is formed into the door to contact the seal in the door channel.
- Box goes through a five-stage zinc phosphate wash, anti-corrosion protection, and is finished with a white super durable polyester powder coat.
- Weight: 151 lbs.



## **UST48CB SINGLE DOOR UPPER SIDE BOX SPECIFICATIONS** **WITH INTEGRAL TOP OPENING COMPARTMENT** **BLACK POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

48-1/2" overall length, 20-1/8" overall height, and 14-1/2" overall depth.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of box is constructed of 14 gauge cold rolled steel.
- Welds are full arc welds, no spot welds.
- Box incorporates a 4-1/2" deep top opening compartment.
- Top opening compartment has adjustable divider slots on 2" centers.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with three 4" stainless steel butt hinges that are welded to the hull of the box and the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the top compartment opening.
- Lid design forms a drip rail over the doors.
- 8 dividers are furnished for top opening compartment.
- Front horizontally hinged door is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Door is attached to the hull of the box with 3 stainless steel pillow block type hinges with self-lubricating bushings and 5/16" stainless steel hinge pins.
- Hinges are welded to the box.
- Door has heavy duty machine chain to hold it in the horizontal position.
- Chain detaches to swing the door down to 180°.
- A full size stainless steel paddle latch is recessed into each door.
- Door can be closed with the latch in the locked position.
- Two keys are furnished per box.
- Ribbed D-Bulb seal is installed in a full perimeter channel around the door opening.
- A knife edge is formed into the door to contact the seal in the door channel.
- Box goes through a five-stage zinc phosphate wash, anti-corrosion protection, and is finished with a black super durable polyester powder coat.
- Weight: 151 lbs.



## **UST60C TWO DOOR UPPER SIDE BOX SPECIFICATIONS** **WITH INTEGRAL TOP OPENING COMPARTMENT** **WHITE POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

60-1/2" overall length, 20-1/8" overall height, and 14-1/2" overall depth.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of box is constructed of 14 gauge cold rolled steel.
- Welds are full arc welds, no spot welds.
- Box incorporates a 4-1/2" deep top opening compartment.
- Top opening compartment has adjustable divider slots on 2" centers.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with six 4" stainless steel butt hinges that are welded to the hull of the box and the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the top compartment opening.
- Lid design forms a drip rail over the doors.
- 8 dividers are furnished for top opening compartment.
- Front horizontally hinged doors are constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Doors are attached to the hull of the box with 3 stainless steel pillow block type hinges with self-lubricating bushings and 5/16" stainless steel hinge pins.
- Hinges are welded to the box.
- Doors have heavy duty machine chain to hold them in the horizontal position.
- Chain detaches to swing the door down to 180°.
- A full size stainless steel paddle latch is recessed into each door.
- Doors can be closed with the latch in the locked position.
- Two keys are furnished per box.
- Ribbed D-Bulb seal is installed in a full perimeter channel around the door openings.
- A knife edge is formed into the door to contact the seal in the door channel.
- Box goes through a five-stage zinc phosphate wash, anti-corrosion protection, and is finished with a white super durable polyester powder coat.
- Weight: 188 lbs.



**UST60CB TWO DOOR UPPER SIDE BOX SPECIFICATIONS**  
**WITH INTEGRAL TOP OPENING COMPARTMENT**  
**BLACK POWDER FINISH**

**BOX DIMENSIONS AS FOLLOWS:**

60-1/2" overall length, 20-1/8" overall height, and 14-1/2" overall depth.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of box is constructed of 14 gauge cold rolled steel.
- Welds are full arc welds, no spot welds.
- Box incorporates a 4-1/2" deep top opening compartment.
- Top opening compartment has adjustable divider slots on 2" centers.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with six 4" stainless steel butt hinges that are welded to the hull of the box and the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the top compartment opening.
- Lid design forms a drip rail over the doors.
- 8 dividers are furnished for top opening compartment.
- Front horizontally hinged doors are constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Doors are attached to the hull of the box with 3 stainless steel pillow block type hinges with self-lubricating bushings and 5/16" stainless steel hinge pins.
- Hinges are welded to the box.
- Doors have heavy duty machine chain to hold them in the horizontal position.
- Chain detaches to swing the door down to 180°.
- A full size stainless steel paddle latch is recessed into each door.
- Doors can be closed with the latch in the locked position.
- Two keys are furnished per box.
- Ribbed D-Bulb seal is installed in a full perimeter channel around the door openings.
- A knife edge is formed into the door to contact the seal in the door channel.
- Box goes through a five-stage zinc phosphate wash, anti-corrosion protection, and is finished with a black super durable polyester powder coat.
- Weight: 188 lbs.



## **UST72A TWO DOOR ALUMINUM UPPER SIDE BOX SPECIFICATIONS** **WITH INTEGRAL TOP OPENING COMPARTMENT** **BRIGHT DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

73" overall length, 20" overall height, and 14-1/2" overall depth.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of box is constructed of .080 diamond treadplate aluminum.
- Welds are full arc welds, no spot welds.
- Box incorporates a 4-1/2" deep top opening compartment.
- Top opening compartment has adjustable divider slots on 2" centers.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Lid is equipped with gas pressure shocks for one-hand opening of the box.
- Lid is attached to the hull of the box with five 4" aluminum butt hinges with 1/4" hinge pins that are welded to the hull of the box and the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the top compartment opening.
- Lid design forms a drip rail over the doors.
- 8 dividers are furnished for top opening compartment.
- Front horizontally hinged doors are constructed of .080 diamond treadplate aluminum, with a .090 smooth aluminum inner stiffener.
- Doors are attached to the hull of the box with 3 stainless steel pillow block type hinges with self-lubricating bushings and 5/16" stainless steel hinge pins.
- Hinges are welded to the box.
- Doors have heavy duty machine chain to hold them in the horizontal position.
- Chain detaches to swing the door down to 180°.
- A full size stainless steel paddle latch is recessed into each door.
- Doors can be closed with the latch in the locked position.
- Two keys are furnished per box.
- Ribbed D-Bulb seal is installed in a full perimeter channel around the door openings.
- A knife edge is formed into the door to contact the seal in the door channel.
- Weight: 107 lbs.



## **UST72AB TWO DOOR ALUMINUM UPPER SIDE BOX SPECIFICATIONS WITH INTEGRAL TOP OPENING COMPARTMENT BLACK DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

73" overall length, 20" overall height, and 14-1/2" overall depth.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of box is constructed of .080 diamond treadplate aluminum.
- Welds are full arc welds, no spot welds.
- Box incorporates a 4-1/2" deep top opening compartment.
- Top opening compartment has adjustable divider slots on 2" centers.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Lid is equipped with gas pressure shocks for one-hand opening of the box.
- Lid is attached to the hull of the box with five 4" aluminum butt hinges with 1/4" hinge pins that are welded to the hull of the box and the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the top compartment opening.
- Lid design forms a drip rail over the doors.
- 8 dividers are furnished for top opening compartment.
- Front horizontally hinged doors are constructed of .080 diamond treadplate aluminum, with a .090 smooth aluminum inner stiffener.
- Doors are attached to the hull of the box with 3 stainless steel pillow block type hinges with self-lubricating bushings and 5/16" stainless steel hinge pins.
- Hinges are welded to the box.
- Doors have heavy duty machine chain to hold them in the horizontal position.
- Chain detaches to swing the door down to 180°.
- A full size stainless steel paddle latch is recessed into each door.
- Doors can be closed with the latch in the locked position.
- Two keys are furnished per box.
- Ribbed D-Bulb seal is installed in a full perimeter channel around the door openings.
- Box goes through a five-stage zinc phosphate wash and is finished with a black super durable powder coat.
- A knife edge is formed into the door to contact the seal in the door channel.
- Weight: 107 lbs.





## **UST72AW TWO DOOR ALUMINUM UPPER SIDE BOX SPECIFICATIONS** **WITH INTEGRAL TOP OPENING COMPARTMENT** **WHITE DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

73" overall length, 20" overall height, and 14-1/2" overall depth.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of box is constructed of .080 diamond treadplate aluminum.
- Welds are full arc welds, no spot welds.
- Box incorporates a 4-1/2" deep top opening compartment.
- Top opening compartment has adjustable divider slots on 2" centers.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Lid is equipped with gas pressure shocks for one-hand opening of the box.
- Lid is attached to the hull of the box with five 4" aluminum butt hinges with 1/4" hinge pins that are welded to the hull of the box and the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the top compartment opening.
- Lid design forms a drip rail over the doors.
- 8 dividers are furnished for top opening compartment.
- Front horizontally hinged doors are constructed of .080 diamond treadplate aluminum, with a .090 smooth aluminum inner stiffener.
- Doors are attached to the hull of the box with 3 stainless steel pillow block type hinges with self-lubricating bushings and 5/16" stainless steel hinge pins.
- Hinges are welded to the box.
- Doors have heavy duty machine chain to hold them in the horizontal position.
- Chain detaches to swing the door down to 180°.
- A full size stainless steel paddle latch is recessed into each door.
- Doors can be closed with the latch in the locked position.
- Two keys are furnished per box.
- Ribbed D-Bulb seal is installed in a full perimeter channel around the door openings.
- Box goes through a five-stage zinc phosphate wash and is finished with a white super durable powder coat.
- A knife edge is formed into the door to contact the seal in the door channel.
- Weight: 107 lbs.



**UST72C TWO DOOR UPPER SIDE BOX SPECIFICATIONS**  
**WITH INTEGRAL TOP OPENING COMPARTMENT**  
**WHITE POWDER FINISH**

**BOX DIMENSIONS AS FOLLOWS:**

73" overall length, 20" overall height, and 14-1/2" overall depth.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of box is constructed of 14 gauge cold rolled steel.
- Welds are full arc welds, no spot welds.
- Box incorporates a 4-1/2" deep top opening compartment.
- Top opening compartment has adjustable divider slots on 2" centers.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with six 4" stainless steel butt hinges that are welded to the hull of the box and the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the top compartment opening.
- Lid design forms a drip rail over the doors.
- 8 dividers are furnished for top opening compartment.
- Front horizontally hinged doors are constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Doors are attached to the hull of the box with 3 stainless steel pillow block type hinges with self-lubricating bushings and 5/16" stainless steel hinge pins.
- Hinges are welded to the box.
- Doors have heavy duty machine chain to hold them in the horizontal position.
- Chain detaches to swing the door down to 180°.
- A full size stainless steel paddle latch is recessed into each door.
- Doors can be closed with the latch in the locked position.
- Two keys are furnished per box.
- Ribbed D-Bulb seal is installed in a full perimeter channel around the door openings.
- A knife edge is formed into the door to contact the seal in the door channel.
- Box goes through a five-stage zinc phosphate wash, anti-corrosion protection, and is finished with a white super durable polyester powder coat.
- Weight: 226 lbs.



## **UST72CB TWO DOOR UPPER SIDE BOX SPECIFICATIONS** **WITH INTEGRAL TOP OPENING COMPARTMENT** **BLACK POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

73" overall length, 20-1/8" overall height, and 14-1/2" overall depth.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of box is constructed of 14 gauge cold rolled steel.
- Welds are full arc welds, no spot welds.
- Box incorporates a 4-1/2" deep top opening compartment.
- Top opening compartment has adjustable divider slots on 2" centers.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with six 4" stainless steel butt hinges that are welded to the hull of the box and the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the top compartment opening.
- Lid design forms a drip rail over the doors.
- 8 dividers are furnished for top opening compartment.
- Front horizontally hinged doors are constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Doors are attached to the hull of the box with 3 stainless steel pillow block type hinges with self-lubricating bushings and 5/16" stainless steel hinge pins.
- Hinges are welded to the box.
- Doors have heavy duty machine chain to hold them in the horizontal position.
- Chain detaches to swing the door down to 180°.
- A full size stainless steel paddle latch is recessed into each door.
- Doors can be closed with the latch in the locked position.
- Two keys are furnished per box.
- Ribbed D-Bulb seal is installed in a full perimeter channel around the door openings.
- A knife edge is formed into the door to contact the seal in the door channel.
- Box goes through a five-stage zinc phosphate wash, anti-corrosion protection, and is finished with a black super durable polyester powder coat.
- Weight: 226 lbs.



## **UST90C TWO DOOR UPPER SIDE BOX SPECIFICATIONS** **WITH INTEGRAL TOP OPENING COMPARTMENT** **WHITE POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

90-1/2" overall length, 20-1/8" overall height, and 14-1/2" overall depth.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of box is constructed of 14 gauge cold rolled steel.
- Welds are full arc welds, no spot welds.
- Box incorporates a 4-1/2" deep top opening compartment.
- Top opening compartment has adjustable divider slots on 2" centers.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with six 4" stainless steel butt hinges that are welded to the hull of the box and the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the top compartment opening.
- Lid design forms a drip rail over the doors.
- 8 dividers are furnished for top opening compartment.
- Front horizontally hinged doors are constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Doors are attached to the hull of the box with 3 stainless steel pillow block type hinges with self-lubricating bushings and 5/16" stainless steel hinge pins.
- Hinges are welded to the box.
- Doors have heavy duty machine chain to hold them in the horizontal position.
- Chain detaches to swing the door down to 180°.
- A full size stainless steel paddle latch is recessed into each door.
- Doors can be closed with the latch in the locked position.
- Two keys are furnished per box.
- Ribbed D-Bulb seal is installed in a full perimeter channel around the door openings.
- A knife edge is formed into the door to contact the seal in the door channel.
- Box goes through a five-stage zinc phosphate wash, anti-corrosion protection, and is finished with a white super durable polyester powder coat.
- Weight: 261 lbs.



**UST90CB TWO DOOR UPPER SIDE BOX SPECIFICATIONS**  
**WITH INTEGRAL TOP OPENING COMPARTMENT**  
**BLACK POWDER FINISH**

**BOX DIMENSIONS AS FOLLOWS:**

90-1/2" overall length, 20-1/8" overall height, and 14-1/2" overall depth.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of box is constructed of 14 gauge cold rolled steel.
- Welds are full arc welds, no spot welds.
- Box incorporates a 4-1/2" deep top opening compartment.
- Top opening compartment has adjustable divider slots on 2" centers.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with six 4" stainless steel butt hinges that are welded to the hull of the box and the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the top compartment opening.
- Lid design forms a drip rail over the doors.
- 8 dividers are furnished for top opening compartment.
- Front horizontally hinged doors are constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Doors are attached to the hull of the box with 3 stainless steel pillow block type hinges with self-lubricating bushings and 5/16" stainless steel hinge pins.
- Hinges are welded to the box.
- Doors have heavy duty machine chain to hold them in the horizontal position.
- Chain detaches to swing the door down to 180°.
- A full size stainless steel paddle latch is recessed into each door.
- Doors can be closed with the latch in the locked position.
- Two keys are furnished per box.
- Ribbed D-Bulb seal is installed in a full perimeter channel around the door openings.
- A knife edge is formed into the door to contact the seal in the door channel.
- Box goes through a five-stage zinc phosphate wash, anti-corrosion protection, and is finished with a black super durable polyester powder coat.
- Weight: 261 lbs.



## **UST96A TWO DOOR ALUMINUM UPPER SIDE BOX SPECIFICATIONS** **WITH INTEGRAL TOP OPENING COMPARTMENT** **BRIGHT DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

97" overall length, 20" overall height, and 14-1/2" overall depth.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of box is constructed of .080 diamond treadplate aluminum.
- Welds are full arc welds, no spot welds.
- Box incorporates a 4-1/2" deep top opening compartment.
- Top opening compartment has adjustable divider slots on 2" centers.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Lid is equipped with two gas shocks for one-hand opening of the box.
- Lid is attached to the hull of the box with five 4" aluminum butt hinges with 1/4" hinge pins that are welded to the hull of the box and the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the top compartment opening.
- Lid design forms a drip rail over the doors.
- 8 dividers are furnished for top opening compartment.
- Front horizontally hinged doors are constructed of .080 diamond treadplate aluminum, with a .090 smooth aluminum inner stiffener.
- Doors are attached to the hull of the box with 3 stainless steel pillow block type hinges with self-lubricating bushings and 5/16" stainless steel hinge pins.
- Door hinges are riveted to the box.
- Doors are held in the open position with heavy-duty machine chains.
- Chains are easily detachable to drop doors down to 180°.
- A full size, stainless steel paddle latch is recessed into each door.
- Doors can be closed with the latch in the locked position.
- Two keys are furnished per box.
- Ribbed D-Bulb seal is installed in a full perimeter channel around the door openings.
- A knife edge is formed into the door to contact the seal in the door channel.
- Mounting and mounting instructions included.
- Weight: 142 lbs.



## **UST96AB TWO DOOR ALUMINUM UPPER SIDE BOX SPECIFICATIONS WITH INTEGRAL TOP OPENING COMPARTMENT BLACK DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

97" overall length, 20" overall height, and 14-1/2" overall depth.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of box is constructed of .080 diamond treadplate aluminum.
- Welds are full arc welds, no spot welds.
- Box incorporates a 4-1/2" deep top opening compartment.
- Top opening compartment has adjustable divider slots on 2" centers.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Lid is equipped with gas pressure shocks for one-hand opening of the box.
- Lid is attached to the hull of the box with five 4" aluminum butt hinges with 1/4" hinge pins that are welded to the hull of the box and the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the top compartment opening.
- Lid design forms a drip rail over the doors.
- 8 dividers are furnished for top opening compartment.
- Front horizontally hinged doors are constructed of .080 diamond treadplate aluminum, with a .090 smooth aluminum inner stiffener.
- Doors are attached to the hull of the box with 3 stainless steel pillow block type hinges with self-lubricating bushings and 5/16" stainless steel hinge pins.
- Hinges are welded to the box.
- Doors have heavy duty machine chain to hold them in the horizontal position.
- Chain detaches to swing the door down to 180°.
- A full size stainless steel paddle latch is recessed into each door.
- Doors can be closed with the latch in the locked position.
- Two keys are furnished per box.
- Ribbed D-Bulb seal is installed in a full perimeter channel around the door openings.
- A knife edge is formed into the door to contact the seal in the door channel.
- Box goes through a five-stage zinc phosphate wash, anti-corrosion protection, and is finished with a black super durable polyester powder coat.
- Weight: 142 lbs.



## **UST96AW TWO DOOR ALUMINUM UPPER SIDE BOX SPECIFICATIONS WITH INTEGRAL TOP OPENING COMPARTMENT WHITE DIAMOND TREADPLATE**

### **BOX DIMENSIONS AS FOLLOWS:**

97" overall length, 20" overall height, and 14-1/2" overall depth.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of box is constructed of .080 diamond treadplate aluminum.
- Welds are full arc welds, no spot welds.
- Box incorporates a 4-1/2" deep top opening compartment.
- Top opening compartment has adjustable divider slots on 2" centers.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Lid is equipped with gas pressure shocks for one-hand opening of the box.
- Lid is attached to the hull of the box with five 4" aluminum butt hinges with 1/4" hinge pins that are welded to the hull of the box and the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the top compartment opening.
- Lid design forms a drip rail over the doors.
- 8 dividers are furnished for top opening compartment.
- Front horizontally hinged doors are constructed of .080 diamond treadplate aluminum, with a .090 smooth aluminum inner stiffener.
- Doors are attached to the hull of the box with 3 stainless steel pillow block type hinges with self-lubricating bushings and 5/16" stainless steel hinge pins.
- Hinges are welded to the box.
- Doors have heavy duty machine chain to hold them in the horizontal position.
- Chain detaches to swing the door down to 180°.
- A full size stainless steel paddle latch is recessed into each door.
- Doors can be closed with the latch in the locked position.
- Two keys are furnished per box.
- Ribbed D-Bulb seal is installed in a full perimeter channel around the door openings.
- A knife edge is formed into the door to contact the seal in the door channel.
- Box goes through a five-stage zinc phosphate wash, anti-corrosion protection, and is finished with a white super durable polyester powder coat.
- Weight: 142 lbs.





## **UST96C TWO DOOR UPPER SIDE BOX SPECIFICATIONS** **WITH INTEGRAL TOP OPENING COMPARTMENT** **WHITE POWDER FINISH**

### **BOX DIMENSIONS AS FOLLOWS:**

96-1/2" overall length, 20-1/8" overall height, and 14-1/2" overall depth.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of box is constructed of 14 gauge cold rolled steel.
- Welds are full arc welds, no spot welds.
- Box incorporates a 4-1/2" deep top opening compartment.
- Top opening compartment has adjustable divider slots on 2" centers.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Four spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with four 4" stainless steel butt hinges that are welded to the hull of the box and the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the top compartment opening.
- Lid design forms a drip rail over the doors.
- 8 dividers are furnished for top opening compartment.
- Front horizontally hinged doors are constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Doors are attached to the hull of the box with 3 stainless steel pillow block type hinges with self-lubricating bushings and 5/16" stainless steel hinge pins.
- Door hinges are welded to the box.
- Doors are held in the open position with heavy-duty machine chains.
- Chains are easily detachable to drop doors down to 180°.
- A full size, stainless steel paddle latch is recessed into each door.
- Doors can be closed with the latch in the locked position.
- Two keys are furnished per box.
- Ribbed D-Bulb seal is installed in a full perimeter channel around the door openings.
- A knife edge is formed into the door to contact the seal in the door channel.
- Box goes through a five-stage zinc phosphate wash, anti-corrosion protection, and is finished with a white super durable polyester powder coat.
- Mounting hardware and mounting instructions included.
- Weight: 287 lbs.



**UST96CB TWO DOOR UPPER SIDE BOX SPECIFICATIONS**  
**WITH INTEGRAL TOP OPENING COMPARTMENT**  
**BLACK POWDER FINISH**

**BOX DIMENSIONS AS FOLLOWS:**

96-1/2" overall length, 20-1/8" overall height, and 14-1/2" overall depth.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of box is constructed of 14 gauge cold rolled steel.
- Welds are full arc welds, no spot welds.
- Box incorporates a 4-1/2" deep top opening compartment.
- Top opening compartment has adjustable divider slots on 2" centers.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with six 4" stainless steel butt hinges that are welded to the hull of the box and the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the top compartment opening.
- Lid design forms a drip rail over the doors.
- 8 dividers are furnished for top opening compartment.
- Front horizontally hinged doors are constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Doors are attached to the hull of the box with 3 stainless steel pillow block type hinges with self-lubricating bushings and 5/16" stainless steel hinge pins.
- Hinges are welded to the box.
- Doors have heavy duty machine chain to hold them in the horizontal position.
- Chain detaches to swing the door down to 180°.
- A full size stainless steel paddle latch is recessed into each door.
- Doors can be closed with the latch in the locked position.
- Two keys are furnished per box.
- Ribbed D-Bulb seal is installed in a full perimeter channel around the door openings.
- A knife edge is formed into the door to contact the seal in the door channel.
- Box goes through a five-stage zinc phosphate wash, anti-corrosion protection, and is finished with a white super durable polyester powder coat.
- Weight: 287 lbs.



## **WG10 NL “NO LOUVER” WINDOW GRILLE SPECIFICATIONS** **WHITE POWDER FINISH**

### **NO LOUVER WINDOW GRILLE DIMENSIONS AS FOLLOWS:**

71" overall length, 24-1/2" wide including brackets, and 28" tall.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a white super durable polyester powder coat.
- End plates are 1/2" x 3" cold rolled steel flatbar.
- Upper and lower crossbars are 2" x 2" square tubing with .065 wall.
- Welds are full arc welds, no spot welds.
- Mounting brackets are of 3/16" steel construction.
- Mounting hardware and instructions are included.
- Weight: 64 lbs.



## **WG10 WINDOW GRILLE SPECIFICATIONS** **WHITE POWDER FINISH**

### **WINDOW GRILLE DIMENSIONS AS FOLLOWS:**

71" overall length, 24-1/2" wide including brackets, and 28" tall.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a white super durable polyester powder coat.
- End plates are 1/2" x 3" cold rolled steel flatbar.
- Upper and lower crossbars are 2" x 2" square tubing with .065 wall.
- Welds are full arc welds, no spot welds.
- Mounting brackets are of 3/16" steel construction.
- Mounting hardware and instructions are included.
- Weight: 88 lbs.



## **WG10B NL “NO LOUVER” WINDOW GRILLE SPECIFICATIONS** **BLACK POWDER FINISH**

### **NO LOUVER WINDOW GRILLE DIMENSIONS AS FOLLOWS:**

71" overall length, 24-1/2" wide including brackets, and 28" tall.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a black super durable polyester powder coat.
- End plates are 1/2" x 3" cold rolled steel flatbar.
- Upper and lower crossbars are 2" x 2" square tubing with .065 wall.
- Welds are full arc welds, no spot welds.
- Mounting brackets are of 3/16" steel construction.
- Mounting hardware and instructions are included.
- Weight: 64 lbs.



## **WG10B WINDOW GRILLE SPECIFICATIONS** **BLACK POWDER FINISH**

### **WINDOW GRILLE DIMENSIONS AS FOLLOWS:**

71" overall length, 24-1/2" wide including brackets, and 28" tall.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a black super durable polyester powder coat.
- End plates are 1/2" x 3" cold rolled steel flatbar.
- Upper and lower crossbars are 2" x 2" square tubing with .065 wall.
- Louvers are constructed of 14 gauge cold rolled steel with four 1/2" round rod vertical supports.
- Louvers are assembled as to allow an unobstructed view of the center high mount stop light.
- Welds are full arc welds, no spot welds.
- Mounting brackets are of 3/16" steel construction.
- Mounting hardware and instructions are included.
- Weight: 88 lbs.



## **WG11 NL “NO LOUVER” WINDOW GRILLE SPECIFICATIONS** **WHITE POWDER FINISH**

### **NO LOUVER WINDOW GRILLE DIMENSIONS AS FOLLOWS:**

71" overall length, 24-1/2" wide including brackets, and 29-3/8" tall.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a white super durable polyester powder coat.
- End plates are 1/2" x 3" cold rolled steel flatbar.
- Upper and lower crossbars are 2" x 2" square tubing with .065 wall.
- Welds are full arc welds, no spot welds.
- Mounting brackets are of 3/16" steel construction.
- Mounting hardware and instructions are included.
- Weight: 65 lbs.



## **WG11 WINDOW GRILLE SPECIFICATIONS** **WHITE POWDER FINISH**

### **WINDOW GRILLE DIMENSIONS AS FOLLOWS:**

71" overall length, 24-1/2" wide including brackets, and 29-3/8" tall.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a white super durable polyester powder coat.
- End plates are 1/2" x 3" cold rolled steel flatbar.
- Upper and lower crossbars are 2" x 2" square tubing with .065 wall.
- Welds are full arc welds, no spot welds.
- Mounting brackets are of 3/16" steel construction.
- Mounting hardware and instructions are included.
- Weight: 88 lbs.





## **WG11B NL “NO LOUVER” WINDOW GRILLE SPECIFICATIONS** **BLACK POWDER FINISH**

### **NO LOUVER WINDOW GRILLE DIMENSIONS AS FOLLOWS:**

71" overall length, 24-1/2" wide including brackets, and 29-3/8" tall.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a black super durable polyester powder coat.
- End plates are 1/2" x 3" cold rolled steel flatbar.
- Upper and lower crossbars are 2" x 2" square tubing with .065 wall.
- Welds are full arc welds, no spot welds.
- Mounting brackets are of 3/16" steel construction.
- Mounting hardware and instructions are included.
- Weight: 65 lbs.



## **WG11B WINDOW GRILLE SPECIFICATIONS** **BLACK POWDER FINISH**

### **WINDOW GRILLE DIMENSIONS AS FOLLOWS:**

71" overall length, 24-1/2" wide including brackets, and 29-3/8" tall.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a black super durable polyester powder coat.
- End plates are 1/2" x 3" cold rolled steel flatbar.
- Upper and lower crossbars are 2" x 2" square tubing with .065 wall.
- Louvers are constructed of 14 gauge cold rolled steel with four 1/2" round rod vertical supports.
- Louvers are assembled as to allow an unobstructed view of the center high mount stop light.
- Welds are full arc welds, no spot welds.
- Mounting brackets are of 3/16" steel construction.
- Mounting hardware and instructions are included.
- Weight: 88 lbs.



## **WG14 WINDOW GRILLE SPECIFICATIONS** **WHITE POWDER FINISH**

### **WINDOW GRILLE DIMENSIONS AS FOLLOWS:**

59-7/8" overall length, 24-1/2" wide including brackets, and 27" tall.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a white super durable polyester powder coat.
- End plates are 1/2" x 3" cold rolled steel flatbar.
- Upper and lower crossbars are 2" x 2" square tubing with .065 wall.
- Louvers are constructed of 14 gauge cold rolled steel with four 1/2" round rod vertical supports.
- Louvers are assembled as to allow an unobstructed view of the center high mount stop light.
- Welds are full arc welds, no spot welds.
- Mounting brackets are of 3/16" steel construction.
- Mounting hardware and instructions are included.
- Weight: 78 lbs.



## **WG14B NL “NO LOUVER” WINDOW GRILLE SPECIFICATIONS** **BLACK POWDER FINISH**

### **NO LOUVER WINDOW GRILLE DIMENSIONS AS FOLLOWS:**

59-7/8" overall length, 24-1/2" wide including brackets, and 27" tall.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a black super durable polyester powder coat.
- End plates are 1/2" x 3" cold rolled steel flatbar.
- Upper and lower crossbars are 2" x 2" square tubing with .065 wall.
- Welds are full arc welds, no spot welds.
- Mounting brackets are of 3/16" steel construction.
- Mounting hardware and instructions are included.
- Weight: 57 lbs.



## **WG14B WINDOW GRILLE SPECIFICATIONS** **BLACK POWDER FINISH**

### **WINDOW GRILLE DIMENSIONS AS FOLLOWS:**

59-7/8" overall length, 24-1/2" wide including brackets, and 27" tall.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a black super durable polyester powder coat.
- End plates are 1/2" x 3" cold rolled steel flatbar.
- Upper and lower crossbars are 2" x 2" square tubing with .065 wall.
- Louvers are constructed of 14 gauge cold rolled steel with four 1/2" round rod vertical supports.
- Louvers are assembled as to allow an unobstructed view of the center high mount stop light.
- Welds are full arc welds, no spot welds.
- Mounting brackets are of 3/16" steel construction.
- Mounting hardware and instructions are included.
- Weight: 78 lbs.



**WG14 NL "NO LOUVER" WINDOW GRILLE SPECIFICATIONS**  
**WHITE POWDER FINISH**

**NO LOUVER WINDOW GRILLE DIMENSIONS AS FOLLOWS:**

59-7/8" overall length, 24-1/2" wide including brackets, and 27" tall.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a white super durable polyester powder coat.
- End plates are 1/2" x 3" cold rolled steel flatbar.
- Upper and lower crossbars are 2" x 2" square tubing with .065 wall.
- Welds are full arc welds, no spot welds.
- Mounting brackets are of 3/16" steel construction.
- Mounting hardware and instructions are included.
- Weight: 57 lbs.



## **WG15 NL “NO LOUVER” WINDOW GRILLE SPECIFICATIONS** **WHITE POWDER FINISH**

### **NO LOUVER WINDOW GRILLE DIMENSIONS AS FOLLOWS:**

71" overall length, 24-1/2" wide including brackets, and 26-3/8" tall.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a white super durable polyester powder coat.
- End plates are 1/2" x 3" cold rolled steel flatbar.
- Upper and lower crossbars are 2" x 2" square tubing with .065 wall.
- Welds are full arc welds, no spot welds.
- Mounting brackets are of 3/16" steel construction.
- Mounting hardware and instructions are included.
- Weight: 62 lbs.



## **WG15 WINDOW GRILLE SPECIFICATIONS** **WHITE POWDER FINISH**

### **WINDOW GRILLE DIMENSIONS AS FOLLOWS:**

71" overall length, 24-1/2" wide including brackets, and 26-3/8" tall.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a white super durable polyester powder coat.
- End plates are 1/2" x 3" cold rolled steel flatbar.
- Upper and lower crossbars are 2" x 2" square tubing with .065 wall.
- Welds are full arc welds, no spot welds.
- Mounting brackets are of 3/16" steel construction.
- Mounting hardware and instructions are included.
- Weight: 83 lbs.





## **WG15B NL “NO LOUVER” WINDOW GRILLE SPECIFICATIONS** **BLACK POWDER FINISH**

### **NO LOUVER WINDOW GRILLE DIMENSIONS AS FOLLOWS:**

71" overall length, 24-1/2" wide including brackets, and 26-3/8" tall.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a black super durable polyester powder coat.
- End plates are 1/2" x 3" cold rolled steel flatbar.
- Upper and lower crossbars are 2" x 2" square tubing with .065 wall.
- Welds are full arc welds, no spot welds.
- Mounting brackets are of 3/16" steel construction.
- Mounting hardware and instructions are included.
- Weight: 62 lbs.



## **WG15B WINDOW GRILLE SPECIFICATIONS** **BLACK POWDER FINISH**

### **WINDOW GRILLE DIMENSIONS AS FOLLOWS:**

71" overall length, 24-1/2" wide including brackets, and 26-3/8" tall.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a black super durable polyester powder coat.
- End plates are 1/2" x 3" cold rolled steel flatbar.
- Upper and lower crossbars are 2" x 2" square tubing with .065 wall.
- Louvers are constructed of 14 gauge cold rolled steel with four 1/2" round rod vertical supports.
- Louvers are assembled as to allow an unobstructed view of the center high mount stop light.
- Welds are full arc welds, no spot welds.
- Mounting brackets are of 3/16" steel construction.
- Mounting hardware and instructions are included.
- Weight: 83 lbs.



## **WG3 NL "NO LOUVER" WINDOW GRILLE SPECIFICATIONS** **WHITE POWDER FINISH**

### **NO LOUVER WINDOW GRILLE DIMENSIONS AS FOLLOWS:**

59-3/8" overall length, 24-1/2" wide including brackets, and 25-3/8" tall.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a white super durable polyester powder coat.
- End plates are 1/2" x 3" cold rolled steel flatbar.
- Upper and lower crossbars are 2" x 2" square tubing with .065 wall.
- Welds are full arc welds, no spot welds.
- Mounting brackets are of 3/16" steel construction.
- Mounting hardware and instructions are included.
- Weight: 58 lbs.



## **WG3 WINDOW GRILLE SPECIFICATIONS** **WHITE POWDER FINISH**

### **WINDOW GRILLE DIMENSIONS AS FOLLOWS:**

59-3/8" overall length, 24-1/2" wide including brackets, and 25-3/8" tall.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a white super durable polyester powder coat.
- End plates are 1/2" x 3" cold rolled steel flatbar.
- Upper and lower crossbars are 2" x 2" square tubing with .065 wall.
- Louvers are constructed of 14 gauge cold rolled steel with four 1/2" round rod vertical supports.
- Louvers are assembled as to allow an unobstructed view of the center high mount stop light.
- Welds are full arc welds, no spot welds.
- Mounting brackets are of 3/16" steel construction.
- Mounting hardware and instructions are included.
- Weight: 80 lbs.



## **WG3B NL “NO LOUVER” WINDOW GRILLE SPECIFICATIONS** **BLACK POWDER FINISH**

### **NO LOUVER WINDOW GRILLE DIMENSIONS AS FOLLOWS:**

59-3/8" overall length, 24-1/2" wide including brackets, and 25-3/8" tall.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a black super durable polyester powder coat.
- End plates are 1/2" x 3" cold rolled steel flatbar.
- Upper and lower crossbars are 2" x 2" square tubing with .065 wall.
- Welds are full arc welds, no spot welds.
- Mounting brackets are of 3/16" steel construction.
- Mounting hardware and instructions are included.
- Weight: 58 lbs.



## **WG3B WINDOW GRILLE SPECIFICATIONS** **BLACK POWDER FINISH**

### **WINDOW GRILLE DIMENSIONS AS FOLLOWS:**

59-3/8" overall length, 24-1/2" wide including brackets, and 25-3/8" tall.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a black super durable polyester powder coat.
- End plates are 1/2" x 3" cold rolled steel flatbar.
- Upper and lower crossbars are 2" x 2" square tubing with .065 wall.
- Louvers are constructed of 14 gauge cold rolled steel with four 1/2" round rod vertical supports.
- Louvers are assembled as to allow an unobstructed view of the center high mount stop light.
- Welds are full arc welds, no spot welds.
- Mounting brackets are of 3/16" steel construction.
- Mounting hardware and instructions are included.
- Weight: 80 lbs.