

## Fully automatic, unmatched 98.5% recovery



## **Robinair A/C Comparison**

Combining Simple Operation with Superior Accuracy. These machines will test, recover and recharge R-134a automotive AC system quickly and accurately.

Robinair A/C service tools and equipment are sold through distribution partners, resellers and retailers. Visit robinair.com to find a partner near you.



## Industry-leading efficiency and more accurate service





	a 8.			
Features	34288NI	34788NI	34788NI-H	34988NI
<b>ully-Automatic Function:</b> Program to recover, vacuum, leak test and harge without operating panel valves.		×	×	×
<b>utomatic Dye Inject:</b> Gives the user the ability to use the machine to inject UV dye into vehicle's A/C system.				×
utomatic Oil Drain: A display reminds you to empty the graduated ontainer to show the amount of oil to replace.	×	×	×	×
il Inject: Automatically inject oil back into the vehicle's A/C systems.		<b>×</b> *		<b>X</b> **
<b>defrigerant &amp; Oil Database:</b> A/C system capacities for North American market vehicles Dptional – not included with the machine)	Optional	Optional	Optional	Optional
<b>/C System Flush:</b> Flushes a vehicle's A/C system with refrigerant, eliminating any sidual oil or other liquid. (Flushing adapters not included)		×	×	×
ave & print before and after service data: Allows the user to store before and after ervice information by vehicle and print this information to provide to a customer.		×	×	×
isual & Audible Alarm: Notifies the user when service is complete, or if a problem as occurred.		×	×	×
acuum Leak Test: Monitors level after evacuation, informs of possible leak.		×	×	×
u <b>tomatic Air Purge:</b> Eliminates system-damaging air without monitoring gauges r opening valves.	×	×	×	×
u <b>tomatic Refrigerant Refill:</b> Maintains a user-selectable amount of refrigerant an internal vessel and signals when it's time to change supply tank, p monitoring required.		×	×	×
acuum Feature: Defaults to 15 mins, programmable up to 99 mins. "Remaining time" displayed.	×	×	×	×
isplay: Multilingual.	×	×	×	×
efrigerant Charging:	×	<b>X</b> ***	<b>X</b> ***	<b>X</b> ***
<b>efrigerant Management System:</b> Displays refrigerant use and monitors remaining Iter life. Prompts appear when 1/3 of filter life remains.	×	×	×	×
lectric Vehicle: Capable of servicing high voltage electric compressor /C systems.			×	
rinter	Optional	Optional	Optional	×

\* One oil bottle. \*\* Two oil bottles and one UV dye bottle.

ttle. \*\*\* Charge mode from high or low side, or use both sides.

## **Related Service**





Check out the collection of automotive tools we offer.