

Transmission Fluid Exchanger

Robinair's transmission oil exchanger has the vehicle in and out of the service bay in less than 20 minutes!



Our unique approach to exchanging fluid... through the transmission oil dipstick!

- › No rusty fittings to break loose.
- › Easy, convenient, and no damage to other engine components.
- › Exchange oil in the pan before it passes through the transmission filter.
- › It cannot be hooked up backwards (even in cooler line modes).

Three modes of operations dipstick only, cooler line or a combination of the two!

- › Exchange accuracy approximately +/- 1/4 qt.
- › 32-quart supply tank; 34-quart waste tank.
- › Unprecedented one-tenth quart flow metering for adding or subtracting fluid from the pan.
- › Complete set of cooler line adapters for most foreign and domestic vehicles.
- › Works with all types of automatic transmission fluid.
- › Integral performance designed hose and tool compartment with drain.

Industry-leading efficiency and more accurate service

Features

- › Top-off feature. Add or subtract in 1/10 qt. increments.
- › “Low Fluid Alarm” and “Indicator Light” to alert operator.
- › “Drain Waste” feature automatically pumps used fluid from the machine into a waste oil container.
- › “Drain Pan” feature drains the pan for easy filter replacement. No mess.

92500 – Transmission fluid exchanger.

529560 – Replacement Nylon tube.

High intensity LEDs with UV filters make display readable in direct sunlight.

Additional Tool Storage

Flow Meter Monitor Exchange Process. Clear lens acts as a sight glass.

High Capacity Oil Supply Tank

Large pneumatic tires & casters make unit easy to position near vehicle.



Specifications

Electrical	12V DC
Exchange Accuracy	+/- 1/4 qt.
Controls	Microprocessor with digital keypad and LEDs
Fluid Tanks	32 quarts supply (24.6 liters), 34 quarts waste (26.6 liters)
Hoses	91" black & red (Exchange); 76" white transfer tube (Straw)
Fluid Types	Multiple fluid capability.
Adapter Set	Complete set for most applications. Standard adapters for Ford, GM, Chrysler, European, and Universal (covering most Asian imports).
Pump	Positive displacement gear pump, 2 gallons per minute maximum
Weight	158 lbs. (72 kg)
Dimensions	52" H x 33" W x 20" D (132 cm x 84 cm x 51 cm)
Process Time	Depends on mode
Warranty	1 year parts and labor

92001

Automatic Transmission Fluid Diagnostic Pads

Easy, quick way to test automatic transmission fluid to determine when service is necessary. Simply place a few drops of transmission fluid from transmission dipstick onto test pad. Pad will change color indicating condition of transmission fluid. Package contains 100 pads.

