

2007-Current Jeep® Wrangler JK-Neoprene Front Seat Covers 2-door and 4-door (front seats only)

Parts included:



- (1) Front driver's side seat cover - with head rest
- (1) Front passenger's side seat cover - with head rest



PLEASE READ ALL INSTRUCTIONS CAREFULLY BEFORE YOU BEGIN.



Step 1. Slide, and tilt back of seat forward.

Step 2. Remove head rest.



Step 3. Place upper cover over top of seat.
Pull all the way down as shown.

Step 4. The neoprene cover has two holes located on top. Push the fabric down and under plastic head rest lock tabs mounted into top of seat.




Step 5. Fish front flap through gap between the upper and lower seat sections. This is a tight fit. Folding seat forward may help.

Step 6. Pull rear flap tight and attach to the front flap using attached Velcro. Adjust cover for proper fit.



Step 7. Side ABS air bag cover should slipped under cover as shown. Install head rest cover and attach velcro to secure.

Step 8. Place driver's side lower cover onto seat.
Fish rear buckles through gap between the upper and lower seat. This is a tight fit. Folding the seat forward



Step 9. Attach two side hooks to the underside of the seat. The hooks can be attached to and secure point under the seat.

Step 10. Slide front and rear lower straps under seat. Make sure that the front straps are inserted through the front seat adjuster arm to insure proper operation of seat slider. Connect front clip to rear clip and adjust. **DO NOT OVER TIGHTEN!!!**



Step 11. Install the headrest cover.

Note: 2011 and newer headrest covers are longer on the back side and have a Velcro strap on the bottom to secure.

Step 12. Repeat step 1-11 for other side.

