

S3CR04

S3-1 INTERFACE HARNESS FOR 2007-11 CHRYSLER CAN BUS DATA SYSTEM

APPLICATIONS

CHRYSLER	
2011	200
2008-10	300
2008-09	Aspen
2007-10	Sebring
2008-11	Town & Country
DODGE	
2007-11	Avenger
2009-11	Caliber
2008-11	Caravan
2009-11	Challenger
2008-10	Charger
2008-11	Dakota
2008-09	Durango
2011	Durango
2009-10	Journey
2008-09	Magnum
2007-11	Nitro
2009-11	Ram Pickup
JEEP	
2008-10	Commander
2009-11	Compass
2008-11	Grand Cherokee
2008-11	Liberty

Patriot

Wrangler

2009-11

2007-11

INSTALLATION NOTES

This S3CR04 harness is designed for use with the Scosche S3-1 interface. It allows you to replace your Factory OEM stereo while retaining the Factory Timed Accessory output as well as retaining Factory Digital Premium audio systems. The S3CR04/S3-1 combination will also allow you to retain Factory steering wheel controls if vehicle is equipped. Please review this information for specific installation in Chrysler, Dodge and Jeep vehicles. For steering wheel control information, consult the S3-1 interface installation instructions.

S3CR04/S3-1 FEATURES

- Keeps Factory CAN Bus data system intact for Diagnostic purposes.
- Provides Data-controlled +12V Accessory Output for Aftermaket stereo
- Retains Factory Premium Audio systems (Boston Acc) in a 2CH format. (See note below)

Data-controlled:

- Parking Brake Trigger
- Reverse Trigger
- Vehicle Speed Sense (VSS)
- Illumination Output

PREMIUM ALPINE, BOSTON and INFINITY SYSTEMS

These factory amplified sound systems are driven and digitally controlled by a single set of Left/Right input channels only. The Aftermarket radio does not have the ability to control Fade on these types of systems, therefore NO front/rear fader control is available. The fader is set to center by interface control software.

WIRING INSTRUCTIONS

- Disconnect the Negative battery cable from the battery to avoid short circuits.
- 2. Remove and unplug Factory stereo.
- Match and connect the Power/ground wires from the S3-1 Vehicle specific harness to the wires from your stereo. The color codes on the Scosche harness are designed to match most Aftermarket stereos.
 - Take note that some of the wires for your new stereo come from the S3-1 interface box itself and not the vehicle connectors.
- Wire the S3CR04 speaker leads directly to the speaker wires from the new stereo. (Diagram on reverse)
- 5. Tape any unused wiring to prevent short circuits.
- Connect all harnessed between S3-1, Vehicle and Aftermarket stereo.



S3-1 INTERFACE HARNESS FOR 2007-UP CHRYSLER CAN BUS DATA SYSTEM

WIRE COLOR CODES

White = Left Front Positive (LF+) = Right Front Positive (RF+) Grav Gray/Black = Right Front Negative (RF-) White/Black = Left Front Negative (LF-) = Left Rear Positive (LR+) Violet = Right Rear Positive (RR+) Green Violet/Black = Right Rear Negative (RR-) Green/Black = Left Rear Negative (LR-) Black = Chassis Ground Orange = Illumination Yellow = +12V Constant Power Blue/White = +12 Remote Output (Amp, Red = +12V Accessory / R.A.P output radio on signal)

Blue = +12V Power Antenna

NAVIGATION CONNECTIONS:

Violet/White = VSS Vehicle speed pulse signal

Red/White = Reverse light trigger (+12V when in reverse gear)
Yellow/Black = Parking Brake trigger (-12V when park brake ON)
Orange/White = Auto illumination (Data controlled lighting)

NOTE: The RED Accessory output wire from the S3-1 interface is rated at 10A Max output for most Aftermarket headunit demands. We do NOT recommended connecting additional +12V switched accessories to this output source as that may cause damage to the S3-1 module itself. If 10A output is not sufficient, then a relay is needed. (Relay not included)

NOTE: Illimination & Auto illumination outputs are designed for headunit connections only.

S3CR04 WIRING DIAGRAM

