

### 1 Identification

· Product identifier

· Trade name: 13003-13023 Clear Aerosol

· Article number: 13003, 13013, 13023

· Application of the substance / the mixture Coating

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier: SEM Products Inc.

#### 2 Hazard(s) identification

· Classification of the substance or mixture





GHS02 GHS04 Flame, Gas cylinder

Flam. Aerosol 1 H222 Extremely flammable aerosol.



GHS04 Gas cylinder

Press. Gas H280 Contains gas under pressure; may explode if heated.



#### GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



#### GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction. STOT SE 3 H336 May cause drowsiness or dizziness.

· Label elements

· GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). (Contd. on page 2)

n page 2



Trade name: 13003-13023 Clear Aerosol

(Contd. of page 1)

#### · Hazard pictograms









GHS02

GHS04

GHS07

· Signal word Danger

#### · Hazard-determining components of labeling:

toluene

acetone

4-methylpentan-2-one

butanone

*bis*(1,2,2,6,6-Pentamethyl-4-piperidinyl) sebacate

#### · Hazard statements

H222 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H361 Suspected of damaging fertility or the unborn child.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

| atements  |  |
|---|--|
| Obtain special instructions before use.   |  |
| Do not handle until all safety precautions have been read and understood.                         |  |
| Keep away from heat/sparks/open flames/hot surfaces No smoking.                                   |  |
| Do not spray on an open flame or other ignition source.   |  |
| Pressurized container: Do not pierce or burn, even after use.                                     |  |
| Do not breathe dust/fume/gas/mist/vapors/spray.   |  |
| Wash thoroughly after handling.   |  |
| Use only outdoors or in a well-ventilated area.   |  |
| Contaminated work clothing must not be allowed out of the workplace.                              |  |
| Wear protective gloves/protective clothing/eye protection/face protection.                        |  |
| If on skin: Wash with plenty of water.  |  |
| IF INHALED: Remove person to fresh air and keep comfortable for breathing.                        |  |
| 88 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present |  |
| and easy to do. Continue rinsing.   |  |
|   |  |
| Call a poison center/doctor if you feel unwell.   |  |
| Specific treatment (see on this label).   |  |
|   |  |
|   |  |
|   |  |
|   |  |
| Wash contaminated clothing before reuse.  |  |
| Store in a well-ventilated place. Keep container tightly closed.                                  |  |
| Store locked up.  |  |
| Protect from sunlight. Store in a well-ventilated place.  |  |
|   |  |
| (Contd. on page 3)  |  |
|   | Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. If on skin: Wash with plenty of water. IF INHALED: Remove person to fresh air and keep comfortable for breathing. 38 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Specific treatment (see on this label). Get medical advice/attention if you feel unwell. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Wash contaminated clothing before reuse. Store in a well-ventilated place. Keep container tightly closed. Store locked up. |



Trade name: 13003-13023 Clear Aerosol

(Contd. of page 2)

P501

Dispose of contents/container in accordance with local/regional/national/international

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 2

Fire = 4

Reactivity = 3

· HMIS-ratings (scale 0 - 4)



2 Health = 2

Fire = 4

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

#### 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description:

Mixture: consisting of the following components.

Weight percentages

| · Dangerous components: |                                 |         |
|-------------------------|---------------------------------|---------|
| 67-64-1                 | acetone                         | 40-60%  |
| 74-98-6                 | propane                         | 13-30%  |
| 108-88-3                |                                 | ≥7-<10% |
|                         | isobutyl acetate                | ≥7-<10% |
|                         | 4-methylpentan-2-one            | 5-7%    |
|                         | butanone                        | 1.5-5%  |
|                         | 2-methoxy-1-methylethyl acetate | 1.5-5%  |
|                         | ethyl 3-ethoxypropionate        | 1-1.5%  |
| 2807-30-9               | 2-(propyloxy)ethanol            | 1-1.5%  |

#### 4 First-aid measures

- · Description of first aid measures
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

*In case of unconsciousness place patient stably in side position for transportation.* 

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 4)



Trade name: 13003-13023 Clear Aerosol

(Contd. of page 3)

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

#### 5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

#### 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- · Environmental precautions: Do not allow to enter sewers/surface or ground water.
- · Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

| 67-64-1 acetone         |                     | 200 ppm             |
|-------------------------|---------------------|---------------------|
| 74-98-6 propane         |                     | 5500* ppn           |
| 108-88-3 toluene        |                     | 67 ppm              |
| 110-19-0 isobutyl aceta | ite                 | 450 ppm             |
| 108-10-1 4-methylpente  | an-2-one            | 75 ppm              |
| 78-93-3 butanone        |                     | 200 ppm             |
| 108-65-6 2-methoxy-1-   | methylethyl acetate | 50 ppm              |
| 763-69-9 ethyl 3-ethoxy | propionate          | 1.6 ppm             |
| 2807-30-9 2-(propyloxy) | ethanol             | 2.2 ppm             |
| 111-76-2 2-butoxyetha   | nol                 | 60 ppm              |
| 25322-68-3 Polyethylene | glycol              | $30 \text{ mg/m}^3$ |
| PAC-2:                  |                     |                     |
| 67-64-1 acetone         |                     | 3200* ppm           |
| 74-98-6 propane         |                     | 17000** ppn         |
| 108-88-3 toluene        |                     | 560 ppm             |
| 110-19-0 isobutyl aceta | ite                 | 1300* ppm           |
| 108-10-1 4-methylpente  | an-2-one            | 500 ppm             |
| 78-93-3 butanone        |                     | 2700* ppm           |
| 108-65-6 2-methoxy-1-   | methylethyl acetate | 1,000 ppm           |



Trade name: 13003-13023 Clear Aerosol

|            |                                 | (Contd. of page 4)     |
|------------|---------------------------------|------------------------|
| 763-69-9   | ethyl 3-ethoxypropionate        | 18 ppm                 |
| 2807-30-9  | 2-(propyloxy)ethanol            | 24 ppm                 |
| 111-76-2   | 2-butoxyethanol                 | 120 ppm                |
| 25322-68-3 | Polyethylene glycol             | $1,300 \text{ mg/m}^3$ |
| · PAC-3:   |                                 |                        |
| 67-64-1    | acetone                         | 5700* ppm              |
| 74-98-6    | propane                         | 33000*** ppm           |
| 108-88-3   | toluene                         | 3700* ppm              |
| 110-19-0   | isobutyl acetate                | 7500** ppm             |
| 108-10-1   | 4-methylpentan-2-one            | 3000* ppm              |
| 78-93-3    | butanone                        | 4000* ppm              |
| 108-65-6   | 2-methoxy-1-methylethyl acetate | 5000* ppm              |
| 763-69-9   | ethyl 3-ethoxypropionate        | 110 ppm                |
| 2807-30-9  | 2-(propyloxy)ethanol            | 140 ppm                |
| 111-76-2   | 2-butoxyethanol                 | 700 ppm                |
| 25322-68-3 | Polyethylene glycol             | $7,700 \text{ mg/m}^3$ |

#### 7 Handling and storage

- · Handling:
- · Precautions for safe handling No special measures required.
- Information about protection against explosions and fires:

Do not spray on a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurized containers.

- Information about storage in one common storage facility: Store away from oxidizing agents.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · **Specific end use(s)** No further relevant information available.

#### 8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

| 110 0000 | time, the cone constituents have no mine in our conformer times. |
|----------|--|
| 67-64-   | 1 acetone  |
| PEL      | Long-term value: 2400 mg/m³, 1000 ppm                            |

(Contd. on page 6)



Trade name: 13003-13023 Clear Aerosol

|              |   | (Contd. of pa |
|--------------|---|---------------|
| REL          | Long-term value: 590 mg/m³, 250 ppm   |               |
| TLV          | Short-term value: 1187 mg/m³, 500 ppm<br>Long-term value: 594 mg/m³, 250 ppm<br>BEI           |               |
| <i>74-98</i> | -6 propane  |               |
| PEL          | Long-term value: 1800 mg/m³, 1000 ppm   |               |
| REL          | Long-term value: 1800 mg/m³, 1000 ppm   |               |
| TLV          | refer to Appendix F inTLVs&BEIs book; D, EX   |               |
|              | 8-3 toluene   |               |
| PEL          | Long-term value: 200 ppm<br>Ceiling limit value: 300; 500* ppm<br>*10-min peak per 8-hr shift |               |
| REL          | Short-term value: 560 mg/m³, 150 ppm<br>Long-term value: 375 mg/m³, 100 ppm                   |               |
| TLV          | Long-term value: 75 mg/m³, 20 ppm<br>BEI  |               |
| 110-1        | 9-0 isobutyl acetate  |               |
| PEL          | Long-term value: 700 mg/m³, 150 ppm   |               |
| REL          | Long-term value: 700 mg/m³, 150 ppm   |               |
| TLV          | Short-term value: 712 mg/m³, 150 ppm<br>Long-term value: 238 mg/m³, 50 ppm                    |               |
| 108-1        | 0-1 4-methylpentan-2-one  |               |
| PEL          | Long-term value: 410 mg/m³, 100 ppm   |               |
| REL          | Short-term value: 300 mg/m³, 75 ppm<br>Long-term value: 205 mg/m³, 50 ppm                     |               |
| TLV          | Short-term value: 307 mg/m³, 75 ppm<br>Long-term value: 82 mg/m³, 20 ppm<br>BEI               |               |
| <i>78-93</i> | -3 butanone   |               |
| PEL          | Long-term value: 590 mg/m³, 200 ppm   |               |
| REL          | Short-term value: 885 mg/m³, 300 ppm<br>Long-term value: 590 mg/m³, 200 ppm                   |               |
| TLV          | Short-term value: 885 mg/m³, 300 ppm<br>Long-term value: 590 mg/m³, 200 ppm<br>BEI            |               |
| 108-6        | 5-6 2-methoxy-1-methylethyl acetate   |               |
| WEEL         | L Long-term value: 50 ppm   |               |
| Ingred       | dients with biological limit values:  |               |
|              | -1 acetone  |               |
|              | 50 mg/L   |               |
|              | Medium: urine   |               |
|              | Time: end of shift  |               |
| F            | Parameter: Acetone (nonspecific)  |               |



Trade name: 13003-13023 Clear Aerosol

(Contd. of page 6)

#### 108-88-3 toluene

BEI 0.02 mg/L

Medium: blood

Time: prior to last shift of workweek

Parameter: Toluene

0.03 mg/LMedium: urine Time: end of shift Parameter: Toluene

0.3 mg/g creatinine Medium: urine Time: end of shift

Parameter: o-Cresol with hydrolysis (background)

#### 108-10-1 4-methylpentan-2-one

#### BEI 1 mg/L

Medium: urine *Time: end of shift* Parameter: MIBK

#### 78-93-3 butanone

#### BEI 2 mg/L

Medium: urine Time: end of shift Parameter: MEK

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

#### Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

#### · Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

#### Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 8)



Trade name: 13003-13023 Clear Aerosol

(Contd. of page 7)

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

• **Eye protection:** Safety glasses



Tightly sealed goggles

| Information on basic physical and    | chemical properties                                      |
|--------------------------------------|--|
| General Information                  | enemical properties                                      |
| Appearance:                          |  |
| Form:                                | Aerosol  |
| Color:                               | According to product specification                       |
| Odor:                                | Characteristic   |
| Odor threshold:                      | Not determined.  |
| pH-value:                            | Not determined.  |
| Change in condition                  |  |
| Melting point/Melting range:         | Undetermined.  |
| Boiling point/Boiling range:         | 55.8-56.6 °C   |
| Flash point:                         | -97 °C   |
| Flammability (solid, gaseous):       | Not applicable.  |
| Ignition temperature:                | 405 °C   |
| Decomposition temperature:           | Not determined.  |
| Auto igniting:                       | Product is not selfigniting.                             |
| Danger of explosion:                 | In use, may form flammable/explosive vapour-air mixture. |
| Explosion limits:                    |  |
| Lower:                               | 1.7 Vol %  |
| Upper:                               | 13 Vol %   |
| Vapor pressure at 20 °C:             | 8,300 hPa  |
| Density at 20 °C:                    | $0.75341 \text{ g/cm}^3$                                 |
| Relative density                     | Not determined.  |
| Vapor density                        | Not determined.  |
| Evaporation rate                     | Not applicable.  |
| Solubility in / Miscibility with     |  |
| Water:                               | Not miscible or difficult to mix.                        |
| Partition coefficient (n-octanol/wat | t <b>er):</b> Not determined.                            |
| Viscosity:                           |  |
| Dynamic:                             | Not determined.  |
| Kinematic:                           | Not determined.  |

(Contd. on page 9)



Trade name: 13003-13023 Clear Aerosol

 \* Solvent content:

 Organic solvents:
 92.0 %

 VOC content:
 51.64 %

 632.8 g/l / 5.28 lb/gl

 Solids content:
 8.0 %

 • Other information
 No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products:

Nitrogen oxides Hydrocarbons

Carbon monoxide and carbon dioxide

#### 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

| · LD/LC50 values that are relevant for classification: |                  |                       |  |
|--|------------------|-----------------------|--|
| 108-88-3 t   | 108-88-3 toluene |                       |  |
| Oral   |                  | 5,000 mg/kg (rat)     |  |
| Dermal   | LD50             | 12,124 mg/kg (rabbit) |  |
| Inhalative   | LC50/4 h         | 5,320 mg/l (mouse)    |  |

- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization: Sensitization possible through skin contact.
- Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

| · IARC (In | ternational Agency for Research on Cancer) |    |
|------------|--|----|
| 108-88-3   | toluene                                    | 3  |
| 108-10-1   | 4-methylpentan-2-one                       | 2B |
| 111-76-2   | 2-butoxyethanol                            | 3  |
| · NTP (Na  | tional Toxicology Program)                 |    |
| None of t  | he ingredients is listed                   |    |

(Contd. on page 10)



Trade name: 13003-13023 Clear Aerosol

(Contd. of page 9)

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

#### 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

#### 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

#### 14 Transport information

- · UN-Number
- · DOT, ADR, IMDG, IATA

UN1950

· UN proper shipping name

DOT

 Aerosols, flammable

 ADR

 1950 Aerosols
 AEROSOLS
 IATA
 AEROSOLS, flammable

- · Transport hazard class(es)
- $\cdot DOT$



· Class 2.1

(Contd. on page 11)



Trade name: 13003-13023 Clear Aerosol

|  | (Contd. of page  |
|--|--|
| Label                                    | 2.1  |
| ADR                                      |  |
|  |  |
|  |  |
|  |  |
| Class                                    | 2 5F Gases   |
| Label                                    | 2.1  |
| IMDG, IATA                               |  |
|  |  |
|  |  |
|  |  |
| Class                                    | 2.1  |
| Label                                    | 2.1  |
| Packing group                            |  |
| DOT, ADR, IMDG, IATA                     | Void   |
| Environmental hazards:                   | M.   |
| Marine pollutant:                        | No   |
| Special precautions for user EMS Number: | Warning: Gases<br>F-D,S-U  |
| Stowage Code                             | SW1 Protected from sources of heat.  |
| 3  | SW22 For AEROSOLS with a maximum capacity of 1 litr  |
|  | Category A. For AEROSOLS with a capacity above 1 litr  |
|  | Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.  |
| Segregation Code                         | SG69 For AEROSOLS with a maximum capacity of 1 litr  |
|  | Segregation as for class 9. Stow "separated from" class 1 except f   |
|  | division 1.4. For AEROSOLS with a capacity above 1 litr<br>Segregation as for the appropriate subdivision of class 2. F. |
|  | WASTE AEROSOLS: Segregation as for the appropriate subdivision   |
|  | of class 2.  |
| Transport in bulk according to Annex     |  |
| MARPOL73/78 and the IBC Code             | Not applicable.  |
| Transport/Additional information:        |  |
| DOT                                      | 0  |
| Quantity limitations                     | On passenger aircraft/rail: 75 kg<br>On cargo aircraft only: 150 kg  |
| Remarks                                  | ORM-D CFR49 173.150,156,306  |
| ADR                                      |  |
| Excepted quantities (EQ)                 | Code: E0   |
|  | Not permitted as Excepted Quantity   |
| IMDG                                     |  |
| Limited quantities (LQ)                  | 1L   |



Trade name: 13003-13023 Clear Aerosol

(Contd. of page 11)

| · Excepted quantities (EQ) | Code: E0 Not permitted as Excepted Quantity | .ge 11) |
|----------------------------|---|---------|
| · UN ''Model Regulation'': | UN 1950 AEROSOLS, 2.1                       |         |

#### 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara

#### · Section 355 (extremely hazardous substances):

None of the ingredient is listed.

#### · Section 313 (Specific toxic chemical listings):

108-88-3 toluene

108-10-1 4-methylpentan-2-one

78-93-3 butanone

111-76-2 2-butoxyethanol

#### · TSCA (Toxic Substances Control Act):

| 67-64-1 ac | etone |
|------------|-------|
|------------|-------|

74-98-6 propane

108-88-3 toluene

110-19-0 isobutyl acetate

108-10-1 4-methylpentan-2-one

78-93-3 butanone

108-65-6 2-methoxy-1-methylethyl acetate

763-69-9 ethyl 3-ethoxypropionate

2807-30-9 2-(propyloxy)ethanol

41556-26-7 bis(1,2,2,6,6-Pentamethyl-4-piperidinyl) sebacate

104810-48-2 poly(oxy-1,2-ethanediyl),  $\alpha$ -[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-ω-hydroxy-

104810-47-1 poly(oxy-1,2-ethanediyl),  $\alpha$ -[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]- $I-oxopropy[]-\omega-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1$ oxopropoxy]-

111-76-2 2-butoxyethanol

9038-95-3 OXIRANE, ME, POLYMER

82919-37-7 *Methyl* (1,2,2,6,6,- pentamethyl-4-piperidinyl) sebacate

25322-68-3 Polyethylene glycol

106-79-6 Dimethyl sebacate(Impurity)

2403-89-6 4-Piperidinol, 1,2,2,6,6 pentamethyl- (Impurity)

· Proposition 65

#### · Chemicals known to cause cancer:

108-10-1 4-methylpentan-2-one

#### · Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

(Contd. on page 13)



Trade name: 13003-13023 Clear Aerosol

(Contd. of page 12) · Chemicals known to cause reproductive toxicity for males: None of the ingredients is listed. · Chemicals known to cause developmental toxicity: 108-88-3 toluene 108-10-1 4-methylpentan-2-one · Cancerogenity categories · EPA (Environmental Protection Agency) 67-64-1 acetone 108-88-3 toluene II 108-10-1 4-methylpentan-2-one 78-93-3 butanone 111-76-2 2-butoxyethanol NLTLV (Threshold Limit Value established by ACGIH) 67-64-1 acetone A4108-88-3 toluene A4111-76-2 2-butoxyethanol A3· NIOSH-Ca (National Institute for Occupational Safety and Health) None of the ingredients is listed.

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms









GHS02

GHS04

GHS07

07 GH

· Signal word Danger

· Hazard-determining components of labeling:

toluene

acetone

4-methylpentan-2-one

butanone

bis(1,2,2,6,6-Pentamethyl-4-piperidinyl) sebacate

#### · Hazard statements

H222 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H361 Suspected of damaging fertility or the unborn child.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

#### · Precautionary statements

*P201 Obtain special instructions before use.* 

P202 Do not handle until all safety precautions have been read and understood. P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

(Contd. on page 14)



Trade name: 13003-13023 Clear Aerosol

|                 | (Contd. of page 13)  |
|-----------------|--|
| P211            | Do not spray on an open flame or other ignition source.  |
| P251            | Pressurized container: Do not pierce or burn, even after use.                                      |
| P260            | Do not breathe dust/fume/gas/mist/vapors/spray.  |
| P264            |  |
|                 | Wash thoroughly after handling.  |
| P271            | Use only outdoors or in a well-ventilated area.  |
| P272            | Contaminated work clothing must not be allowed out of the workplace.                               |
| P280            | Wear protective gloves/protective clothing/eye protection/face protection.                         |
| P302+P352       | If on skin: Wash with plenty of water.   |
| P304+P340       | IF INHALED: Remove person to fresh air and keep comfortable for breathing.                         |
| P305+P351+P     | 338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present |
|                 | and easy to do. Continue rinsing.  |
| P308+P313       | IF exposed or concerned: Get medical advice/attention.   |
| P312            | Call a poison center/doctor if you feel unwell.  |
| P321            | Specific treatment (see on this label).  |
| P314            | Get medical advice/attention if you feel unwell.   |
| P362+P364       | Take off contaminated clothing and wash it before reuse.   |
| P333+P313       | If skin irritation or rash occurs: Get medical advice/attention.                                   |
| P337+P313       | If eye irritation persists: Get medical advice/attention.  |
| P363            | Wash contaminated clothing before reuse.   |
| P403+P233       | Store in a well-ventilated place. Keep container tightly closed.                                   |
| P405            | Store locked up.   |
| P410+P403       | Protect from sunlight. Store in a well-ventilated place.   |
| P410+P412       | Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.                         |
| P501            | Dispose of contents/container in accordance with local/regional/national/international             |
|                 | regulations.   |
| Chemical safety | w assessment: A Chemical Safety Assessment has not been carried out.                               |
| 0 2             |  |

#### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact: Rita Joiner
- · Date of preparation / last revision 03/14/2018 / 14
- · Abbreviations and acronyms:

RID: (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

 ${\it HMIS: Hazardous\ Materials\ Identification\ System\ (USA)}$ 

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

(Contd. on page 15)



#### Trade name: 13003-13023 Clear Aerosol

(Contd. of page 14)

TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit BEI: Biological Exposure Limit Flam. Aerosol 1: Aerosols – Category 1

Press. Gas: Gases under pressure – Compressed gas Skin Irrit 2: Skin corrosion/irritation – Category 2

Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Skin Sens. 1: Skin sensitisation – Category 1
Carc. 2: Carcinogenicity – Category 2
Repr. 2: Reproductive toxicity – Category 2
STOT SE 3: Specific target organ toxicity (single 6)

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

\* \* Data compared to the previous version altered.

JSA -