

## 1 Identification

· **Product identifier**

· **Trade name:** 15003-15893 Color Coat Aerosol

· **Article number:**

15003, 15013, 15023, 15033, 15043, 15053, 15063, 15083, 15093, 15103, 15113, 15123, 15133, 15143, 15163, 15173, 15183, 15213, 15223, 15233, 15243, 15253, 15273, 15283, 15293, 15303, 15313, 15323, 15353, 15363, 15373, 15393, 15413, 15423, 15433, 15453, 15463, 15473, 15483, 15493, 15603, 15643, 15673, 15703, 15713, 15723, 15753, 15763, 15773, 15783, 15793, 15803, 15813, 15823, 15833, 15843, 15853, 15863, 15873, 15883, 15893

· **Application of the substance / the mixture** Coating

· **Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**

SEM Products Inc.

## 2 Hazard(s) identification

· **Classification of the substance or mixture**



GHS02 GHS04 Flame, Gas cylinder

Flam. Aerosol 1 H222 Extremely flammable aerosol.



GHS04 Gas cylinder

Press. Gas H280 Contains gas under pressure; may explode if heated.



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

(Contd. on page 2)

USA

Trade name: 15003-15893 Color Coat Aerosol

(Contd. of page 1)

· **Label elements**

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS04 GHS07 GHS08

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

*toluene*

*acetone*

*4-methylpentan-2-one*

*ethylbenzene*

· **Hazard statements**

*H222 Extremely flammable aerosol.*

*H280 Contains gas under pressure; may explode if heated.*

*H315 Causes skin irritation.*

*H319 Causes serious eye irritation.*

*H351 Suspected of causing cancer.*

*H361 Suspected of damaging fertility or the unborn child.*

*H336 May cause drowsiness or dizziness.*

*H373 May cause damage to organs through prolonged or repeated exposure.*

*H304 May be fatal if swallowed and enters airways.*

· **Precautionary statements**

*P201 Obtain special instructions before use.*

*P202 Do not handle until all safety precautions have been read and understood.*

*P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.*

*P211 Do not spray on an open flame or other ignition source.*

*P251 Pressurized container: Do not pierce or burn, even after use.*

*P260 Do not breathe dust/fume/gas/mist/vapors/spray.*

*P264 Wash thoroughly after handling.*

*P271 Use only outdoors or in a well-ventilated area.*

*P280 Wear protective gloves/protective clothing/eye protection/face protection.*

*P301+P310 If swallowed: Immediately call a poison center/doctor.*

*P321 Specific treatment (see on this label).*

*P331 Do NOT induce vomiting.*

*P302+P352 If on skin: Wash with plenty of water.*

*P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.*

*P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.*

*P308+P313 IF exposed or concerned: Get medical advice/attention.*

*P312 Call a poison center/doctor if you feel unwell.*

*P314 Get medical advice/attention if you feel unwell.*

*P362+P364 Take off contaminated clothing and wash it before reuse.*

*P332+P313 If skin irritation occurs: Get medical advice/attention.*

*P337+P313 If eye irritation persists: Get medical advice/attention.*

*P403+P233 Store in a well-ventilated place. Keep container tightly closed.*

*P405 Store locked up.*

*P410+P403 Protect from sunlight. Store in a well-ventilated place.*

(Contd. on page 3)

Trade name: 15003-15893 Color Coat Aerosol

(Contd. of page 2)

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- Classification system:
- NFPA ratings (scale 0 - 4)



- HMIS-ratings (scale 0 - 4)



- Other hazards
- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.

### 3 Composition/information on ingredients

- Chemical characterization: Mixtures
- Description:  
Mixture: consisting of the following components.  
Weight percentages

· Dangerous components:

67-64-1	acetone	30-40%
68476-86-8	Petroleum gases, liquefied, sweetened	13-30%
108-88-3	toluene	10-13%
110-19-0	isobutyl acetate	1.5-5%
108-10-1	4-methylpentan-2-one	1.5-5%
78-93-3	butanone	1.5-5%
763-69-9	ethyl 3-ethoxypropionate	1.5-5%
108-65-6	2-methoxy-1-methylethyl acetate	1-1.5%
2807-30-9	2-(propyloxy)ethanol	1-1.5%

### 4 First-aid measures

- Description of first aid measures
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact:  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 4)



Trade name: 15003-15893 Color Coat Aerosol

(Contd. of page 3)

- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

### 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

### 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· **PAC-1:**

67-64-1	acetone	200 ppm
108-88-3	toluene	67 ppm
110-19-0	isobutyl acetate	450 ppm
108-10-1	4-methylpentan-2-one	75 ppm
78-93-3	butanone	200 ppm
763-69-9	ethyl 3-ethoxypropionate	1.6 ppm
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
2807-30-9	2-(propyloxy)ethanol	2.2 ppm
13463-67-7	titanium dioxide	30 mg/m <sup>3</sup>
1333-86-4	Carbon black	9 mg/m <sup>3</sup>
112926-00-8	precipitated Silica (Silica-Amorphous)	18 mg/m <sup>3</sup>
1330-20-7	xylene	130 ppm
67-56-1	methanol	530 ppm
100-41-4	ethylbenzene	33 ppm
108-83-8	2,6-dimethylheptan-4-one	75 ppm

· **PAC-2:**

67-64-1	acetone	3200* ppm
108-88-3	toluene	560 ppm
110-19-0	isobutyl acetate	1300* ppm

(Contd. on page 5)



Trade name: 15003-15893 Color Coat Aerosol

(Contd. of page 4)

108-10-1	4-methylpentan-2-one	500 ppm
78-93-3	butanone	2700* ppm
763-69-9	ethyl 3-ethoxypropionate	18 ppm
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm
2807-30-9	2-(propyloxy)ethanol	24 ppm
13463-67-7	titanium dioxide	330 mg/m <sup>3</sup>
1333-86-4	Carbon black	99 mg/m <sup>3</sup>
112926-00-8	precipitated Silica (Silica-Amorphous)	200 mg/m <sup>3</sup>
1330-20-7	xylene	920* ppm
67-56-1	methanol	2,100 ppm
100-41-4	ethylbenzene	1100* ppm
108-83-8	2,6-dimethylheptan-4-one	330 ppm

· **PAC-3:**

67-64-1	acetone	5700* ppm
108-88-3	toluene	3700* ppm
110-19-0	isobutyl acetate	7500** ppm
108-10-1	4-methylpentan-2-one	3000* ppm
78-93-3	butanone	4000* ppm
763-69-9	ethyl 3-ethoxypropionate	110 ppm
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm
2807-30-9	2-(propyloxy)ethanol	140 ppm
13463-67-7	titanium dioxide	2,000 mg/m <sup>3</sup>
1333-86-4	Carbon black	590 mg/m <sup>3</sup>
112926-00-8	precipitated Silica (Silica-Amorphous)	1,200 mg/m <sup>3</sup>
1330-20-7	xylene	2500* ppm
67-56-1	methanol	7200* ppm
100-41-4	ethylbenzene	1800* ppm
108-83-8	2,6-dimethylheptan-4-one	2000* ppm

**7 Handling and storage**

· **Handling:**

· **Precautions for safe handling** No special measures required.

· **Information about protection against explosions and fires:**

Do not spray on a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

· **Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:**

Observe official regulations on storing packagings with pressurized containers.

· **Information about storage in one common storage facility:** Not required.

· **Further information about storage conditions:** Keep receptacle tightly sealed.

(Contd. on page 6)



Trade name: 15003-15893 Color Coat Aerosol

(Contd. of page 5)

· *Specific end use(s)* No further relevant information available.

**8 Exposure controls/personal protection**

· *Additional information about design of technical systems:* No further data; see item 7.

· *Control parameters*

· *Components with limit values that require monitoring at the workplace:*

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

**67-64-1 acetone**

PEL	Long-term value: 2400 mg/m <sup>3</sup> , 1000 ppm
REL	Long-term value: 590 mg/m <sup>3</sup> , 250 ppm
TLV	Short-term value: 1187 mg/m <sup>3</sup> , 500 ppm Long-term value: 594 mg/m <sup>3</sup> , 250 ppm
BEI	

**108-88-3 toluene**

PEL	Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift
REL	Short-term value: 560 mg/m <sup>3</sup> , 150 ppm Long-term value: 375 mg/m <sup>3</sup> , 100 ppm
TLV	Long-term value: 75 mg/m <sup>3</sup> , 20 ppm
BEI	

**110-19-0 isobutyl acetate**

PEL	Long-term value: 700 mg/m <sup>3</sup> , 150 ppm
REL	Long-term value: 700 mg/m <sup>3</sup> , 150 ppm
TLV	Short-term value: 712 mg/m <sup>3</sup> , 150 ppm Long-term value: 238 mg/m <sup>3</sup> , 50 ppm

**108-10-1 4-methylpentan-2-one**

PEL	Long-term value: 410 mg/m <sup>3</sup> , 100 ppm
REL	Short-term value: 300 mg/m <sup>3</sup> , 75 ppm Long-term value: 205 mg/m <sup>3</sup> , 50 ppm
TLV	Short-term value: 307 mg/m <sup>3</sup> , 75 ppm Long-term value: 82 mg/m <sup>3</sup> , 20 ppm
BEI	

**78-93-3 butanone**

PEL	Long-term value: 590 mg/m <sup>3</sup> , 200 ppm
REL	Short-term value: 885 mg/m <sup>3</sup> , 300 ppm Long-term value: 590 mg/m <sup>3</sup> , 200 ppm
TLV	Short-term value: 885 mg/m <sup>3</sup> , 300 ppm Long-term value: 590 mg/m <sup>3</sup> , 200 ppm
BEI	

**108-65-6 2-methoxy-1-methylethyl acetate**

WEEL	Long-term value: 50 ppm
------	-------------------------

(Contd. on page 7)

Trade name: 15003-15893 Color Coat Aerosol

(Contd. of page 6)

**· Ingredients with biological limit values:**

**67-64-1 acetone**

BEI 50 mg/L  
Medium: urine  
Time: end of shift  
Parameter: Acetone (nonspecific)

**108-88-3 toluene**

BEI 0.02 mg/L  
Medium: blood  
Time: prior to last shift of workweek  
Parameter: Toluene

0.03 mg/L  
Medium: urine  
Time: end of shift  
Parameter: Toluene

0.3 mg/g creatinine  
Medium: urine  
Time: end of shift  
Parameter: o-Cresol with hydrolysis (background)

**108-10-1 4-methylpentan-2-one**

BEI 1 mg/L  
Medium: urine  
Time: end of shift  
Parameter: MIBK

**78-93-3 butanone**

BEI 2 mg/L  
Medium: urine  
Time: end of shift  
Parameter: MEK

**· Additional information:** The lists that were valid during the creation were used as basis.

**· Exposure controls**

**· Personal protective equipment:**

**· General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.
- Avoid contact with the eyes and skin.

**· Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

**· Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Contd. on page 8)

Trade name: 15003-15893 Color Coat Aerosol

(Contd. of page 7)

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**

Safety glasses



Tightly sealed goggles

**9 Physical and chemical properties**

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

· <b>Form:</b>	Aerosol
· <b>Color:</b>	According to product specification
· <b>Odor:</b>	Characteristic
· <b>Odor threshold:</b>	Not determined.

· **pH-value:** Not determined.

· **Change in condition**

· <b>Melting point/Melting range:</b>	Undetermined.
· <b>Boiling point/Boiling range:</b>	55.8-56.6 °C

· **Flash point:** -103 °C

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:** 465 °C

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** In use, may form flammable/explosive vapour-air mixture.

· **Explosion limits:**

· <b>Lower:</b>	1.2 Vol %
· <b>Upper:</b>	13 Vol %

· **Vapor pressure at 20 °C:** 233 hPa

· <b>Density at 20 °C:</b>	0.74862 g/cm <sup>3</sup>
· <b>Relative density</b>	Not determined.
· <b>Vapor density</b>	Not determined.
· <b>Evaporation rate</b>	Not applicable.

· **Solubility in / Miscibility with**

· **Water:** Not miscible or difficult to mix.

(Contd. on page 9)





Trade name: 15003-15893 Color Coat Aerosol

(Contd. of page 8)

- **Partition coefficient (n-octanol/water):** Not determined.
- **Viscosity:**
  - Dynamic:* Not determined.
  - Kinematic:* Not determined.
- **Solvent content:**
  - Organic solvents:* 89.9 %
  - Water:* 0.0 %
  - VOC content:* 54.73 %  
614.8 g/l / 5.13 lb/gl
- **Solids content:** 10.2 %
- **Other information** No further relevant information available.

### 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

### 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

**108-88-3 toluene**

Oral	LD50	5,000 mg/kg (rat)
Dermal	LD50	12,124 mg/kg (rabbit)
Inhalative	LC50/4 h	5,320 mg/l (mouse)

- **Primary irritant effect:**
  - **on the skin:** Irritant to skin and mucous membranes.
  - **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**  
The product shows the following dangers according to internally approved calculation methods for preparations:  
Irritant

- **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

108-88-3	toluene	3
108-10-1	4-methylpentan-2-one	2B
13463-67-7	titanium dioxide	2B
1333-86-4	Carbon black	2B

(Contd. on page 10)



Trade name: 15003-15893 Color Coat Aerosol

(Contd. of page 9)

1330-20-7	xylene	3
100-41-4	ethylbenzene	2B

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

**12 Ecological information**

· **Toxicity**

- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.

· **Behavior in environmental systems:**

- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.

· **Additional ecological information:**

· **General notes:**

Water hazard class 2 (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.

· **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

**13 Disposal considerations**

· **Waste treatment methods**

· **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packagings:**

- **Recommendation:** Disposal must be made according to official regulations.

**14 Transport information**

· **UN-Number**

· **DOT, ADR, IMDG, IATA** UN1950

· **UN proper shipping name**

· **DOT** Aerosols, flammable  
· **ADR** 1950 Aerosols  
· **IMDG** AEROSOLS  
· **IATA** AEROSOLS, flammable

(Contd. on page 11)

Trade name: 15003-15893 Color Coat Aerosol

(Contd. of page 10)

· **Transport hazard class(es)**

· **DOT**



· **Class** 2.1  
· **Label** 2.1

· **ADR**



· **Class** 2 5F Gases  
· **Label** 2.1

· **IMDG, IATA**



· **Class** 2.1  
· **Label** 2.1

· **Packing group**  
· **DOT, ADR, IMDG, IATA** Void

· **Environmental hazards:** Not applicable.

· **Special precautions for user** Warning: Gases  
· **EMS Number:** F-D,S-U  
· **Stowage Code** SW1 Protected from sources of heat.  
SW22 For AEROSOLS with a maximum capacity of 1 litre:  
Category A. For AEROSOLS with a capacity above 1 litre:  
Category B. For WASTE AEROSOLS: Category C, Clear of living  
quarters.  
· **Segregation Code** SG69 For AEROSOLS with a maximum capacity of 1 litre:  
Segregation as for class 9. Stow "separated from" class 1 except for  
division 1.4. For AEROSOLS with a capacity above 1 litre:  
Segregation as for the appropriate subdivision of class 2. For  
WASTE AEROSOLS: Segregation as for the appropriate subdivision  
of class 2.

· **Transport in bulk according to Annex II of  
MARPOL73/78 and the IBC Code** Not applicable.

· **Transport/Additional information:**

· **DOT**  
· **Quantity limitations** On passenger aircraft/rail: 75 kg  
On cargo aircraft only: 150 kg

(Contd. on page 12)



Trade name: 15003-15893 Color Coat Aerosol

(Contd. of page 11)

· <b>ADR</b>	
· <b>Excepted quantities (EQ)</b>	Code: E0 Not permitted as Excepted Quantity
<hr/>	
· <b>IMDG</b>	
· <b>Limited quantities (LQ)</b>	1L
· <b>Excepted quantities (EQ)</b>	Code: E0 Not permitted as Excepted Quantity
· <b>UN "Model Regulation":</b>	UN 1950 AEROSOLS, 2.1

**15 Regulatory information**

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· **Section 355 (extremely hazardous substances):**

None of the ingredient is listed.

· **Section 313 (Specific toxic chemical listings):**

108-88-3	toluene
	Acrylic Resin
108-10-1	4-methylpentan-2-one
78-93-3	butanone
1330-20-7	xylene
67-56-1	methanol
100-41-4	ethylbenzene

· **TSCA (Toxic Substances Control Act):**

67-64-1	acetone
108-88-3	toluene
110-19-0	isobutyl acetate
108-10-1	4-methylpentan-2-one
78-93-3	butanone
763-69-9	ethyl 3-ethoxypropionate
108-65-6	2-methoxy-1-methylethyl acetate
2807-30-9	2-(propyloxy)ethanol
13463-67-7	titanium dioxide
51274-00-1	YELLOW IRON OXIDE
1333-86-4	Carbon black
1330-20-7	xylene
67-56-1	methanol
1332-37-2	Iron oxide
100-41-4	ethylbenzene
108-83-8	2,6-dimethylheptan-4-one
61791-55-7	Amines, N-tallow alkyltrimethylenedi-

(Contd. on page 13)



Trade name: 15003-15893 Color Coat Aerosol

(Contd. of page 12)

7732-18-5	water
-----------	-------

· **TSCA new (21st Century Act) (Substances not listed)**

68476-86-8	Petroleum gases, liquefied, sweetened
------------	---------------------------------------

· **Proposition 65**

· **Chemicals known to cause cancer:**

108-10-1	4-methylpentan-2-one
13463-67-7	titanium dioxide
1333-86-4	Carbon black
1330-20-7	xylene
100-41-4	ethylbenzene

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

108-88-3	toluene
108-10-1	4-methylpentan-2-one
67-56-1	methanol

· **Carcinogenicity categories**

· **EPA (Environmental Protection Agency)**

67-64-1	acetone	I
108-88-3	toluene	II
108-10-1	4-methylpentan-2-one	I
78-93-3	butanone	I
1330-20-7	xylene	I
100-41-4	ethylbenzene	D

· **TLV (Threshold Limit Value established by ACGIH)**

67-64-1	acetone	A4
108-88-3	toluene	A4
13463-67-7	titanium dioxide	A4
1333-86-4	Carbon black	A4
1330-20-7	xylene	A4
100-41-4	ethylbenzene	A3

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

13463-67-7	titanium dioxide
1333-86-4	Carbon black
67-56-1	methanol

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 14)

Trade name: 15003-15893 Color Coat Aerosol

(Contd. of page 13)

· **Hazard pictograms**



· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

toluene  
acetone  
4-methylpentan-2-one  
ethylbenzene

· **Hazard statements**

H222 Extremely flammable aerosol.  
H280 Contains gas under pressure; may explode if heated.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H351 Suspected of causing cancer.  
H361 Suspected of damaging fertility or the unborn child.  
H336 May cause drowsiness or dizziness.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H304 May be fatal if swallowed and enters airways.

· **Precautionary statements**

P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Pressurized container: Do not pierce or burn, even after use.  
P260 Do not breathe dust/fume/gas/mist/vapors/spray.  
P264 Wash thoroughly after handling.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P301+P310 If swallowed: Immediately call a poison center/doctor.  
P321 Specific treatment (see on this label).  
P331 Do NOT induce vomiting.  
P302+P352 If on skin: Wash with plenty of water.  
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
  
P308+P313 IF exposed or concerned: Get medical advice/attention.  
P312 Call a poison center/doctor if you feel unwell.  
P314 Get medical advice/attention if you feel unwell.  
P362+P364 Take off contaminated clothing and wash it before reuse.  
P332+P313 If skin irritation occurs: Get medical advice/attention.  
P337+P313 If eye irritation persists: Get medical advice/attention.  
P403+P233 Store in a well-ventilated place. Keep container tightly closed.  
P405 Store locked up.  
P410+P403 Protect from sunlight. Store in a well-ventilated place.  
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 15)



Trade name: 15003-15893 Color Coat Aerosol

(Contd. of page 14)

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Environment protection department.

· **Contact:** Rita Joiner

· **Date of preparation / last revision** 03/14/2018 / 9

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Aerosol 1: Aerosols – Category 1

Press. Gas: Gases under pressure – Compressed gas

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Carc. 2: Carcinogenicity – Category 2

Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

· **\* Data compared to the previous version altered.**

USA